

Access DB# 103510

## SEARCH REQUEST FORM

Scientific and Technical Information Center

Requester's Full Name: Raymond Alejandro Examiner #: 76895 Date: 09/10/03  
Art Unit: 1745 Phone Number 306-3326 Serial Number: 101079003  
Mail Box and Bldg/Room Location: C Plaza 3, 8 E02 Results Format Preferred (circle): PAPER DISK E-MAIL

If more than one search is submitted, please prioritize searches in order of need.

\*\*\*\*\*

Please provide a detailed statement of the search topic, and describe as specifically as possible the subject matter to be searched. Include the elected species or structures, keywords, synonyms, acronyms, and registry numbers, and combine with the concept or utility of the invention. Define any terms that may have a special meaning. Give examples or relevant citations, authors, etc, if known. Please attach a copy of the cover sheet, pertinent claims, and abstract.

Title of Invention: Galvanic element having at least one lithium-intercalating electrodeInventors (please provide full names): Huang et alEarliest Priority Filing Date: 02/20/02 DE 101 08 695 2/23/01

\*For Sequence Searches Only\* Please include all pertinent information (parent, child, divisional, or issued patent numbers) along with the appropriate serial number.

US 2002 0119 376

Please, refer to claims 1-10 (attached copy) for subject matter to be searched.

BEST AVAILABLE COPY

## STAFF USE ONLY

	Type of Search	Vendors and cost where applicable
Searcher: <u>SC</u>	NA Sequence (#) _____	STN _____
Searcher Phone #: _____	AA Sequence (#) _____	Dialog _____
Searcher Location: _____	Structure (#) _____	Questel/Orbit _____
Date Searcher Picked Up: <u>9/11/03</u>	Bibliographic <u>/</u>	Dr. Link _____
Date Completed: <u>9/11/03</u>	Litigation _____	Lexis/Nexis _____
Searcher Prep & Review Time: <u>120</u>	Fulltext _____	Sequence Systems _____
Clerical Prep Time: _____	Patent Family _____	WWW/Internet _____
Online Time: <u>120</u>	Other _____	Other (specify) _____

=> file hca

FILE 'HCA' ENTERED AT 11:59:25 ON 11 SEP 2003

USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.

PLEASE SEE "HELP USAGETERMS" FOR DETAILS.

COPYRIGHT (C) 2003 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 4 Sep 2003 VOL 139 ISS 11

FILE LAST UPDATED: 4 Sep 2003 (20030904/ED)

This file contains CAS Registry Numbers for easy and accurate substance identification.

=> d his nofile

(FILE 'HOME' ENTERED AT 10:46:23 ON 11 SEP 2003)

FILE 'HCA' ENTERED AT 10:46:36 ON 11 SEP 2003

E US20020119376/PN

L1 1 SEA ABB=ON PLU=ON US2002119376/PN  
D SCAN  
SEL L1 RN

FILE 'REGISTRY' ENTERED AT 10:47:07 ON 11 SEP 2003

L2 23 SEA ABB=ON PLU=ON (12190-79-3/BI OR 12597-68-1/BI OR  
25038-59-9/BI OR 7429-90-5/BI OR 7439-89-6/BI OR 7439-93-2/BI  
OR 7440-02-0/BI OR 7440-22-4/BI OR 7440-31-5/BI OR 7440-32-6/BI  
OR 7440-36-0/BI OR 7440-44-0/BI OR 7440-47-3/BI OR 7440-48-4/B  
I OR 7440-50-8/BI OR 7440-62-2/BI OR 7440-66-6/BI OR 7440-69-9/  
BI OR 7440-74-6/BI OR 7782-42-5/BI OR 84-74-2/BI OR 9011-17-0/B  
I OR 95-14-7/BI)

L3 1 SEA ABB=ON PLU=ON L2 AND AYS/CI  
D SCAN

L4 1 SEA ABB=ON PLU=ON L2 AND TIS/CI  
D SCAN  
D SCAN L3  
D SCAN L4

L5 21 SEA ABB=ON PLU=ON L2 NOT (L3 OR L4)  
D SCAN

L6 15 SEA ABB=ON PLU=ON L5 AND 1-10/M

L7 6 SEA ABB=ON PLU=ON L5 NOT L6  
D SCAN

L8 2 SEA ABB=ON PLU=ON L2 AND LITHIUM#  
D SCAN  
E LITHIUM/CN

L9 1 SEA ABB=ON PLU=ON LITHIUM/CN

FILE 'HCA' ENTERED AT 10:57:13 ON 11 SEP 2003

L10 767351 SEA ABB=ON PLU=ON ANOD? OR CATHOD? OR ELECTRODE?  
L11 342051 SEA ABB=ON PLU=ON L9 OR LI OR LITHIUM#  
L12 34153 SEA ABB=ON PLU=ON L11(2A)USE?  
L13 22091 SEA ABB=ON PLU=ON L10(2A)L11  
L14 7006 SEA ABB=ON PLU=ON L13 AND L12  
L15 34932 SEA ABB=ON PLU=ON INTERCALAT? OR INTER(W)CALAT?  
L16 1513 SEA ABB=ON PLU=ON L14 AND L15

FILE 'LCA' ENTERED AT 11:00:23 ON 11 SEP 2003

L17 15976 SEA ABB=ON PLU=ON ALUMINUM# OR AL OR IRON# OR FE OR NICKEL#  
OR NI OR SILVER# OR AG OR TIN# OR SN OR TITANIUM# OR TI OR  
ANTIMONY# OR SB OR CHROMIUM# OR CR OR COBALT# OR CO OR COPPER#  
OR CU OR VANADIUM# OR V OR BISMUTH# OR BI OR ZINC# OR ZN OR  
INDIUM# OR IN  
L18 7671 SEA ABB=ON PLU=ON FILM? OR THINFILM? OR LAYER? OR OVERLAY?  
OR OVERLAID? OR LAMIN? OR LAMEL? OR MULTILAYER? OR SHEET? OR  
LEAF? OR FOIL? OR COAT? OR TOPCOAT? OR OVERCOAT? OR VENEER? OR  
SHEATH? OR COVER? OR ENVELOP? OR ENCASE? OR ENWRAP? OR  
OVERSPREAD?  
L19 106 SEA ABB=ON PLU=ON CRYSTALLIT?  
L20 4562 SEA ABB=ON PLU=ON CRYSTAL?

FILE 'HCA' ENTERED AT 11:06:25 ON 11 SEP 2003

D L1 ALL

FILE 'LCA' ENTERED AT 11:06:48 ON 11 SEP 2003

L21 32336 SEA ABB=ON PLU=ON PRODUC? OR PROD# OR GENERAT? OR MANUF? OR  
MFR# OR CREAT? OR FORM## OR FORMING# OR FORMAT? OR MAKE# OR  
MADE# OR MAKIN# OR FABRICAT? OR SYNTHESI? OR PREPAR? OR PREP#  
L22 10068 SEA ABB=ON PLU=ON SUBSTRAT? OR SURFACE? OR BASE# OR SUBSTRUCT  
? OR UNDERSTRUCTUR? OR UNDERLAY?  
L23 1804 SEA ABB=ON PLU=ON DEPOSIT?

FILE 'REGISTRY' ENTERED AT 11:18:23 ON 11 SEP 2003

D SCAN L6  
D SCAN L7

L24 1 SEA ABB=ON PLU=ON L7 AND 1H-BENZOTRIAZOLE

FILE 'HCA' ENTERED AT 11:19:37 ON 11 SEP 2003

L25 1593650 SEA ABB=ON PLU=ON L6  
L26 670378 SEA ABB=ON PLU=ON (L25 OR L17) (2A)USE?  
L27 728290 SEA ABB=ON PLU=ON DEPOSIT?  
L28 38755 SEA ABB=ON PLU=ON CRYSTALLIT?  
L29 1747254 SEA ABB=ON PLU=ON CRYSTAL?  
L30 119033 SEA ABB=ON PLU=ON L27(2A)L17  
L31 59063 SEA ABB=ON PLU=ON L27(2A) (ALLOY? OR AMALGAM? OR METAL?)  
L32 161619 SEA ABB=ON PLU=ON L27(2A) (L18 OR FILM#)  
L33 23591 SEA ABB=ON PLU=ON L32 AND L26  
L34 90 SEA ABB=ON PLU=ON L14 AND L33  
L35 90 SEA ABB=ON PLU=ON L34 AND L18  
L36 5 SEA ABB=ON PLU=ON L35 AND L28  
L37 15 SEA ABB=ON PLU=ON L35 AND L20  
L38 189 SEA ABB=ON PLU=ON CHROMATIZ? OR CHROMATIS?  
L39 14247 SEA ABB=ON PLU=ON L24 OR BENZOTRIAZOLE?  
L40 0 SEA ABB=ON PLU=ON L35 AND L38  
L41 1 SEA ABB=ON PLU=ON L35 AND L39  
D SCAN

FILE 'STNGUIDE' ENTERED AT 11:27:18 ON 11 SEP 2003

FILE 'HCA' ENTERED AT 11:31:35 ON 11 SEP 2003

L42 64 SEA ABB=ON PLU=ON L34 AND L22  
L43 770790 SEA ABB=ON PLU=ON CHROMAT?  
L44 2 SEA ABB=ON PLU=ON L42 AND (L43 OR L39)  
L45 12666 SEA ABB=ON PLU=ON L31 AND L26  
L46 112 SEA ABB=ON PLU=ON L45 AND L13  
L47 90 SEA ABB=ON PLU=ON L34 AND L13  
L48 64 SEA ABB=ON PLU=ON L47 AND L22  
L49 10 SEA ABB=ON PLU=ON L46 AND (L19 OR L20)  
L50 362 SEA ABB=ON PLU=ON L32 AND L13  
L51 159 SEA ABB=ON PLU=ON L50 AND L26  
L52 111 SEA ABB=ON PLU=ON L51 AND L22  
L53 2 SEA ABB=ON PLU=ON L52 AND L43  
L54 0 SEA ABB=ON PLU=ON L52 AND L39  
L55 42206 SEA ABB=ON PLU=ON ?TRIAZOLE?  
L56 0 SEA ABB=ON PLU=ON L52 AND L55  
L57 15526 SEA ABB=ON PLU=ON L52 AND CORROS? OR CORROD?  
L58 1 SEA ABB=ON PLU=ON L52 AND (CORROS? OR CORROD?)  
L59 24 SEA ABB=ON PLU=ON L52 AND (L19 OR L20)  
L60 4 SEA ABB=ON PLU=ON L52 AND L19  
L61 9 SEA ABB=ON PLU=ON L36 OR L41 OR L53 OR L58 OR L60  
L62 6 SEA ABB=ON PLU=ON L61 AND L19  
L63 3 SEA ABB=ON PLU=ON L59 AND L15  
L64 19 SEA ABB=ON PLU=ON L52 AND L15  
L65 1 SEA ABB=ON PLU=ON L64 AND L19  
L66 6 SEA ABB=ON PLU=ON L62 OR L65  
L67 19 SEA ABB=ON PLU=ON L64 AND L13  
L68 41 SEA ABB=ON PLU=ON L37 OR L49 OR L64 OR L67  
L69 35 SEA ABB=ON PLU=ON L68 NOT L61  
L70 34 SEA ABB=ON PLU=ON L69 AND 1907-2002/PY, PRY  
L71 31 SEA ABB=ON PLU=ON L69 AND 1907-2001/PY, PRY  
L72 0 SEA ABB=ON PLU=ON L71 NOT L70  
L73 3 SEA ABB=ON PLU=ON L70 NOT L71

FILE 'JAPIO' ENTERED AT 11:42:52 ON 11 SEP 2003

L74 461940 SEA ABB=ON PLU=ON ELECTROD? OR ANOD? OR CATHOD?  
L75 28174 SEA ABB=ON PLU=ON LI OR LITHIUM#  
L76 4620 SEA ABB=ON PLU=ON L74(3A)L75  
L77 84 SEA ABB=ON PLU=ON L76 AND L15  
L78 3 SEA ABB=ON PLU=ON L77 AND L19  
L79 76 SEA ABB=ON PLU=ON L77 AND L17  
L80 37660 SEA ABB=ON PLU=ON L23(2A)(L17 OR METAL? OR ALLOY? OR STEEL?)  
  
L81 3 SEA ABB=ON PLU=ON L77 AND L80  
L82 93 SEA ABB=ON PLU=ON L76 AND L80  
L83 50 SEA ABB=ON PLU=ON L82 AND L22  
L84 24 SEA ABB=ON PLU=ON (L77 OR L79 OR L82 OR L83) AND L20  
L85 30032 SEA ABB=ON PLU=ON H01M004?/IC  
L86 125 SEA ABB=ON PLU=ON (L77 OR L79 OR L82 OR L83) AND L85  
L87 21 SEA ABB=ON PLU=ON L86 AND L20  
L88 6 SEA ABB=ON PLU=ON (L78 OR L81 ) AND L86  
L89 18 SEA ABB=ON PLU=ON L87 NOT L88

FILE 'WPIX' ENTERED AT 11:51:01 ON 11 SEP 2003

L90 592465 SEA ABB=ON PLU=ON L74 OR ELECTRODE#  
L91 61136 SEA ABB=ON PLU=ON L75 OR LI  
L92 6900 SEA ABB=ON PLU=ON L90(2A)L91  
L93 287 SEA ABB=ON PLU=ON L92 AND L15

L94 9445 SEA ABB=ON PLU=ON L90(4A)L91  
L95 373 SEA ABB=ON PLU=ON L94 AND L15  
L96 43537 SEA ABB=ON PLU=ON L23(2A)(L17 OR METAL? OR ALLOY? OR STEEL?)  
  
L97 93 SEA ABB=ON PLU=ON L94 AND L96  
L98 57 SEA ABB=ON PLU=ON L97 AND L22  
L99 36328 SEA ABB=ON PLU=ON H01M004?/IC  
L100 39 SEA ABB=ON PLU=ON L98 AND L99  
L101 1 SEA ABB=ON PLU=ON L100 AND L19  
L102 6 SEA ABB=ON PLU=ON L100 AND L20  
L103 6828 SEA ABB=ON PLU=ON CHROMATIZ? OR CHROMATIS? OR BENZOTRIAZOL?  
L104 1 SEA ABB=ON PLU=ON L100 AND L103  
L105 2 SEA ABB=ON PLU=ON L100 AND CORROS?  
L106 72679 SEA ABB=ON PLU=ON L23(2A)(L18 OR FILM#)  
L107 21 SEA ABB=ON PLU=ON L100 AND L106  
L108 7 SEA ABB=ON PLU=ON L101 OR L102 OR L104 OR L105  
L109 18 SEA ABB=ON PLU=ON L107 NOT L108

=> d L66 1-6 cbib abs hitind hitrn

L66 ANSWER 1 OF 6 HCA COPYRIGHT 2003 ACS on STN

138:128834 Enhancement of luminance and life in electroluminescent devices.  
Beatty, Paul Hanlon James (Lite Array Inc., USA). U.S. Pat. Appl. Publ.  
US 2003020397 A1 20030130, 15 pp. (English). CODEN: USXXCO.  
APPLICATION: US 2002-185749 20020628. PRIORITY: US 2001-PV301995  
20010628.

AB An electroluminescent device for improving luminance by reducing light trapping caused by total internal reflection is described comprising a 1st electrode **layer**, a 2nd electrode **layer**, and a light-emitting **layer** disposed between the 1st and 2nd electrode **layers**, wherein the light-emitting **layer** includes a polycryst. or amorphous material from which light can be trapped by total internal reflection until reaching a region of **crystallite** capable of scattering light. An electroluminescent device having a plurality of **layers deposited** on a viewing **surface**, is also described which comprise a light-emitting means wherein the light-emitting means includes the light-scattering means which is at least one **crystallite** within the light-emitting means; a light-scattering means for increasing a luminance of the device, wherein the light-scattering means is a gap within a **layer** of the device wherein the gap includes two sidewalls positioned at an angle; and a conducting means for establishing a voltage across the light-emitting means, wherein the conducting means includes the light-scattering means which is a roughened **surface** of a **layer** within the device. Methods of fabricating the devices are also described.

IC ICM H05B033-22

NCL 313503000

CC 73-11 (Optical, Electron, and Mass Spectroscopy and Other Related Properties)

Section cross-reference(s): 74, 76

IT 123847-85-8, NPD

RL: DEV (Device component use); USES (Uses)

(NPD, hole transport **layer**; electroluminescent device having improved luminance)

IT 37271-44-6

RL: DEV (Device component use); USES (Uses)

- (cathode **layer**; electroluminescent device having improved luminance)
- IT 132614-63-2, Silicon nitride oxide (SiNO)  
RL: DEV (Device component use); USES (Uses)  
(dielec. **layer**; electroluminescent device having improved luminance)
- IT 7440-47-3, **Chromium, uses**  
RL: DEV (Device component use); USES (Uses)  
(electrode with CrO; electroluminescent device having improved luminance)
- IT 7429-90-5, **Aluminum, uses** 7789-24-4,  
**Lithium** fluoride, **uses** 50926-11-9, Indium tin oxide  
RL: DEV (Device component use); USES (Uses)  
(**electrode**; electroluminescent device having improved luminance)
- IT 147-14-8, Copper phthalocyanine  
RL: DEV (Device component use); USES (Uses)  
(hole injection **layer**; electroluminescent device having improved luminance)
- IT 1314-98-3, **Zinc** sulfide (**ZnS**), **uses**  
2085-33-8, AlQ3  
RL: DEV (Device component use); USES (Uses)  
(luminescent **layer**; electroluminescent device having improved luminance)
- IT 7440-47-3, **Chromium, uses**  
RL: DEV (Device component use); USES (Uses)  
(electrode with CrO; electroluminescent device having improved luminance)
- IT 7429-90-5, **Aluminum, uses**  
RL: DEV (Device component use); USES (Uses)  
(**electrode**; electroluminescent device having improved luminance)
- L66 ANSWER 2 OF 6 HCA COPYRIGHT 2003 ACS on STN
- 137:203949 Galvanic element with a **lithium** intercalating **electrode**. Haug, Peter; Birke, Peter; Holl, Konrad; Ilic, Dejan (Microbatterie G.m.b.H., Germany). Eur. Pat. Appl. EP 1235286 A2 20020828, 6 pp. DESIGNATED STATES: R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, SI, LT, LV, FI, RO, MK, CY, AL, TR. (German). CODEN: EPXXDW. APPLICATION: EP 2002-1556 20020123. PRIORITY: DE 2001-10108695 20010223.
- AB This galvanic element has a **lithium** intercalating **electrode** with electrochem. active material on a **foil** -like metallic conductor. The conductor is **coated** with electrochem. **deposited** crystals of another metal or of the same metal as the conductor. This **coating** increases the contact area and reduces the transition resistance of the active material. The metal support may be Al, Cu, V, Ti, Cr, Fe, Ni, Co, alloys of these metals, or a stainless steel. The deposited metal may be Cu, V, Ti, Cr, Fe, Ni, Co, Zn, Sn, In, Sb, Bi, Ag or alloys of these metals. The crystal size of the electrochem. deposited material is 1-10 .mu.m and there is preferably only 3 **deposited** cryst. layers.
- IC ICM H01M004-02  
ICS H01M004-66
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST battery **anode cathode lithium** intercalating **electrode metal crystallite**
- IT Battery anodes  
Battery cathodes  
Electric capacitance

Film electrodes  
Grain size  
Laminated materials  
(galvanic element with a lithium intercalating electrode)  
IT Alloys, uses  
Polyesters, uses  
RL: DEV (Device component use); USES (Uses)  
(galvanic element with a lithium intercalating electrode)  
IT Chromating  
(treatment of electrode; galvanic element with a lithium intercalating electrode)  
IT 7782-42-5, Graphite, uses  
RL: DEV (Device component use); USES (Uses)  
(MCMB or KS 6; galvanic element with a lithium intercalating electrode)  
IT 9011-17-0, Powerflex  
RL: DEV (Device component use); USES (Uses)  
(Powerflex; galvanic element with a lithium intercalating electrode)  
IT 7440-44-0, Super P, uses  
RL: DEV (Device component use); USES (Uses)  
(activated; galvanic element with a lithium intercalating electrode)  
IT 95-14-7, 1H-Benzotriazole  
RL: DEV (Device component use); USES (Uses)  
(electrode coating; galvanic element with a lithium intercalating electrode)  
IT 84-74-2, Dibutyl phthalate 7429-90-5, Aluminum, uses 7439-89-6, Iron, uses 7439-93-2, Lithium, uses 7440-02-0, Nickel, uses 7440-22-4, Silver, uses 7440-31-5, Tin, uses 7440-32-6, Titanium, uses 7440-36-0, Antimony, uses 7440-47-3, Chromium, uses 7440-48-4, Cobalt, uses 7440-50-8, Copper, uses 7440-62-2, Vanadium, uses 7440-66-6, Zinc, uses 7440-69-9, Bismuth, uses 7440-74-6, Indium, uses 12190-79-3, Cobalt lithium oxide (CoLiO<sub>2</sub>) 12597-68-1, Stainless steel, uses 25038-59-9, Mylar, uses  
RL: DEV (Device component use); USES (Uses)  
(galvanic element with a lithium intercalating electrode)  
IT 95-14-7, 1H-Benzotriazole  
RL: DEV (Device component use); USES (Uses)  
(electrode coating; galvanic element with a lithium intercalating electrode)  
IT 7429-90-5, Aluminum, uses 7439-89-6, Iron, uses 7439-93-2, Lithium, uses 7440-02-0, Nickel, uses 7440-22-4, Silver, uses 7440-31-5, Tin, uses 7440-32-6, Titanium, uses 7440-36-0, Antimony, uses 7440-47-3, Chromium, uses 7440-48-4, Cobalt, uses 7440-50-8, Copper, uses 7440-62-2, Vanadium, uses 7440-66-6, Zinc, uses 7440-69-9,

**Bismuth, uses 7440-74-6, Indium,  
uses**

RL: DEV (Device component use); USES (Uses)  
(galvanic element with a **lithium** intercalating  
**electrode**)

L66 ANSWER 3 OF 6 HCA COPYRIGHT 2003 ACS on STN

136:376315 Electrodeposited tin **coating** as negative  
**electrode** material for **lithium-ion** battery in room  
temperature molten salt. Fung, Y. S.; Zhu, D. R. (Department of  
Chemistry, The University of Hong Kong, Hong Kong, Peop. Rep. China).  
Journal of the Electrochemical Society, 149(3), A319-A324 (English) 2002.  
CODEN: JESOAN. ISSN: 0013-4651. Publisher: Electrochemical Society.

AB A new room temp. molten salt (RTMS) [1-methyl-3-  
ethylimidazolium/AlCl<sub>3</sub>/SnCl<sub>2</sub> (3:2:0.5)] was developed for depositing tin  
on a copper electrode. Different tin **crystallites** were  
deposited at different temps., giving widely different performances of the  
assembled lithium cell [Sn (Cu)/LiCl buffered MEICl-AlCl<sub>3</sub> RTMS/lithium].  
Tin **film deposited** at 50.degree. or higher gave a more  
desirable crystal structure and an improved performance than **films**  
obtained at lower temps. Both cyclic voltammetry and galvanostatic  
cycling show the formation of three major lithium-tin alloy phases  
corresponding to the phase transition of LiSn/Li<sub>7</sub>Sn<sub>3</sub>, Li<sub>13</sub>Sn<sub>5</sub>/Li<sub>7</sub>Sn<sub>2</sub>, and  
Li<sub>7</sub>Sn<sub>2</sub>/Li<sub>22</sub>Sn<sub>5</sub>. Increases in the charging and discharging capacities were  
found with the deposition of higher lithium-rich tin alloys, though at the  
degrdn. of the irreversible capacity at the first cycle. The discharging  
capacity decreased rapidly, producing loose, expanded, and irregular  
**crystallites** upon cycling at a high c.d. (cd) (1.0 mA/cm<sup>2</sup>).  
However, an av. capacity of 140 mAh/g, coulombic efficiency around 85%,  
and more than 200 cycles were obtained at a low cd (0.4 mA/cm<sup>2</sup>). The  
improvement is attributed to the deposition of small and regular tin  
**crystallites** that allows reversible insertion and removal of  
lithium from a more stable crystal structure without a significant vol.  
change during cycling.

CC 72-8 (Electrochemistry)

Section cross-reference(s): 52, 56

ST tin **electrodeposit** lithium battery **electrode**  
room temp molten salt

IT Battery electrodes

**Coating** materials

Secondary batteries

(electrodeposited tin **coating** as neg. **electrode**

material for **lithium-ion** battery in room temp. molten salt)

IT Salts, **uses**

RL: NUU (Other use, unclassified); USES (Uses)

(molten; electrodeposited tin **coating** as neg.

**electrode** material for **lithium-ion** battery in room  
temp. molten salt)

IT Electric capacitance

(of tin **coated** electrodes in 1-methyl-3-  
ethylimidazolium/AlCl<sub>3</sub>/SnCl<sub>2</sub> electrolyte buffered with LiCl)

IT Electrodeposition

(of tin **coating** as neg. **electrode** material for  
**lithium-ion** battery in room temp. molten salt)

IT **Surface** structure

(of tin **coating** as neg. **electrode** material for  
**lithium-ion** battery in room temp. molten salt during  
charge-discharge cycling)

IT 7447-41-8, **Lithium** chloride, **uses**

RL: NUU (Other use, unclassified); USES (Uses)

- (cyclic voltammetry of copper pure and tin coated electrodes in 1-methyl-3-ethylimidazolium/AlCl<sub>3</sub>/SnCl<sub>2</sub> electrolyte buffered with)
- IT 65039-03-4, 1-Methyl-3-ethylimidazolium  
RL: NUU (Other use, unclassified); USES (Uses)  
(electrodeposited tin coating as neg. electrode material for lithium-ion battery in room temp. molten salt)
- IT 7446-70-0, Aluminum chloride, uses  
RL: NUU (Other use, unclassified); USES (Uses)  
(electrodeposited tin coating as neg. electrode material for lithium-ion battery in room temp. molten salt contg.)
- IT 7439-93-2, Lithium, uses  
RL: CPS (Chemical process); DEV (Device component use); PEP (Physical, engineering or chemical process); RCT (Reactant); PROC (Process); RACT (Reactant or reagent); USES (Uses)  
(formation with tin electrodeposited on copper in room temp. molten salt lithium cell)
- IT 7772-99-8, Tin dichloride, reactions  
RL: CPS (Chemical process); PEP (Physical, engineering or chemical process); RCT (Reactant); PROC (Process); RACT (Reactant or reagent)  
(of tin coating as neg. electrode material for lithium-ion battery in room temp. molten salt contg.)
- IT 7439-93-2, Lithium, uses  
RL: CPS (Chemical process); DEV (Device component use); PEP (Physical, engineering or chemical process); RCT (Reactant); PROC (Process); RACT (Reactant or reagent); USES (Uses)  
(formation with tin electrodeposited on copper in room temp. molten salt lithium cell)
- L66 ANSWER 4 OF 6 HCA COPYRIGHT 2003 ACS on STN
- 127:7048 Ultrahigh reversible capacity carbon-lithium anode material. Yazami, R.; Deschamps, M. (LIESG, St. Martin-d'Heres, 38402, Fr.). Progress in Batteries & Battery Materials, 15, 161-167 (English) 1996. CODEN: PBBMEF. Publisher: ITE-JEC Press.
- AB We have used a soft type carbon heat treated at a temp. below 1000.degree. in polymer electrolyte-based Li batteries. An unexpected ultrahigh capacity up to 1900 mA-h/g is obtained. A method involving the epitaxial multilayer deposit on the external a,b layers and on the edges of the carbon crystallites is proposed to describe these results.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST battery carbon lithium anode material
- IT Coal tar pitch  
RL: RCT (Reactant); RACT (Reactant or reagent)  
(carbon precursor; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT Battery anodes  
(ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7439-93-2, Lithium, uses  
RL: DEV (Device component use); USES (Uses)  
(carbon intercalated with; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7440-44-0, Carbon, uses  
RL: DEV (Device component use); USES (Uses)  
(lithium-intercalated; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 39448-96-9, Graphite-lithium  
RL: DEV (Device component use); USES (Uses)

- (ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7439-93-2, **Lithium, uses**  
RL: DEV (Device component use); USES (Uses)  
(carbon **intercalated** with; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- L66 ANSWER 5 OF 6 HCA COPYRIGHT 2003 ACS on STN
- 125:70186 Molten salt electrolytes for electrodeposition of CdTe **films**  
. Raza, Arif; Engelken, Robert; Kemp, Brandon; Siddiqui, Arees; Mustafa, Omer (Department Engineering, Arkansas State University, State University, AR, 72467, USA). Proceedings of the Arkansas Academy of Science, 49, 143-148 (English) 1995. CODEN: AKASAO. ISSN: 0097-4374. Publisher: Arkansas Academy of Science.
- AB The authors report preliminary study of several molten salt electrolytes contg. CdCl<sub>2</sub> and TeCl<sub>4</sub> for the electrodeposition of CdTe **films** at temps. well above (>250.degree.) those used with aq. and org. electrolytes. These high temps. have potential to dramatically increase the **crystallite** size (C.Poole, et al., 1994), as is important for optoelectronic device applications of CdTe, a leading II-VI semiconductor. This paper will survey the results obtained with electrolytes such as B<sub>2</sub>O<sub>3</sub>/HBO<sub>2</sub> (m.p. .apprxeq. 230.degree.), NaCH<sub>3</sub>COO (m.p. .apprxeq. 324.degree.), ZnCl<sub>2</sub> (m.p. .apprxeq. 283.degree.), and LiCl/KCl (m.p. .apprxeq. 350.degree.), with an emphasis on the latter two. Key material to be presented includes (1) voltammetric data for the solns., (2) x-ray diffractometry data for **deposited films**, (3) a discussion of the numerous practical problems assocd. with high temp. electrochem., esp. in corrosive, volatile systems, and (4) emphasis of the value of an operationally feasible high temp. plating system to the com. viability of electrodeposited semiconductor **films**.
- CC 72-5 (Electrochemistry)  
Section cross-reference(s): 76
- ST molten salt electrolyte electrodeposition cadmium telluride;  
**lithium** potassium chloride **electrodeposition** cadmium telluride
- IT Electrodeposition and Electroplating  
(molten salt electrolytes for electrodeposition of CdTe **films**)
- IT 127-09-3, Sodium acetate 1303-86-2, Boron oxide b<sub>2</sub>o<sub>3</sub>, uses 7447-40-7, Potassium chloride (KCl), uses 7447-41-8, **Lithium** chloride (LiCl), **uses** 7646-85-7, **Zinc** chloride, **uses** 13460-50-9, Boric acid hbo<sub>2</sub>  
RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)  
(molten salt electrolytes contg. CdCl<sub>2</sub> and TeCl<sub>4</sub> for electrodeposition of CdTe **films**)
- IT 10026-07-0, Tellurium chloride (TeCl<sub>4</sub>) 10108-64-2, Cadmium chloride (CdCl<sub>2</sub>)  
RL: RCT (Reactant); RACT (Reactant or reagent)  
(molten salt electrolytes contg. CdCl<sub>2</sub> and TeCl<sub>4</sub> for electrodeposition of CdTe **films**)
- IT 1306-25-8, Cadmium telluride (CdTe), properties  
RL: PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process)  
(molten salt electrolytes for electrodeposition of CdTe **films**)

L66 ANSWER 6 OF 6 HCA COPYRIGHT 2003 ACS on STN

120:176368 Reversible electrodeposition of bismuth thin films for flat panel display applications. Howard, Bruce M.; Ziegler, John P.; McKee, Max;

Tornberg, Neal; Caudy, Kim (McDonnell Douglas Technol. Inc., San Diego, CA, 92037, USA). Proceedings - Electrochemical Society, 93-26(Proceedings of the Symposium on Electrochemically Deposited Thin Films, 1993), 353-61 (English) 1993. CODEN: PESODO. ISSN: 0161-6374.

- AB A new type of electrochromic display technol. **based** on reversible electrodeposition is being investigated for possible use in military display systems. The reversible electrodeposition of thin metal films of bismuth was characterized in aq. soln. using traditional 3-electrode electrochem. cells and solid state (gel) electrochem. cells. The solid state cell structure consisted of transparent conducting working electrode/bismuth-contg. gel electrolyte/porous carbon plastic counter electrode. Application of a DC bias (-1.5 V) to the working electrode resulted in the deposition of thin bismuth films and a resulting change in optical d. A reverse bias (+1.5 V) was applied to remove the bismuth deposit (cell erasure). By varying the thickness of the bismuth deposit between 0 and 6 .mu.m the visible reflectance (gray shade) of the device could be controlled. Thin **film bismuth deposition** was initiated by monolayer (UPD) formation followed by bismuth island **crystallite** formation and growth. The morphol. of the bismuth deposit was found to have a large, irregular **surface** area.
- CC 72-8 (Electrochemistry)  
Section cross-reference(s): 74
- ST bismuth reversible electrodeposition electrochromic display device;  
**surface** structure reflection spectrum bismuth electrodeposit
- IT **Surface** structure  
(of bismuth electrodeposits, from gel media)
- IT 7447-39-4, **Copper** dichloride, **uses** 7550-35-8,  
**Lithium** bromide 7787-60-2, Bismuth trichloride 9004-62-0,  
Hydroxyethylcellulose 13463-67-7, **Titanium** oxide, **uses**  
RL: USES (Uses)  
(**electrodeposition** of **bismuth** from gel media  
contg., for electrochromic display devices)
- IT **7440-69-9, Bismuth, uses**  
RL: PEP (Physical, engineering or chemical process); PROC (Process)  
(reversible electrodeposition of, for electrochromic display devices)
- IT **7440-69-9, Bismuth, uses**  
RL: PEP (Physical, engineering or chemical process); PROC (Process)  
(reversible electrodeposition of, for electrochromic display devices)

=> d L63 1-3 cbib abs hitind hitrn

L63 ANSWER 1 OF 3 HCA COPYRIGHT 2003 ACS on STN

- 127:7048 Ultrahigh reversible capacity carbon-lithium **anode** material. Yazami, R.; Deschamps, M. (LIESG, St. Martin-d'Heres, 38402, Fr.). Progress in Batteries & Battery Materials, 15, 161-167 (English) 1996. CODEN: PBBMEF. Publisher: ITE-JEC Press.
- AB We have used a soft type carbon heat treated at a temp. below 1000.degree. in polymer electrolyte-**based** Li batteries. An unexpected ultrahigh capacity up to 1900 mA-h/g is obtained. A method involving the epitaxial **multilayer deposit** on the external a,b layers and on the edges of the carbon **crystallites** is proposed to describe these results.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST battery carbon **lithium anode** material
- IT Coal tar pitch  
RL: RCT (Reactant); RACT (Reactant or reagent)  
(carbon precursor; ultrahigh reversible capacity carbon-lithium **anode** materials for batteries)
- IT Battery anodes

- (ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7439-93-2, Lithium, **uses**  
RL: DEV (Device component use); USES (Uses)  
(carbon **intercalated** with; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7440-44-0, Carbon, **uses**  
RL: DEV (Device component use); USES (Uses)  
(lithium-**intercalated**; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 39448-96-9, Graphite-lithium  
RL: DEV (Device component use); USES (Uses)  
(ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- IT 7439-93-2, Lithium, **uses**  
RL: DEV (Device component use); USES (Uses)  
(carbon **intercalated** with; ultrahigh reversible capacity carbon-lithium anode materials for batteries)
- L63 ANSWER 2 OF 3 HCA COPYRIGHT 2003 ACS on STN
- 123:118408 Vanadium pentoxide gels from liquid **crystals** to lithium batteries. Livage, J.; Baffier, N.; Pereira-Ramos, J. P.; Davidson, P. (Chim. Matiere Condensee, Univ. P. M. Curie, Paris, 75252, Fr.). Materials Research Society Symposium Proceedings, 369(Solid State Ionics IV), 179-90 (English) 1995. CODEN: MRSPDH. ISSN: 0272-9172. Publisher: Materials Research Society.
- AB Vanadium pentoxide gels V2O5.nH2O are formed via the condensation of vanadic acid in aq. solns. They exhibit both ionic and electronic cond. and could therefore be used as **cathode** materials in **lithium** batteries or electrochromic display devices. The polymn. process leads to ribbon-like vanadium pentoxide particles. In a given range of concn., sols and gels exhibit a homogeneous lyotropic nematic phase in which the ribbons align in the same direction. Ordered fluid phases are thus obtained leading to oriented **films** when **deposited** onto flat **substrates**. Moreover, mixed oxides MxV2O5 (M = Na+, K+, Ba2+, Al3+, Fe3+,...) exhibiting some preferred orientation are obtained via ion exchange. These compds. exhibit improved electrochem. properties (specific capacity, cycling properties) compared to usual mixed oxides prepd. via solid state reactions.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 72, 74
- ST **lithium** battery **cathode** vanadium pentoxide gel;  
electrochromic display device vanadium pentoxide gel
- IT Cathodes  
(battery, vanadium pentoxide gels from liq. **crystals** to lithium batteries)
- IT Inclusion reaction  
(**intercalation**, electrochem., electrochem. insertion of lithium in vanadium pentoxide gels for lithium batteries)
- IT 1314-62-1, **Vanadium** pentoxide, **uses**  
RL: DEV (Device component use); USES (Uses)  
(**vanadium** pentoxide gels from liq. **crystals** to lithium batteries)
- L63 ANSWER 3 OF 3 HCA COPYRIGHT 2003 ACS on STN
- 110:196330 Behavior of the negative and positive electrodes in an aprotic secondary lithium cell. Wiesener, K.; Eckoldt, U.; Muller, J.; Schneider, W.; Rahner, D. (Dep. Chem., Dresden Univ. Technol., Dresden, 8027, Ger. Dem. Rep.). Bulletin of Electrochemistry, 5(1), 23-7 (English) 1989.. CODEN: BUELE6. ISSN: 0256-1654.

- AB The performance of **Li anodes** was affected by Li deposition and dissoln. i.e. the formation and removal of **surface** layers related to electrolyte and side reactions, as indicated by studies by Li and **Li-Al anodes** in org. solvent electrolyte. The cycling efficiency of V2O5 cathodes was detd. by **cryst.** structure changes; .ltoreq. 3.1 V, the cycling reaction (i.e. **Li intercalation**) was reversible, but when the discharge voltage reached the 2nd plateau, .ltoreq.2.0 V, irreversible lattice changes occurred and the cycling efficiency deteriorated.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 72
- ST **lithium anode surface** layer cycling;  
vanadium oxide cathode cycleing performance; **intercalation**  
lithium vanadium oxide reversibility; battery **intercalation**  
lithium vanadium oxide
- IT Electric resistance  
(of **lithium anode surface** layer, cycling  
efficiency in relation to)
- IT Electrolytic polarization  
(of lithium, **surface layer deposition**  
-dissoln. during, cycling efficiency in relation to)
- IT **Anodes**  
(battery, **lithium**, cycling efficiency of, **surface**  
layer formation-dissoln. effect on)
- IT Cathodes  
(battery, vanadium pentoxide, phase changes during cycling of, lithium  
**intercalation** effect on)
- IT Inclusion reaction  
(**intercalation**, electrochem., of lithium, by vanadium  
pentoxide cathode, phase change and cycling efficiency in relation to)
- IT **7439-93-2**, Lithium, **uses** and miscellaneous  
RL: USES (Uses)  
(anodes, cycling efficiency of, **surface** layer  
formation-dissoln. effect on)
- IT 1314-62-1, **Vanadium** oxide (V2O5), **uses** and  
miscellaneous  
RL: USES (Uses)  
(cathodes, phase changes during cycling of, lithium  
**intercalation** effect on)
- IT **7429-90-5**, **Aluminum**, **uses** and miscellaneous  
**7440-02-0**, **Nickel**, **uses** and miscellaneous  
RL: USES (Uses)  
(**electrodes**, **lithium surface** layer on,  
anode cycling efficiency in relation to)
- IT 96-47-9, 2-Methyltetrahydrofuran 109-99-9, THF, **uses** and miscellaneous  
RL: USES (Uses)  
(electrolytes contg. lithium salt and, **lithium anode**  
cycling characteristics in)
- IT 14727-56-1, Decaline  
RL: USES (Uses)  
(electrolytes contg., lithium salt-org. solvent, **lithium**  
**anode** potential in relation to)
- IT 7791-03-9, Lithium perchlorate (LiClO4) 21324-40-3, Lithium  
hexafluorophosphate (LiPF6) 29935-35-1, Lithium hexafluoroarsenate  
(LiAsF6)  
RL: USES (Uses)  
(electrolytes of org. solvent and, **lithium anode**  
cycling characteristics in)
- IT **7439-93-2**, Lithium, **uses** and miscellaneous  
RL: USES (Uses)

(anodes, cycling efficiency of, **surface** layer formation-dissoln. effect on)

IT 7429-90-5, **Aluminum, uses** and miscellaneous  
7440-02-0, **Nickel, uses** and miscellaneous  
RL: USES (Uses)

(**electrodes, lithium surface** layer on,  
anode cycling efficiency in relation to)

=> d L113 1-11 cbib abs hitind hitrn

L113 ANSWER 1 OF 11 HCA COPYRIGHT 2003 ACS on STN

137:339939 Secondary **lithium battery anode** and the **battery**. Fujimoto, Hiroyuki; Mita, Hiroko; Okamoto, Takashi; Fujiwara, Toyoki; Iyori, Masahiro; Kamino, Maruo (Sanyo Electric Co., Ltd., Japan). Jpn. Kokai Tokkyo Koho JP 2002313319 A2 20021025, 9 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2001-110149 20010409.

AB The anode has a thin Li-**intercalating** active mass **layer deposited** on a current collector having a corrugated **surface**; where the active mass layer in its thickness direction has gaps among concavities of the collector **surface**. Preferable, the gap width is .ltoreq.10 um, the active mass layer is an amorphous silicon film and the collector is formed by depositing metal particles on a rough **surface** treated metal foil. The **battery** has the above anode, a cathode and a nonaq. electrolyte.

IC ICM H01M004-02

ICS H01M004-64; H01M004-70; H01M010-40

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)

ST secondary **lithium battery** silicon **anode**

active mass gap structure

IT **Battery** anodes

(Anodes contg. Si films with small gaps deposited on Cu collectors for secondary lithium **batteries**)

IT 7440-50-8, **Copper, uses**

RL: DEV (Device component use); USES (Uses)

(Anodes contg. Si films with small gaps deposited on Cu collectors for secondary lithium **batteries**)

IT 7440-21-3, **Silicon, uses**

RL: DEV (Device component use); USES (Uses)

(anodes contg. Si films with small gaps deposited on Cu collectors for secondary lithium **batteries**)

IT 7440-50-8, **Copper, uses**

RL: DEV (Device component use); USES (Uses)

(Anodes contg. Si films with small gaps deposited on Cu collectors for secondary lithium **batteries**)

L113 ANSWER 2 OF 11 HCA COPYRIGHT 2003 ACS on STN

137:143087 Electrode or separator having porous lithium film, their manufacture, and secondary lithium **battery** using them. Hashimoto, Tsutomu; Takano, Akemi; Kodama, Masaru; Takano, Takayuki; Tajima, Hidehiko (Mitsubishi Heavy Industries, Ltd., Japan). Jpn. Kokai Tokkyo Koho JP 2002231221 A2 20020816, 11 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2001-25443 20010201.

AB The claimed electrode, for a secondary Li **battery** equipped with a Li mixed oxide **cathode** and a Li-**intercalating anode**, has a porous Li film on a **surface** of the cathode and/or the anode. The claimed separator has a porous Li film having uneven **surface** with av. height 0.1-30 .mu.m and (av. width)/(av. height) ratio 1-10 on a **surface** of a synthetic resin film. The claimed **battery** is equipped with

the above electrode or the separator. The claimed process comprises forming the Li film by vacuum **deposition**, ion plating, or sputtering at 20-150.degree., .ltoreq.1 .times. 10<sup>-2</sup> Torr, and deposition rate 1-30 nm/s on an electrode **substrate** or a synthetic resin film. The **battery** provides high discharge capacity d.

- IC ICM H01M004-02  
ICS H01M002-18; H01M004-04; H01M004-58; H01M010-40  
CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
ST lithium porous **film deposition battery**  
electrode separator  
IT **Battery** anodes  
    **Battery** cathodes  
Secondary **battery** separators  
Sputtering  
    (electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT Vapor deposition process  
    (ion plating; electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT Secondary **batteries**  
    (**lithium**; **electrode** or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT Vapor deposition process  
    (vacuum; electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT 7440-44-0, Carbon, uses  
    RL: DEV (Device component use); USES (Uses)  
    (anode; electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT 12031-65-1, Lithium nickel oxide (LiNiO<sub>2</sub>) 12057-17-9, Lithium manganese oxide (LiMn<sub>2</sub>O<sub>4</sub>) 12190-79-3, Cobalt **lithium** oxide (CoLiO<sub>2</sub>)  
    RL: DEV (Device component use); USES (Uses)  
    (**cathode**; electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT 7439-93-2, **Lithium, uses**  
    RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PYP (Physical process); PROC (Process); USES (Uses)  
    (**electrode** or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT 9003-07-0, Polypropylene  
    RL: DEV (Device component use); USES (Uses)  
    (separator; electrode or separator having porous lithium **film** manufd. by **deposition** for **battery**)  
IT 7439-93-2, **Lithium, uses**  
    RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PYP (Physical process); PROC (Process); USES (Uses)  
    (**electrode** or separator having porous lithium **film** manufd. by **deposition** for **battery**)

L113 ANSWER 3 OF 11 HCA COPYRIGHT 2003 ACS on STN

136:265842 Composite electrode material, its manufacture, and secondary **battery** using the material. Yamada, Masayuki; Miyamoto, Miwa; Yokoyama, Eri; Koyama, Toshihiro; Saibara, Shoji; Aoyama, Shigeo (Hitachi Maxell Ltd., Japan). PCT Int. Appl. WO 2002027825 A1 20020404, 23 pp.  
DESIGNATED STATES: W: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD,

SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM; RW: AT, BE, BF, BJ, CF, CG, CH, CI, CM, CY, DE, DK, ES, FI, FR, GA, GB, GR, IE, IT, LU, MC, ML, MR, NE, NL, PT, SE, SN, TD, TG, TR. (Japanese). CODEN: PIXXD2. APPLICATION: WO 2001-JP8348 20010926. PRIORITY: JP 2000-296478 20000928; JP 2001-253239 20010823.

- AB The composite electrode material has a 0.01-30 .mu.m Li transition metal nitride cores coated with a Li **intercalating** or Li+ conducting material, other than Li transition metal nitride, on their **surface** and is prepd. by vapor phase deposition method to form the coating. The transition metal in the nitride is selected from Co, Cu, Fe, and Ni; the Li **intercalating** material is a carbonaceous material or a metal or its oxide or nitride. A secondary Li **battery** uses the material for cathode and/or anode.
- IC ICM **H01M004-58**  
ICS **H01M004-02**; H01M010-40; H01G009-00
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST secondary **lithium battery electrode**  
**lithium** transition metal nitride; **electrode**  
**lithium** transition metal nitride vapor phase coating
- IT Vapor deposition process  
(chem.; CVD **deposition** of **coating** materials on lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT **Battery anodes**  
(**lithium intercalating** and lithium conducting material coated lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT Carbonaceous materials (technological products)  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(**lithium intercalating** and lithium conducting material coated lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT Sputtering  
(sputtering **deposition** of **coating** materials on lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT Vapor deposition process  
(vapor phase **deposition** of **coating** materials on lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT 174421-80-8P, Cobalt lithium nitride (Co<sub>0.4</sub>Li<sub>2.6</sub>N)  
RL: DEV (Device component use); IMF (Industrial manufacture); PEP (Physical, engineering or chemical process); PYP (Physical process); PREP (Preparation); PROC (Process); USES (Uses)  
(**lithium intercalating** and lithium conducting material coated lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT 1308-80-1, Copper nitride (Cu<sub>3</sub>N) **7429-90-5, Aluminum, uses** 10377-52-3, Lithium phosphate 63985-45-5, Lithium orthosilicate 113443-18-8, Silicon oxide (SiO)  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(**lithium intercalating** and lithium conducting material coated lithium transition metal nitride for secondary **lithium battery electrodes**)
- IT **7429-90-5, Aluminum, uses**  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)

(lithium **intercalating** and lithium conducting material coated lithium transition metal nitride for secondary lithium **battery electrodes**)

L113 ANSWER 4 OF 11 HCA COPYRIGHT 2003 ACS on STN

135:360245 **Crystallization** of lithium-transition metal oxide thin **film** for secondary lithium **battery**. Lee, Jai Yon; Kan, Youn Son; Lee, Ho; Park, Soon Chul; Kan, Yon Mok (Korea Advanced Institute of Science and Technology, S. Korea). Jpn. Kokai Tokkyo Koho JP 2001316817 A2 **20011116**, 7 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2000-333625 20001031. PRIORITY: KR 2000-23286 20000501.

AB Li-transition metal oxide thin **films** for **cathodes** of **Li batteries** are formed on substrates by vapor **deposition**, and the **films** are processed with plasma. The oxide shows good **crystallinity** after plasma treatment, and the **battery** using it shows good cycling performance.

IC C23C014-58; H01M004-04

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 75, 76

ST lithium transition metal oxide **crystn** plasma processing **battery** cathode

IT **Battery cathodes**  
**Crystallization**

Plasma  
(**crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li battery** **cathode**)

IT Glass, uses  
RL: NUU (Other use, unclassified); USES (Uses)  
(substrate; **crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li battery** **cathode**)

IT 1314-62-1, **Vanadium** oxide (V2O5), uses 10377-52-3, Lithium phosphate (Li3PO4) 12024-01-0, Gallium lithium oxide (GaLiO2) 12031-65-1, Lithium nickel oxide (LiNiO2) 12037-42-2, Vanadium oxide (V6O13) 12039-13-3, Titanium sulfide (TiS2) 12057-17-9, Lithium manganese oxide (LiMn2O4) 12057-19-1, Lithium titanium oxide (LiTiO2) 12190-79-3, Cobalt lithium oxide (CoLiO2) 12798-95-7 18282-10-5, Tin oxide (SnO2)  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process); USES (Uses)  
(**crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li battery** **cathode**)

IT 7440-06-4, Platinum, uses 7440-32-6, Titanium, uses 7631-86-9, Silica, uses  
RL: NUU (Other use, unclassified); USES (Uses)  
(**multilayer** substrate; **crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li battery** **cathode**)

IT 1344-28-1, Alumina, uses 7429-90-5, Aluminum, uses 7440-21-3, Silicon, uses  
RL: NUU (Other use, unclassified); USES (Uses)  
(substrate; **crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li battery** **cathode**)

IT 7440-32-6, Titanium, uses  
RL: NUU (Other use, unclassified); USES (Uses)  
(**multilayer** substrate; **crystn.** of Li-transition metal oxide thin **film** by plasma processing for **Li**

**battery cathode)**  
IT **7429-90-5, Aluminum, uses**  
RL: NUU (Other use, unclassified); USES (Uses)  
(substrate; **crystn.** of Li-transition metal oxide thin  
**film** by plasma processing for **Li battery**  
**cathode)**

L113 ANSWER 5 OF 11 HCA COPYRIGHT 2003 ACS on STN  
134:283350 **Anodes for secondary lithium batteries**  
and the **batteries**. Ikeda, Hiroaki; Fujimoto, Masahisa;  
Fujitani, Shin; Shima, Masaki; Yagi, Hiromasa; Tarui, Hisaki; Kurokawa,  
Hiroshi; Asaoka, Kenji; Matsuda, Shigeki; Domoto, Yoichi; Ohshita, Ryuji;  
Kato, Yoshio; Nakajima, Hiroshi; Yoshida, Toshikazu (Sanyo Electric Co.,  
Ltd., Japan). PCT Int. Appl. WO 2001029918 A1 **20010426**, 101 pp.  
DESIGNATED STATES: W: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ,  
CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,  
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG;  
RW: AT, BE, BF, BJ, CF, CG, CH, CI, CM, CY, DE, DK, ES, FI, FR, GA, GB,  
GR, IE, IT, LU, MC, ML, MR, NE, NL, PT, SE, SN, TD, TG. (Japanese).  
CODEN: PIXXD2. APPLICATION: WO 2000-JP7297 20001020. PRIORITY: JP  
1999-301646 19991022; JP 1999-357808 19991216; JP 1999-365306 19991222; JP  
1999-374512 19991228; JP 2000-39454 20000217; JP 2000-47675 20000224; JP  
2000-90583 20000329; JP 2000-100405 20000403; JP 2000-150496 20000522; JP  
2000-207274 20000707.

AB The anodes have a thin **Li intercalating** active mass **film**  
**deposited** on both sides of a collector plate. The collector plate  
is preferably a Cu foil having a **surface** roughness Ra 0.1-1  
.mu.m, and the active mass is Si and/or Ge.

IC **H01M004-66; H01M004-02; H01M004-04;**  
**H01M004-38; H01M004-48; H01M004-58; H01M010-40**

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)

ST **secondary lithium battery anode** copper  
collector roughness; silicon anode copper collector roughness lithium  
**battery**; germanium anode copper collector roughness lithium  
**battery**

IT **Battery electrodes**  
**Surface** roughness  
(copper foil collectors with roughened **surface** for  
**anodes** in secondary **lithium batteries**)

IT 7440-21-3, Silicon, **uses** 7440-56-4, Germanium, **uses**  
RL: DEV (Device component use); USES (Uses)  
(**copper** foil collectors with roughened **surface** for  
**anodes** in secondary **lithium batteries**)

IT **7440-50-8, Copper, uses**  
RL: DEV (Device component use); PRP (Properties); USES (Uses)  
(**copper** foil collectors with roughened **surface** for  
**anodes** in secondary **lithium batteries**)

IT **7440-50-8, Copper, uses**  
RL: DEV (Device component use); PRP (Properties); USES (Uses)  
(**copper** foil collectors with roughened **surface** for  
**anodes** in secondary **lithium batteries**)

L113 ANSWER 6 OF 11 HCA COPYRIGHT 2003 ACS on STN  
130:340686 Anode material for nonaqueous secondary **battery**, its  
manufacture, and nonaqueous secondary **battery**. Akagi, Ryuichi;  
Nishimura, Toru; Okamoto, Masayuki (Kao Corp., Japan). Jpn. Kokai Tokkyo  
Koho JP 11135115 A2 **19990521** Heisei, 4 pp. (Japanese). CODEN:  
JKXXAF. APPLICATION: JP 1997-293898 19971027.

AB **Li-intercalating** semiconductor films comprising elements or

comps. selected from Group IIIA elements, Group IVA elements, and Group VA elements are used as anode active materials for nonaq. **batteries**. Anodes are manufd. by formation of semiconductor films on collector **substrates** by evapn. sputtering, ion plating, or CVD. Secondary **batteries** comprising the anodes, transition metal oxide **cathodes**, and Li ion-conducting nonaq. electrolytes comprising org. solvents contg. Li compds., polymers contg Li compds., or polymers carrying org. solns. of Li compds. are also claimed. **Batteries** having excellent charge-discharge cycles, high voltage, and high capacity are obtained.

- IC ICM H01M004-36  
ICS H01M004-02; H01M004-04; H01M010-40
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 76
- ST Group IIIA semiconductor **battery** anode; Group IVA semiconductor **battery** anode; Group VA semiconductor **battery** anode; semiconductor **anode lithium nonaq battery**; film semiconductor **battery** anode deposition
- IT Vapor deposition process  
(chem.; **deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT **Battery** anodes  
Semiconductor **films**  
Sputtering  
Vapor deposition process  
(**deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT Group IIIA elements  
Group IVA elements  
Group VA elements  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(**deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT Vapor deposition process  
(ion plating; **deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT Secondary **batteries**  
(**lithium**; **deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT 7429-90-5, Aluminum, uses 7439-92-1, Lead, uses 7440-21-3, Silicon, uses 7440-28-0, Thallium, uses 7440-31-5, Tin, uses 7440-36-0, Antimony, uses 7440-38-2, Arsenic, uses 7440-42-8, Boron, uses 7440-44-0, Carbon, uses 7440-55-3, Gallium, uses 7440-56-4, Germanium, uses 7440-69-9, Bismuth, uses 7440-74-6, Indium, uses 7723-14-0, Phosphorus, uses 7727-37-9, Nitrogen, uses  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(**deposition** of semiconductor **films** for manuf. of **anodes** for nonaq. **lithium** secondary **batteries**)
- IT 7429-90-5, Aluminum, uses 7440-31-5, Tin, uses 7440-36-0, Antimony,

uses 7440-69-9, Bismuth, uses  
7440-74-6, Indium, uses

RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)

(deposition of semiconductor films for manuf. of  
anodes for nonaq. lithium secondary batteries  
)

L113 ANSWER 7 OF 11 HCA COPYRIGHT 2003 ACS on STN

130:225427 **Anode for lithium secondary battery**

and its production. Akiyama, Shoichi (Ricoh Co., Ltd., Japan). Jpn. Kokai Tokkyo Koho JP 11067208 A2 19990309 Heisei, 22 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 1997-231848 19970813.

AB This anode contains anode active mass of a Li metal-Li compds. composite material comprising a large no. of Li particles coated with Li compds. contg. Li<sub>2</sub>CO<sub>3</sub> and compacted. The anode is produced by depositing a large no. of Li metal particles coated with Li compds. on a collector by evapg. or spray coating Li while reacting Li with the ambient gas in a treatment chamber and then pressurizing the **deposited Li metal** -Li compds. composite material. Dendrite formation in the obtained anode is suppressed and a Li secondary **battery** comprising the anode has a long cycle life and safety property.

IC ICM H01M004-58

ICS H01M004-02; H01M004-04; H01M004-40;  
H01M010-40

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)

ST **anode lithium** composite dendrite prevention  
**battery; safety lithium battery anode**  
dendrite prevention

IT Dendrites (**crystal**)

(formation prevention in **anode; lithium** secondary  
**battery** comprising **anode** contg. **lithium-**  
**lithium** compd. composite active mass with high resistance to  
dendrite formation)

IT **Battery anodes**

(**lithium** secondary **battery** comprising **anode**  
contg. **lithium-lithium** compd. composite active mass  
with high resistance to dendrite formation)

IT **Secondary batteries**

(**lithium; lithium** secondary **battery** comprising **anode**  
contg. **lithium-lithium** compd. composite active mass  
with high resistance to dendrite formation)

IT **Safety**

(of **battery; lithium** secondary **battery** comprising  
**anode** contg. **lithium-lithium** compd.  
composite active mass with high resistance to dendrite formation)

IT 554-13-2, **Lithium** carbonate 7439-93-2, **Lithium**

, uses 7789-24-4, **Lithium** fluoride, uses

RL: DEV (Device component use); USES (Uses)

(**anode** active mass contg.; **lithium** secondary **battery**  
comprising **anode** contg. **lithium-lithium**  
compd. composite active mass with high resistance to dendrite  
formation)

IT 7440-50-8, **Copper**, uses

RL: DEV (Device component use); USES (Uses)

(**anode** collector; **lithium** secondary **battery**  
comprising **anode** contg. **lithium-lithium**  
compd. composite active mass with high resistance to dendrite  
formation)

IT 7439-93-2, **Lithium**, uses

RL: DEV (Device component use); USES (Uses)  
(**anode** active mass contg.; lithium secondary **battery**  
comprising **anode** contg. **lithium-lithium**  
compd. composite active mass with high resistance to dendrite  
formation)

IT **7440-50-8, Copper, uses**

RL: DEV (Device component use); USES (Uses)  
(**anode** collector; **lithium** secondary **battery**  
comprising **anode** contg. **lithium-lithium**  
compd. composite active mass with high resistance to dendrite  
formation)

L113 ANSWER 8 OF 11 HCA COPYRIGHT 2003 ACS on STN

127:193075 **Anodes** for secondary **lithium batteries**

, their manufacture, and the **batteries**. Akiyama, Shoichi (Ricoh  
Co., Ltd., Japan). Jpn. Kokai Tokkyo Koho JP 09199180 A2 **19970731**  
Heisei, 7 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 1996-26125  
19960119.

AB The anodes are carbonaceous anode having areas covered with Li  
**film** by vapor **deposition** and uncovered areas, in a  
periodic arrangement on the **surface**, with 3-98% of the total  
**surface** area being covered. The width of the Li film is  
.ltoreq.2500 time the thickness of the film. Another form of the anodes  
have the whole **surface** covered periodically with thin and thick  
Li films, with 3-98% of the total **surface** covered with thick  
films, the thick films having a width .ltoreq.2500 time their thickness,  
and the thin film having a thickness .ltoreq.5 .mu.m. The electrodes are  
prepd. by masked vapor deposition of Li on the carbonaceous anode.  
Secondary Li **batteries** use the above described **anodes**,  
**Li intercalating cathodes**, and an electrolyte.

IC ICM H01M010-40

ICS H01M004-38

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)

ST **battery lithium** coated carbonaceous **anode**  
manuf

IT **Battery** anodes

(structure and manuf. of carbonaceous **anode** have  
**lithium** coated area for secondary lithium **batteries**)

IT Carbonaceous materials (technological products)

RL: DEV (Device component use); PEP (Physical, engineering or chemical  
process); PROC (Process); USES (Uses)

(structure and manuf. of carbonaceous **anode** have  
**lithium** coated area for secondary lithium **batteries**)

IT **7439-93-2, Lithium, uses**

RL: DEV (Device component use); PEP (Physical, engineering or chemical  
process); PROC (Process); USES (Uses)

(structure and manuf. of carbonaceous **anode** have  
**lithium** coated area for secondary lithium **batteries**)

IT 7782-42-5, Graphite, uses

RL: DEV (Device component use); PEP (Physical, engineering or chemical  
process); PROC (Process); USES (Uses)

(structure and manuf. of graphite **anode** have **lithium**  
coated area for secondary lithium **batteries**)

IT **7439-93-2, Lithium, uses**

RL: DEV (Device component use); PEP (Physical, engineering or chemical  
process); PROC (Process); USES (Uses)

(structure and manuf. of carbonaceous **anode** have  
**lithium** coated area for secondary lithium **batteries**)

L113 ANSWER 9 OF 11 HCA COPYRIGHT 2003 ACS on STN

- 126:253350 Amorphous lithium-containing iron oxide thin **film** as active mass for negative electrode. Guessous, Aicha; Ribes, Michel; Sarradin, Joel (Centre National De La Recherche Scientifique Cnrs, Fr.). Fr. Demande FR 2736043 A1 **19970103**, 20 pp. (French). CODEN: FRXXBL. APPLICATION: FR 1995-7757 19950628.
- AB Prepn. of an amorphous Li-contg. Fe oxide thin **layer** involves (1) **deposition** of an amorphous Fe<sub>2</sub>O<sub>3</sub> or Fe<sub>3</sub>O<sub>4</sub> **film** <10 .mu.m thick (preferably 0.2-2 .mu.m) by cathodic sputtering on a conductive substrate by using a **cryst.** .alpha.-Fe<sub>2</sub>O<sub>3</sub>, .gamma.-Fe<sub>2</sub>O<sub>3</sub>, or Fe<sub>3</sub>O<sub>4</sub> target and (2) insertion of Li<sup>+</sup> into the amorphous thin Fe<sub>2</sub>O<sub>3</sub> or Fe<sub>3</sub>O<sub>4</sub> **film** by using an electrochem. **cell** contg. an electrode consisting of a conductive substrate **coated** with the amorphous Fe<sub>2</sub>O<sub>3</sub> or Fe<sub>3</sub>O<sub>4</sub> **film**, a counter-electrode having an active mass capable of Li<sup>+</sup> liberation (e.g., Li, Li alloy), and an electrolyte contg. .gtoreq.1 Li salt in an aprotic polar solvent. The resulting anode is suitable for rechargeable rocking-chair Li **batteries** (esp. microbatteries).
- IC ICM C01G049-02  
ICS C01D015-02; C23F017-00; C23C014-08; C25D003-42; H01M004-24; H01M010-24
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST lithium iron oxide **battery** anode
- IT **Battery anodes**  
(amorphous lithium-contg. iron oxide thin **film** as active mass for)
- IT Secondary **batteries**  
(rocking-chair; amorphous lithium-contg. iron oxide thin **film** as active mass for anodes in)
- IT **7439-93-2, Lithium, uses**  
RL: TEM (Technical or engineered material use); USES (Uses)  
(in **iron** oxide active mass for **battery** anodes)
- IT 1309-37-1, **Iron** oxide (Fe<sub>2</sub>O<sub>3</sub>), **uses** 1317-61-9, **Iron** oxide (Fe<sub>3</sub>O<sub>4</sub>), **uses**  
RL: TEM (Technical or engineered material use); USES (Uses)  
(**lithium**-contg. amorphous; active mass for **battery** anodes)
- IT **7439-93-2, Lithium, uses**  
RL: TEM (Technical or engineered material use); USES (Uses)  
(in **iron** oxide active mass for **battery** anodes)
- L113 ANSWER 10 OF 11 HCA COPYRIGHT 2003 ACS on STN
- 123:204354 Improved grid alloy for lead-acid **battery**. Dou, Shi Xue; Chen, You Xiao; Luan, Ben Li; Zhao, Hui Jun; Liu, Hua Kun (Australia). PCT Int. Appl. WO 9515587 A1 **19950608**, 20 pp. DESIGNATED STATES: W: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ; RW: AT, BE, BF, BJ, CF, CG, CH, CI, CM, DE, DK, ES, FR, GA, GB, GR, IE, IT, LU, MC, ML, MR, NE, NL, PT, SE, SN, TD, TG. (English). CODEN: PIXXD2. APPLICATION: WO 1994-AU737 19941130. PRIORITY: AU 1993-2707 19931130; AU 1993-2736 19931201; AU 1993-2892 19931209.
- AB A grid alloy for use esp., but not exclusively, in sealed, maintenance-free Pb-acid **batteries** includes a component or components which preferably improve mech. strength of the grid and/or prevent or at least decrease the formation of PbSO<sub>4</sub> a corrosion product and/or which improves the surface state of the grid material and/or which inhibit the **deposition** of various **metals** on **cryst.** boundaries of the alloy. The grid alloy can include group 1A and/or Group 5A metallic elements and/or Ag, esp. As and/or Bi, K and/or Na and optionally Ca and/or Li, Sn and/or Cu, Al and/or Mg and/or

Zn.  
IC ICM H01M004-38  
ICS H01M004-14; H01M004-16; H01M004-73;  
C22C011-00; C22C012-00; C22C024-00  
CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 56  
ST electrode grid alloy lead **battery**; arsenic lead alloy electrode  
grid; bismuth lead alloy electrode grid; potassium lead alloy electrode  
grid; sodium lead alloy electrode grid; calcium lead alloy electrode grid;  
**lithium** lead alloy **electrode** grid; tin lead alloy  
electrode grid; copper lead alloy electrode grid; aluminum lead alloy  
electrode grid; magnesium lead alloy electrode grid; zinc lead alloy  
electrode grid  
IT Electrodes  
(**battery**, alloys for grids of lead-acid)  
IT 167952-11-6P  
RL: SPN (Synthetic preparation); TEM (Technical or engineered material  
use); PREP (Preparation); USES (Uses)  
(electrode grid alloy for lead-acid **battery**)  
IT 62726-93-6 152725-16-1 167952-12-7 167952-13-8 167952-14-9  
167952-15-0  
RL: TEM (Technical or engineered material use); USES (Uses)  
(electrode grid alloy for lead-acid **battery**)  
IT 7429-90-5, Aluminum, uses 7439-93-2,  
Lithium, uses 7439-95-4, Magnesium, uses 7440-09-7,  
Potassium, uses 7440-23-5, Sodium, uses 7440-31-5, Tin  
, uses 7440-38-2, Arsenic, uses 7440-50-8,  
Copper, uses 7440-66-6, Zinc,  
uses 7440-69-9, Bismuth, uses  
7440-70-2, Calcium, uses  
RL: MOA (Modifier or additive use); USES (Uses)  
(lead-acid **battery** electrode grid alloy microalloyed with)  
IT 7429-90-5, Aluminum, uses 7439-93-2,  
Lithium, uses 7440-31-5, Tin, uses  
7440-50-8, Copper, uses 7440-66-6,  
Zinc, uses 7440-69-9, Bismuth,  
uses  
RL: MOA (Modifier or additive use); USES (Uses)  
(lead-acid **battery** electrode grid alloy microalloyed with)  
L113 ANSWER 11 OF 11 HCA COPYRIGHT 2003 ACS on STN  
120:34508 Method for manufacturing carbon composite electrode material.  
Yamada, Kazuo; Tanaka, Hideaki; Mitate, Takehito; Yoshikawa, Masaharu  
(Sharp Kabushiki Kaisha, Japan). Eur. Pat. Appl. EP 555080 A1  
19930811, 10 pp. DESIGNATED STATES: R: DE, FR, GB. (English).  
CODEN: EPXXDW. APPLICATION: EP 1993-300813 19930204. PRIORITY: JP  
1992-17969 19920204.  
AB The carbon composite electrode material is manufd. by **coating**  
the surface of high-**crystallinity** carbon particles (e.g.,  
graphite) with a **film** contg. a Group VIII metal (e.g., Ni, Co)  
followed by **depositing** and/or **covering** the surface  
with a carbon material derived from pyrolysis of hydrocarbons (e.g.,  
propane). The material is esp. useful for **anodes** in Li  
**batteries**.  
IC ICM H01M004-96  
ICS H01M010-40; C01B031-04  
CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
ST **lithium battery anode** carbon  
IT **Anodes**  
(**battery**, lithium, Group VIII metal and carbon-

- coated carbonaceous materials for, manuf. of)**
- IT 7440-44-0P, Carbon, miscellaneous 7782-42-5P, Graphite, miscellaneous  
RL: MSC (Miscellaneous); PREP (Preparation)  
(Group VIII metal- and carbon-coated, manuf. of, for  
**anodes in lithium batteries)**
- IT 7439-93-2P, Lithium, uses  
RL: PREP (Preparation); USES (Uses)  
(**anodes**, Group VIII metal and carbon-coated  
carbonaceous materials for, manuf. of, for **batteries)**
- IT 11148-32-6P 7440-02-0P, Nickel, uses  
**7440-48-4P, Cobalt, uses**  
RL: PREP (Preparation)  
(carbonaceous materials **coated** with, manuf. of, for  
**anodes in lithium batteries)**
- IT 74-98-6, Propane, uses  
RL: USES (Uses)  
(in manuf. of carbon composite material for **anodes in  
lithium batteries)**
- IT 7439-93-2P, Lithium, uses  
RL: PREP (Preparation); USES (Uses)  
(**anodes**, Group VIII metal and carbon-coated  
carbonaceous materials for, manuf. of, for **batteries)**
- IT 7440-02-0P, Nickel, uses 7440-48-4P,  
**Cobalt, uses**  
RL: PREP (Preparation); USES (Uses)  
(carbonaceous materials **coated** with, manuf. of, for  
**anodes in lithium batteries)**

=> d L114 1-10 cbib abs hitind hitrn

L114 ANSWER 1 OF 10 HCA COPYRIGHT 2003 ACS on STN

- 134:369369 Physico-chemical properties of LiMn2O4 **films** grown by  
laser ablation. Camacho-Lopez, M. A.; Escobar-Alarcon, L.;  
Haro-Poniatowski, E.; Julien, C. (LMDH, UMR 7603, LMDH, UMR 7603,  
Universite Pierre et Marie Curie, Paris, 75252, Fr.). NATO Science  
Series, 3: High Technology, 85 (Materials for Lithium-Ion Batteries),  
535-541 (English) 2000. CODEN: NSSTFF. ISSN: 1388-6576.  
Publisher: Kluwer Academic Publishers.
- AB Thin **films** of LiMn2O4 were grown by the pulsed-laser deposition  
(PLD) technique, in which the control of the deposition parameters  
promoted the **film** stoichiometry. The structural properties of  
the PLD **films** were investigated as a function of the deposition  
conditions, that played an important role in the physico-chem.  
characteristics of this material. Thin **films** of LiMn2O4 that  
were grown onto Si wafers heated to 300.degree. under an O2 partial  
pressure of 100 mtorr exhibited a well-structured polycryst. spinel phase.  
**Films deposited** at lower temps. were highly disordered,  
but as an overall result it was demonstrated that the PLD method could be  
used to grow **films** with promising properties for Li microbattery  
application.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 75, 76
- ST lithium manganate **film** laser ablation **deposition**;  
**battery cathode lithium manganate film**  
; Raman scattering spectra lithium manganate **film**; cyclic  
voltammetry lithium manganate **film**
- IT Vapor deposition process  
(laser ablation; physicochem. properties of LiMn2O4 **films**  
grown by laser ablation for **cathodes in Li**

- microbatteries)
- IT **Battery cathodes**  
Secondary **batteries**  
(**lithium**; physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT Cyclic voltammetry  
Disorder  
Electric potential  
**Films**  
Microstructure  
Raman spectra  
Spinel-type **crystals**  
(physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT Laser radiation  
(pulsed; physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT **7439-93-2, Lithium, uses**  
RL: DEV (Device component use); USES (Uses)  
(physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT 12057-17-9P, Lithium manganate (**LiMn<sub>2</sub>O<sub>4</sub>**)  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PRP (Properties); SPN (Synthetic preparation); PREP (Preparation); PROC (Process); USES (Uses)  
(physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT 7440-21-3, Silicon, uses  
RL: TEM (Technical or engineered material use); USES (Uses)  
(wafer, substrate; physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- IT **7439-93-2, Lithium, uses**  
RL: DEV (Device component use); USES (Uses)  
(physicochem. properties of **LiMn<sub>2</sub>O<sub>4</sub>** films grown by laser ablation for **cathodes** in **Li** microbatteries)
- L114 ANSWER 2 OF 10 HCA COPYRIGHT 2003 ACS on STN  
129:304438 Study of **Fe<sub>2</sub>O<sub>3</sub>-based** thin film **electrodes** for **lithium-ion batteries**. Sarradin, J.; Ribes, M.; Guessous, A.; Elkacemi, K. (Laboratoire de Physicochimie de la Matiere Condensee-UMR 5617, Universite Montpellier, Montpellier, II-34095, Fr.). Solid State Ionics, 112(1,2), 35-40 (English) 1998. CODEN: SSIOD3. ISSN: 0167-2738. Publisher: Elsevier Science B.V..
- AB Sputter **deposited** thin films from an  $\alpha$ -**Fe<sub>2</sub>O<sub>3</sub>** target are studied as an alternative to the carbon-based **anode** for **lithium-ion batteries**. The prepn. process of the amorphous thin layers as well as their chem. and phys. properties are described. The value of the elec. cond. of the thin films is astonishingly higher than the one measured on the bulk samples. Depending on the amt. of **intercalated** lithium, a drastic change of this value is obsd. The electrochem. characteristics obtained on these amorphous thin layer electrodes regarding their sp. capacity and cyclability are presented. An attempt to fabricate a lithium-ion **battery** comprising a **Li<sub>3</sub>Fe<sub>2</sub>O<sub>3</sub>-based** thin film anode and a vitreous **V<sub>2</sub>O<sub>5</sub>-B<sub>2</sub>O<sub>3</sub>-based** thin film cathode is described.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
ST iron oxide **anode** lithium ion **battery**  
IT **Battery** anodes

- (study of iron oxide-based thin-film anodes for lithium-ion batteries)
- IT 115428-94-9, Iron lithium oxide ( $\text{Fe}_2\text{Li}_3\text{O}_3$ )  
RL: DEV (Device component use); USES (Uses)  
(anode; study of iron oxide-based thin-film anodes for lithium-ion batteries)
- IT 1309-37-1, Iron oxide ( $\text{Fe}_2\text{O}_3$ ), uses  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(study of iron oxide-based thin-film anodes for lithium-ion batteries)
- L114 ANSWER 3 OF 10 HCA COPYRIGHT 2003 ACS on STN
- 128:160196 **Lithium** insertion **electrodes** based on niobium telluride thin films. Pailharey, Daniel; Mathey, Yves; Lavela, Pedro; Tirado, Jose L. (Departement de Physique, Faculte des Sciences de Luminy, Marseille, 13288, Fr.). Electrochimica Acta, Volume Date 1998, 43(5-6), 495-502 (English) 1997. CODEN: ELCAAV. ISSN: 0013-4686. Publisher: Elsevier Science Ltd..
- AB Niobium telluride thin films were evaluated as **intercalation electrodes** in **lithium cells**. The film were prepd. on Al **substrate** by sputter deposition under different exptl. conditions. Large deposition periods lead to a noncryst. film material, while short **deposition** periods gave **layered** particles structurally similar to niobium ditelluride. For preps. carried out at 300.degree., the particles have sizes of .apprx.1 .mu.m with their 001 planes oriented parallel to the **substrate**. At 330.degree., particles of .apprx.10 .mu.m with their 001 axis parallel to the **substrate** were obtained. Test **batteries** Li/LiClO<sub>4</sub>(PC)/niobium telluride film were studied by potentiostatic and galvanostatic procedures. The performance of the **batteries** is influenced by the prepn. conditions. **Cell** capacities larger than 100 mA h g<sup>-1</sup> and a good capacity retention after 50 cycles were obsd. for films prepd. at 300.degree. when the **cells** were cycled between 0.5 and 2.0 V.
- CC 72-2 (Electrochemistry)  
Section cross-reference(s): 52, 75, 78
- ST **lithium** insertion **electrode** niobium telluride film;  
**intercalation** electrode niobium telluride film lithium
- IT **Intercalation**  
(electrochem.; of lithium by niobium telluride in propylene carbonate contg. LiClO<sub>4</sub>: **lithium** insertion **electrodes** based on niobium telluride thin films)
- IT **Electrodes**  
(**lithium** insertion; sputter deposition of niobium telluride film on aluminum for **lithium** insertion **electrodes**)
- IT **Secondary batteries**  
(lithium-niobium telluride)
- IT **Battery** cathodes  
(niobium telluride)
- IT Sputtering  
(of niobium telluride film on aluminum for **lithium** insertion **electrodes**)
- IT **7439-93-2, Lithium, uses**  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process); USES (Uses)  
(electrochem. **intercalation** by niobium telluride: **lithium** insertion **electrodes** based on niobium telluride thin films)
- IT 7791-03-9, Lithium perchlorate

- RL: NUU (Other use, unclassified); PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process); USES (Uses)  
(electrochem. **intercalation** of lithium by niobium telluride in propylene carbonate contg. LiClO<sub>4</sub>: **lithium** insertion **electrodes** based on niobium telluride thin films)
- IT 12034-83-2, Niobium telluride nbte2 162124-03-0, Niobium telluride 202518-77-2, Niobium telluride (NbTel.28-1.38)  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process); USES (Uses)  
(film prepn. and lithium electrochem. **intercalation**: **lithium** insertion **electrodes** based on niobium telluride thin films)
- IT 7429-90-5, Aluminum, uses  
RL: NUU (Other use, unclassified); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(sputter deposition of niobium telluride film on aluminum for **lithium** insertion **electrodes**)
- IT 7439-93-2, Lithium, uses  
RL: DEV (Device component use); PEP (Physical, engineering or chemical process); PRP (Properties); PROC (Process); USES (Uses)  
(electrochem. **intercalation** by niobium telluride: **lithium** insertion **electrodes** based on niobium telluride thin films)
- IT 7429-90-5, Aluminum, uses  
RL: NUU (Other use, unclassified); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses)  
(sputter deposition of niobium telluride film on aluminum for **lithium** insertion **electrodes**)
- L114 ANSWER 4 OF 10 HCA COPYRIGHT 2003 ACS on STN  
125:15263 Thin-film, solid state **battery** employing electrically insulating, ion-conducting electrolyte material. Ovshinsky, Stanford R. (Ovonic Battery Company, Inc., USA). U.S. US 5512387 A 19960430, 12 pp., Cont.-in-part of U.S. Ser. No. 155,059, abandoned. (English). CODEN: USXXAM. APPLICATION: US 1994-198757 19940218. PRIORITY: US 1993-155059 19931119.
- AB The **battery** comprises a **substrate**, .gtoreq.1 **multilayered** electrochem. **cell** deposited on the **substrate**, and an elec. conductive **layer** deposited on the top of the last of the multilayered electrochem. **cells**. Each layer of the multilayered **cell** consists of a layer of neg. electrode material capable of electrochem. adsorbing and desorbing ions during charge and discharge, a layer of pos. electrode material capable of electrochem. desorbing and adsorbing ions during charge and discharge, and a layer of insulating/conducting material disposed between the layers of pos. and neg. electrode material. The layer of insulating/conducting material is elec. insulating and capable of readily conducting or transporting ions from the layer of pos. electrode material to the layer of neg. electrode material while the **battery** is charging and vice versa while the **battery** is discharging. The elec. conductive layer provides 1 **battery** terminal.
- IC ICM H01M010-36  
ICS H01M002-30
- NCL 429152000
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)
- ST solid state thin film **battery**
- IT **Batteries**, secondary  
(solid-state thin-film)
- IT 12031-65-1, Lithium nickel oxide (LiNiO<sub>2</sub>) 12054-48-7, Nickel hydroxide (Ni(OH)<sub>2</sub>) 12162-79-7, Lithium manganese oxide (LiMnO<sub>2</sub>) 12190-79-3,

Cobalt **lithium** oxide (CoLiO<sub>2</sub>)  
RL: DEV (Device component use); USES (Uses)  
(**cathodes** in solid-state thin-film **batteries**)

IT 1314-62-1, Vanadium oxide (V<sub>2</sub>O<sub>5</sub>), **uses**  
RL: DEV (Device component use); USES (Uses)  
(**cathodes** in solid-state thin-film **batteries** from amorphous)

IT 7439-93-2, Lithium, **uses**  
RL: DEV (Device component use); USES (Uses)  
(solid-state thin-film **battery** anodes)

IT 1333-74-0, Hydrogen, **uses**  
RL: DEV (Device component use); USES (Uses)  
(solid-state thin-film **battery** anodes from alloys absorbing)

IT 7440-44-0, Carbon, **uses**  
RL: DEV (Device component use); USES (Uses)  
(solid-state thin-film **battery** anodes from **lithium-intercalatable** or hydrogenated)

IT 12033-89-5, Silicon nitride, **uses**  
RL: DEV (Device component use); USES (Uses)  
(solid-state thin-film **battery** electrolyte from hydrogenated or lithiated)

IT 7439-93-2, Lithium, **uses**  
RL: DEV (Device component use); USES (Uses)  
(solid-state thin-film **battery** anodes)

L114 ANSWER 5 OF 10 HCA COPYRIGHT 2003 ACS on STN

123:118645 Solid state **battery** using ionic or protonic electrolyte.  
Ovshinsky, Stanford R.; Young, Rosa (Ovonic Battery Co., Inc., USA). PCT  
Int. Appl. WO 9514311 A1 19950526, 26 pp. DESIGNATED STATES: W:  
AU, BR, CA, DK, FI, JP, KR, NO, RU, UA; RW: AT, BE, CH, DE, DK, ES, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE. (English). CODEN: PIXXD2.  
APPLICATION: WO 1994-US12297 19941026. PRIORITY: US 1993-155059 19931119.

AB The **battery** comprises a **substrate**, .gtoreq.1  
**multilayered** electrochem. **cell** deposited on  
the **substrate**, and an elec. conductive **layer**  
**deposited** on the top the last of the multilayered electrochem.  
**cells**, the elec. conductive layer providing 1 **battery**  
terminal. The multilayered electrochem. **cell** comprises a layer  
of neg. electrode material capable of electrochem. adsorbing and desorbing  
ions during charge and discharge, a layer of pos. electrode material  
capable of electrochem. desorbing and adsorbing ions during charge and  
discharge, and a layer of insulating/conducting material disposed between  
the 2 electrode material layers. The layer of insulating/conducting  
material is elec. insulating and capable of readily conducting or  
transporting ions from the layer of pos. electrode material to the layer  
of neg. electrode material while the **battery** is charging and  
from the layer of neg. electrode material to the layer of pos. electrode  
material while the **battery** is discharging.

IC ICM H01M006-18

CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)

ST **battery** ionic protonic electrolyte

IT Carbonaceous materials  
RL: DEV (Device component use); USES (Uses)  
(anodes in solid state **battery** using ionic or protonic  
electrolyte from lithium-intercalatable)

IT **Batteries**, secondary  
(solid-state using ionic or protonic electrolyte)

IT 1333-74-0, Hydrogen, **uses**  
RL: TEM (Technical or engineered material use); USES (Uses)  
(anodes in solid state **battery** using ionic or protonic  
electrolyte)

- IT **7439-93-2, Lithium, uses**  
RL: DEV (Device component use); USES (Uses)  
(**anodes** in solid state **battery** using ionic or protonic electrolyte from carbonaceous materials **intercalatable** with)
- IT 12033-89-5, Silicon nitride, uses  
RL: TEM (Technical or engineered material use); USES (Uses)  
(hydrogenated; insulating/conducting material in solid state **battery** using ionic or protonic electrolyte)
- IT 12031-65-1, Lithium nickel oxide (LiNiO<sub>2</sub>) 12054-48-7, Nickel hydroxide (Ni(OH)<sub>2</sub>) 12162-79-7, Lithium manganese oxide (LiMnO<sub>2</sub>) 12190-79-3, Cobalt lithium oxide (CoLiO<sub>2</sub>)  
RL: DEV (Device component use); USES (Uses)  
(in cathodes of solid state **battery** using ionic or protonic electrolyte)
- IT **7439-93-2, Lithium, uses**  
RL: DEV (Device component use); USES (Uses)  
(**anodes** in solid state **battery** using ionic or protonic electrolyte from carbonaceous materials **intercalatable** with)
- L114 ANSWER 6 OF 10 HCA COPYRIGHT 2003 ACS on STN
- 123:118408 Vanadium pentoxide gels from liquid crystals to lithium **batteries**. Livage, J.; Baffier, N.; Pereira-Ramos, J. P.; Davidson, P. (Chim. Matiere Condensee, Univ. P. M. Curie, Paris, 75252, Fr.). Materials Research Society Symposium Proceedings, 369(Solid State Ionics IV), 179-90 (English) 1995. CODEN: MRSPDH. ISSN: 0272-9172. Publisher: Materials Research Society.
- AB Vanadium pentoxide gels V2O<sub>5</sub>.nH<sub>2</sub>O are formed via the condensation of vanadic acid in aq. solns. They exhibit both ionic and electronic cond. and could therefore be used as **cathode** materials in **lithium batteries** or electrochromic display devices. The polymn. process leads to ribbon-like vanadium pentoxide particles. In a given range of concn., sols and gels exhibit a homogeneous lyotropic nematic phase in which the ribbons align in the same direction. Ordered fluid phases are thus obtained leading to oriented **films** when **deposited** onto flat **substrates**. Moreover, mixed oxides M<sub>x</sub>V<sub>2</sub>O<sub>5</sub> (M = Na<sup>+</sup>, K<sup>+</sup>, Ba<sup>2+</sup>, Al<sup>3+</sup>, Fe<sup>3+</sup>,...) exhibiting some preferred orientation are obtained via ion exchange. These compds. exhibit improved electrochem. properties (specific capacity, cycling properties) compared to usual mixed oxides prepd. via solid state reactions.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 72, 74
- ST **lithium battery cathode** vanadium pentoxide gel; electrochromic display device vanadium pentoxide gel
- IT Cathodes  
(**battery**, vanadium pentoxide gels from liq. crystals to lithium **batteries**)
- IT Inclusion reaction  
(**intercalation**, electrochem., electrochem. insertion of lithium in vanadium pentoxide gels for lithium **batteries**)
- IT 7439-93-2, Lithium, processes  
RL: PEP (Physical, engineering or chemical process); PROC (Process)  
(electrochem. insertion of lithium in vanadium pentoxide gels for lithium **batteries**)
- IT 1314-62-1, **Vanadium** pentoxide, uses  
RL: DEV (Device component use); USES (Uses)  
(**vanadium** pentoxide gels from liq. crystals to lithium **batteries**)

L114 ANSWER 7 OF 10 HCA COPYRIGHT 2003 ACS on STN

110:196330 Behavior of the negative and positive electrodes in an aprotic secondary lithium cell. Wiesener, K.; Eckoldt, U.; Muller, J.; Schneider, W.; Rahner, D. (Dep. Chem., Dresden Univ. Technol., Dresden, 8027, Ger. Dem. Rep.). Bulletin of Electrochemistry, 5(1), 23-7 (English) 1989. CODEN: BUELE6. ISSN: 0256-1654.

- AB The performance of **Li anodes** was affected by Li deposition and dissoln. i.e. the formation and removal of **surface layers** related to electrolyte and side reactions, as indicated by studies by Li and **Li-Al anodes** in org. solvent electrolyte. The cycling efficiency of V2O5 cathodes was detd. by **cryst.** structure changes; .ltoreq. 3.1 V, the cycling reaction (i.e. **Li intercalation**) was reversible, but when the discharge voltage reached the 2nd plateau, .ltoreq.2.0 V, irreversible lattice changes occurred and the cycling efficiency deteriorated.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 72
- ST **lithium anode surface layer** cycling; vanadium oxide cathode cycleing performance; **intercalation** lithium vanadium oxide reversibility; **battery intercalation** lithium vanadium oxide
- IT Electric resistance (of **lithium anode surface layer** , cycling efficiency in relation to)
- IT Electrolytic polarization (of lithium, **surface layer deposition** -dissoln. during, cycling efficiency in relation to)
- IT **Anodes** (**battery, lithium, cycling efficiency of, surface layer** formation-dissoln. effect on)
- IT Cathodes (**battery, vanadium pentoxide, phase changes during cycling of, lithium intercalation** effect on)
- IT Inclusion reaction (**intercalation, electrochem., of lithium, by vanadium pentoxide cathode, phase change and cycling efficiency in relation to**)
- IT 7439-93-2, **Lithium, uses** and miscellaneous  
RL: USES (Uses)  
(anodes, cycling efficiency of, **surface layer** formation-dissoln. effect on)
- IT 1314-62-1, **Vanadium oxide (V2O5), uses** and miscellaneous  
RL: USES (Uses)  
(cathodes, phase changes during cycling of, lithium **intercalation** effect on)
- IT 7429-90-5, **Aluminum, uses** and miscellaneous  
7440-02-0, **Nickel, uses** and miscellaneous  
RL: USES (Uses)  
(**electrodes, lithium surface layer** on, anode cycling efficiency in relation to)
- IT 96-47-9, 2-Methyltetrahydrofuran 109-99-9, THF, uses and miscellaneous  
RL: USES (Uses)  
(electrolytes contg. lithium salt and, **lithium anode** cycling characteristics in)
- IT 14727-56-1, Decaline  
RL: USES (Uses)  
(electrolytes contg., lithium salt-org. solvent, **lithium anode** potential in relation to)
- IT 7791-03-9, Lithium perchlorate (LiClO4) 21324-40-3, Lithium hexafluorophosphate (LiPF6) 29935-35-1, Lithium hexafluoroarsenate

- (LiAsF<sub>6</sub>)  
RL: USES (Uses)  
(electrolytes of org. solvent and, **lithium anode**  
cycling characteristics in)
- IT 7439-93-2, **Lithium, uses** and miscellaneous  
RL: USES (Uses)  
(anodes, cycling efficiency of, **surface layer**  
formation-dissoln. effect on)
- IT 7429-90-5, **Aluminum, uses** and miscellaneous  
7440-02-0, **Nickel, uses** and miscellaneous  
RL: USES (Uses)  
(**electrodes, lithium surface**  
**layer** on, anode cycling efficiency in relation to)
- L114 ANSWER 8 OF 10 HCA COPYRIGHT 2003 ACS on STN  
110:157635 The formation of pyrolytic carbon on a nickel sheet. Wada,  
Hiroshi; Suzuki, Tomonari; Yoshimoto, Yoshikazu; Yoshida, Masaru;  
Nakajima, Shigeo (Cent. Res. Lab., Sharp Corp., Tenri, 632, Japan).  
Japanese Journal of Applied Physics, Part 2: Letters, 28(2), L284-L286  
(English) 1989. CODEN: JAPLD8. ISSN: 0021-4922.
- AB **Films of C deposited on Ni substrates** by  
pyrolysis of C<sub>6</sub>H<sub>6</sub> at 1000.degree., have a a graphitic morphol. suitable  
for **Li intercalation**, for use as **battery** cathodes.  
When the C<sub>6</sub>H<sub>6</sub> concn. in Ar carrier gas was <0.7%, the degree of  
graphitization was high, the **surface** morphol. was angular, and  
there was a 10-35% Ni content on the **surface**, which was extruded  
from the **substrate**.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology)  
Section cross-reference(s): 49
- ST graphitized carbon benzene pyrolysis nickel; **cathode** pyrolytic  
carbon **lithium intercalation; battery**  
cathode pyrolytic carbon
- IT Graphitized carbon black  
RL: PREP (Preparation)  
(prepn. of, benzene pyrolysis for, for **lithium**  
**battery intercalation cathodes**)
- IT Cathodes  
(**battery**, graphitized carbon for, prepn. of, benzene  
pyrolysis for, for **lithium intercalation batteries**)
- IT 71-43-2P, Benzene, reactions  
RL: RCT (Reactant); PREP (Preparation); RACT (Reactant or reagent)  
(pyrolysis of, on nickel, for graphitized carbon prepn., for  
**lithium battery cathodes**)
- IT 7782-42-5P, Graphite, preparation  
RL: PREP (Preparation)  
(pyrolytic, prepn. of, from benzene, for **lithium**  
**battery intercalation cathodes**)
- IT 7440-02-0, **Nickel, uses** and miscellaneous  
RL: USES (Uses)  
(**substrates**, benzene pyrolysis on, graphitization by, for  
**lithium battery cathodes**)
- IT 7440-02-0, **Nickel, uses** and miscellaneous  
RL: USES (Uses)  
(**substrates**, benzene pyrolysis on, graphitization by, for  
**lithium battery cathodes**)

L114 ANSWER 9 OF 10 HCA COPYRIGHT 2003 ACS on STN  
108:189847 Molybdenum trisulfide thin film cathodes prepared by chemical vapor  
deposition. Schleich, D. M.; Chang, H. S.; Barberio, Y. L. (Polytech.  
Univ., Brooklyn, NY, 11201, USA). Proceedings - Electrochemical Society,

- 88-6(Proc. Symp. Primary Second. Ambient Temp. Lithium Batteries, 1987), 464-76 (English) **1988**. CODEN: PESODO. ISSN: 0161-6374.
- AB Thin-film MoS<sub>3</sub> cathodes were prep'd. by chem. vapor deposition from MoF<sub>6</sub> and hexamethyldisilathiane at 200-250.degree. on Al, Ni, and Al<sub>2</sub>O<sub>3</sub> **substrates**. **Films deposited** at 230.degree. have a min. resistivity of 90 k.OMEGA.-cm. In a Li/LiClO<sub>4</sub>-propylene carbonate/MoS<sub>3</sub> test **battery**, 4 equivs. were discharged and 3 equiv. could be reversibly charged at 1.8 V vs. Li. A 2 equiv. capacity was maintained after 100 deep cycles at 0.2 mA/cm<sup>2</sup>.
- CC 52-2 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 72
- ST molybdenum sulfide **cathode lithium intercalation**; lithium molybdenum sulfide **battery**
- IT Cathodes  
(**battery**, molybdenum sulfide, chem. vapor deposition and cycling behavior of, in lithium **intercalation battery**)
- IT Electric resistance  
(sheet, of molybdenum trisulfide thin **films**, **deposition** temp. and thickness effect on)
- IT **7429-90-5, Aluminum, uses** and miscellaneous  
RL: USES (Uses)  
(cathode **substrates**, molybdenum trisulfide deposition on, for lithium **intercalation batteries**)
- IT 12033-29-3, Molybdenum sulfide (MoS<sub>3</sub>)  
RL: USES (Uses)  
(cathodes, chem. vapor deposition and cycling behavior of, in lithium **intercalation batteries**)
- IT **7429-90-5, Aluminum, uses** and miscellaneous  
RL: USES (Uses)  
(cathode **substrates**, molybdenum trisulfide deposition on, for lithium **intercalation batteries**)
- L114 ANSWER 10 OF 10 HCA COPYRIGHT 2003 ACS on STN
- 87:143215 Scanning electron microscopic studies of lithium and cycle behavior of lithium nonaqueous **cells** with transition metal chalcogenide cathodes. Broadhead, John; Trumbore, Forrest A. (Bell Lab., Murray Hill, NJ, USA). Power Sources 5: Res. Dev. Non-Mech. Electr. Power Sources, Proc. Int. Symp., 9th, Meeting Date 1974, 661-82. Editor(s): Collins, Derek H. Academic: London, Engl. (English) **1975**. CODEN: 36LPAF.
- AB Studies were made on the rechargeability of **batteries** contg. cathodes of NbSe<sub>3</sub>, NbS<sub>3</sub>, TaSe<sub>3</sub>, and TiS<sub>3</sub> in 1M LiClO<sub>4</sub> in propylene carbonate. All systems showed rechargeability and, except with TiS<sub>3</sub>, **cell** failures were related to **Li anode** morphol. changes. Scanning electron micrographs of the **Li anodes** as well as the assocd. chronopotentiograms of **Li deposition** on **metal** substrates are also presented. In selected electrolytes, completely smooth surfaces of Li were obsd. for several cycles, while by 10 cycles densely packed **cryst.** Li was obsd. Cycle expts. with **Li anodes** in 0.6M Bu<sub>4</sub>NI in 1M LiClO<sub>4</sub> in propylene carbonate exhibited 130 cycles at .apprx.50% depth of cathode discharge compared with .apprx.90 cycles at 25% depth of discharge when 1M LiClO<sub>4</sub> in propylene carbonate was used as the electrolyte.
- CC 72-2 (Electrochemistry)
- ST **lithium anode** chalcogenide **cathode** org;  
transition metal chalcogenide cathode **battery**
- IT Transition metal chalcogenides  
RL: USES (Uses)  
(**cathodes**, in lithium cells,

rechargeability in relation to)  
IT Cathodes  
(**battery**, transition metal chalcogenide, rechargeability of)  
IT **Anodes**  
(**battery**, **lithium**, rechargeability of)  
IT **7439-93-2, uses** and miscellaneous  
RL: USES (Uses)  
(anodes, in **batteries** with transition metal chalcogenides,  
rechargeability of)  
IT 12034-78-5 12039-57-5 12316-04-0 12423-80-2  
RL: PRP (Properties)  
(**cathodes**, in **lithium batteries**,  
rechargeability of)  
IT **7439-93-2, uses** and miscellaneous  
RL: USES (Uses)  
(anodes, in **batteries** with transition metal chalcogenides,  
rechargeability of)

=> file japio

FILE 'JAPIO' ENTERED AT 12:04:36 ON 11 SEP 2003

COPYRIGHT (C) 2003 Japanese Patent Office (JPO)- JAPIO

FILE LAST UPDATED: 2 SEP 2003 <20030902/UP>

FILE COVERS APR 1973 TO MAY 30, 2003

<<< GRAPHIC IMAGES AVAILABLE >>>

=> d L88 1-6 all

L88 ANSWER 1 OF 6 JAPIO (C) 2003 JPO on STN  
AN 1998-083808 JAPIO  
TI **ANODE FOR LITHIUM SECONDARY BATTERY**  
IN KOJIMA YOSHITSUGU; KOIWAI AKIHIKO; SUZUKI NOBUAKI  
PA TOYOTA CENTRAL RES & DEV LAB INC  
PI JP 10083808 A 19980331 Heisei  
AI JP 1996-262503 (JP08262503 Heisei) 19960910  
PRAI JP 1996-262503 19960910  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1998  
IC ICM **H01M004-02**  
ICS **H01M004-58**; H01M010-40  
AB PROBLEM TO BE SOLVED: To provide a lithium secondary battery with high  
charging and discharging capacity by composing an anode active material of  
coke and graphite and specifying the addition amount of the graphite.  
SOLUTION: The addition amount of graphite is controlled to be 2-40wt.% to  
the total amount (100wt.%) of coke and graphite. Consequently, the  
conductivity of the resultant anode active material becomes high as  
compared with that of an anode active material consisting of only coke.  
The coke **crystallites** 10 partly have the same layer structure as  
graphite and lithium ion can be **intercalated** as it is into the  
interlayers 12 in the layer structure. Cavities 11 are formed  
between end parts 12 of a coke **crystallite** 10 and end parts 12  
of other coke **crystallites** 10 and lithium clusters 20 produced  
from lithium ions 2 are absorbed and stored in the cavities. As  
a result, much more lithium ions can be absorbed and stored and an  
**anode** for a **lithium** secondary battery having high  
charging and discharging capacity can be obtained.  
COPYRIGHT: (C)1998,JPO

L88 ANSWER 2 OF 6 JAPIO (C) 2003 JPO on STN

AN 1996-203527 JAPIO  
TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN NITTA YOSHIKI; WATANABE SHOICHIRO; SHIMAMURA HARUNARI; KAWAMURA YUMIKO  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 08203527 A 19960809 Heisei  
AI JP 1995-12586 (JP07012586 Heisei) 19950130  
PRAI JP 1995-12586 19950130  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1996  
IC ICM H01M004-58  
ICS H01M010-40  
AB PURPOSE: To provide a negative electrode with full reversibility which never allows deposition of Li at the time of its low temperature as well as to prevent needle-like deposition of metallic Li on the electrode plate surface of a negative electrode by using a substance expressed by a specific general formula as the negative electrode.  
CONSTITUTION: A negative pole 5 expressed by a general formula ( $\text{SnS} < \text{SB} > 2 < / \text{SB} >$ ) ( $\text{CoOp} < \text{SB} > 2 < / \text{SB} >$ )  
>)  $\text{Li}_x (0 <= x <= 1.0)$  is produced by intercalating cobaltcene expressed by  $\text{CoCp} < \text{SB} > 3 < / \text{SB} >$  to  $\text{SnS} < \text{SB} > 2 < / \text{SB} >$  at 120°C for 3 weeks. Or it is produced by intercalating cobaltcene to  $\text{SnS} < \text{SB} > 2 < / \text{SB} >$  for 25 days by using ethylene glycol dimethyl ether solution of 0.19M, and specific quantity of depolarizer obtained by mixing 10wt quantity of polyvinylidene fluoride serving as a bonding agent to 90wt part of negative pole is formed on a current collector 3 to build up an electrode. The electrode is dried under reduced pressure at 150°C and then assembled in a battery. Electrolyte may be used in such a manner that solvent formed by equivalent volumes of ethylene carbonate 1 and diethylcarbonate 1 are mixed together may solve 6 fluoric acid Li with its concentration of 1M/l. The negative may satisfy general formula ( $\text{SnS} < \text{SB} > 2 < / \text{SB} >$ ) ( $\text{CoCp} < \text{SB} > 2 < / \text{SB} >$ )  $\text{Li}_x (0 <= x <= 1.0)$  after being charged/discharged.  
COPYRIGHT: (C)1996, JPO

L88 ANSWER 3 OF 6 JAPIO (C) 2003 JPO on STN  
AN 1996-138743 JAPIO  
TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN INOUE KAORU; OZAKI YOSHIYUKI; KOSHINA HIDE; MORITA TERUYOSHI  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 08138743 A 19960531 Heisei  
AI JP 1994-279120 (JP06279120 Heisei) 19941114  
PRAI JP 1994-279120 19941114  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1996  
IC ICM H01M010-40  
ICS H01M004-02; H01M004-62  
AB PURPOSE: To provide a nonaqueous electrolyte secondary battery, preventing the heating of deposited lithium and excellent in safety, by adding carbonate, such as alkaline metal, alkaline earth metal, and transition metal, to a negative electrode having the active material of a lithium ion.  
CONSTITUTION: In a nonaqueous electrolyte secondary battery, the following are used: a positive electrode, composed of a lithium-containing metallic oxide, and a negative electrode, composed of material having the active material of a lithium ion, e.g. carbon material, etc., capable of reversibly intercalating/deintercalating lithium. At that time, carbonate of one kind or more of alkaline metal carbonate, alkaline earth metal carbonate, and transition metal carbonate is added to the negative electrode. This carbonate is preferably e.g.  $\text{Na} < \text{SB} > 2 < / \text{SB} > \text{CO} < \text{SB} >$

>3</SB> or Li<SB>2</SB>CO<SB>3</SB>, and the added quantity is preferably 1-10wt.% of the negative **electrode**. Consequently, **metallic lithium**, dendritically **deposited** on the negative electrode, reacts to an ion carbonate to form insoluble Li<SB>2</SB>CO<SB>3</SB> coating to increase the safety of the battery.  
COPYRIGHT: (C)1996,JPO

L88 ANSWER 4 OF 6 JAPIO (C) 2003 JPO on STN  
AN 1993-307958 JAPIO  
TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN MORIGAKI KENICHI; KOBAYASHI SHIGEO; TERAOKA TAKAHIRO  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 05307958 A 19931119 Heisei  
AI JP 1992-111082 (JP04111082 Heisei) 19920430  
PRAI JP 1992-111082 19920430  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1993  
IC ICM H01M004-58  
ICS H01M004-02; H01M010-40  
AB PURPOSE: To increase the **intercalation** quantity of lithium to increase the capacity of a negative electrode, and prevent the generation of dendrite of lithium by using the spherical graphite, which is obtained by graphitizing the mesophase fine spheres, for a negative electrode. CONSTITUTION: A nonaqueous electrolyte secondary battery consists of a negative electrode 3 mainly composed of the graphite material, a positive **electrode** 6 having the **lithium** included metal oxide as the active material thereof, the organic electrolyte and a separator 5. In this case, as the graphite material, spherical graphite, which is obtained by graphitizing the mesophase fine spheres generated in the liquid phase carbonizing process of a pitch group and which has 3.37 $\mu$ m; or less of layer-to-layer distance measured by the X-ray diffraction method and 500 $\mu$ m; or more of largeness of a **crystallite** in the c-axis direction and 500 $\mu$ m; or more of largeness of a **crystallite** in the a-axis direction and 3-50 $\mu$ m of the mean grain size, is used. A negative electrode 3, in which a large quantity of lithium is **intercalated** to increase the capacity thereof, is thereby obtained, and the generation of dendrite of lithium is prevented.  
COPYRIGHT: (C)1993,JPO&Japio

L88 ANSWER 5 OF 6 JAPIO (C) 2003 JPO on STN  
AN 1993-307957 JAPIO  
TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN MORIGAKI KENICHI; KOBAYASHI SHIGEO; TERAOKA TAKAHIRO; OTA AKIRA  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 05307957 A 19931119 Heisei  
AI JP 1992-111070 (JP04111070 Heisei) 19920430  
PRAI JP 1992-111070 19920430  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1993  
IC ICM H01M004-58  
ICS H01M004-02; H01M010-40  
AB PURPOSE: To increase the **intercalation** quantity of lithium to increase the capacity of a negative electrode, and prevent the generation of dendrite of lithium by graphitizing mesophase fine spheres, which are generated in the liquid phase carbonizing process of a pitch group. CONSTITUTION: A nonaqueous electrolyte secondary battery consists of a negative electrode 3 mainly composed of the graphite material, in which lithium is **intercalated**, a positive **electrode** 6

having the **lithium** included metal oxide as active material, the organic electrolyte and a separator 5. In this case, as the graphite material, the spherical graphite, which is obtained by graphitizing the mesophase fine spheres generated in the liquid phase carbonizing process of a pitch group and which has 3.37 $\mu$ m; or less of a layer-to-layer distance measured by the X-ray diffraction method and 500 $\mu$ m; or more of largeness of a **crystallite** in the c-axis direction and 3% or less of volume ratio of the spherical graphite having the grain size of 6 $\mu$ m or less among the distribution of grain size and 15 $\mu$ m-25 $\mu$ m of mean grain size, is used. A negative electrode, in which a large quantity of lithium is **intercalated** to increase the capacity thereof, is thereby provided, and while the generation of dendrite of lithium is prevented.

COPYRIGHT: (C)1993,JPO&Japio

L88 ANSWER 6 OF 6 JAPIO (C) 2003 JPO on STN  
AN 1989-217854 JAPIO  
TI POSITIVE **ELECTRODE MATERIAL FOR LITHIUM SECONDARY BATTERY**  
IN MIZOGUCHI AKIRA  
PA SUMITOMO ELECTRIC IND LTD  
PI JP 01217854 A 19890831 Heisei  
AI JP 1988-41606 (JP63041606 Showa) 19880223  
PRAI JP 1988-41606 19880223  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1989  
IC ICM **H01M004-02**  
ICS **H01M004-58**  
AB PURPOSE: To obtain a positive electrode material having large energy density and making internal resistance low by containing a graphite vapor-deposition layer directly covered from a vapor phase on a carbon fiber **base** material and a guest compound **intercalated** in this vapor-deposition layer.  
CONSTITUTION: A carbon fiber **base** material 1, a graphite vapor-deposition layer 2 directly covered from a vapor phase on the **base** material 1, and a guest compound **intercalated** in the vapor-deposition layer 2 are contained. The vapor-deposition layer 2 directly covered from the vapor phase on the **base** material 1 grows and it further grows by heat treatment. By **intercalating** a guest compound, an electrochemical reaction area is enlarged, and a positive electrode material having high energy density is obtained. A fibrous graphite **intercalation** compound 4 has good electroconductivity and makes internal resistance low.

COPYRIGHT: (C)1989,JPO&Japio

=> d L89 1-18 all

L89 ANSWER 1 OF 18 JAPIO (C) 2003 JPO on STN  
AN 2003-124064 JAPIO  
TI **ELECTROCHEMICAL DEVICE**  
IN MORIMOTO HIDEYUKI; NAGAI TATSU  
PA HITACHI MAXELL LTD  
PI JP 2003124064 A 20030425 Heisei  
AI JP 2001-312329 (JP2001312329 Heisei) 20011010  
PRAI JP 2001-312329 20011010  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 2003  
IC ICM **H01G009-00**  
ICS **H01G009-038; H01G009-058; H01M004-02; H01M004-52; H01M004-62; H01M010-40**  
AB PROBLEM TO BE SOLVED: To provide an electrochemical device which is

superior in cyclic properties, high in capacitance, and of high-energy density type.

SOLUTION: An electrode contains oxy iron hydroxide-coated high-electron conductivity particulates that are each composed of a high-electron conductivity particulate, having a specific surface area of  $5 \text{ m}^2/\text{g}$  to  $100 \text{ m}^2/\text{g}$  and an average grain diameter of 50 nm or below as a primary particle and oxy iron hydroxide covering the high-electron conductivity particulate. A lithium intercalation electrode contains lithium ions and functions as the counter electrode of the former electrode. These two electrodes are arranged through the intermediary of an electrolyte so as to compose an electrochemical device. The oxy iron hydroxide can be substituted by crystalline  $\beta$ -FeOOH or amorphous material containing, at least, one out of Ti, V, and Cu. It is preferable that acetylene black is used as the high-electron conductivity particulates.

COPYRIGHT: (C)2003,JPO

L89 ANSWER 2 OF 18 JAPIO (C) 2003 JPO on STN  
AN 2001-202961 JAPIO  
TI **ANODE MATERIAL FOR LITHIUM SECONDARY BATTERY, ITS MANUFACTURING METHOD AND LITHIUM SECONDARY BATTERY**  
IN FUKUDA KENJI; HARA YOICHIRO; UMEMO TATSUO; HIRUTA TAKASHI; YASUMOTO YOSHINORI; TSUNAWAKE TADANORI; MATSUNAGA OSAMU; IWANAGA KATSUSUKE  
PA MITSUI MINING CO LTD  
PI JP 2001202961 A 20010727 Heisei  
AI JP 2000-13514 (JP2000013514 Heisei) 20000121  
PRAI JP 2000-13514 20000121  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 2001  
IC ICM **H01M004-58**  
ICS C01B031-04; C23C016-26; **H01M004-02**; H01M010-40  
AB PROBLEM TO BE SOLVED: To provide an **anode** material for realizing **lithium** secondary battery, which has high discharge capacity and which is capable of high-speed charging and discharging as well as restraining decomposition of an electrolytic solvent, and to provide a lithium secondary battery using the anode material.  
SOLUTION: By using a mixed gas of an organic matter and an inert gas, in which the molarity of the organic matter is 2% to 50%, graphite particles are processed by chemical vapor **deposition** in a fluidized bed reactor at a temperature range of 90°C and 1,200°C to form an **anode** material for a **lithium** secondary battery, which is made of graphite particles and a **crystalline** carbon layer that covers the whole **surface** of the graphite particles, and in which the whole **surface** of the graphite particles is parallel to a (002) face of a carbon in the carbon layer.  
COPYRIGHT: (C)2001,JPO

L89 ANSWER 3 OF 18 JAPIO (C) 2003 JPO on STN  
AN 2000-231937 JAPIO  
TI **NONAQUEOUS ELECTROLYTE SECONDARY BATTERY**  
IN TAKEUCHI YOJI; UKIYOU YOSHIO; HONMA TAKAHIKO; NORITAKE TATSUO; NAKANO HIDEYUKI; OKUDA NARUAKI; KOBAYASHI TETSUO; SASAKI ITSUKI; MUKAI KAZUHIKO  
PA TOYOTA CENTRAL RES & DEV LAB INC  
PI JP 2000231937 A 20000822 Heisei  
AI JP 1999-31085 (JP11031085 Heisei) 19990209  
PRAI JP 1999-31085 19990209  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 2000  
IC ICM H01M010-40  
ICS **H01M004-02**; **H01M004-58**  
AB PROBLEM TO BE SOLVED: To reduce a cost, enhance cycle characteristics and

secure safety when overcharging as well as to stabilize a positive electrode active material itself, by using a positive electrode active material of a lithium nickel composite oxide having a rock-salt structure with orderly arranged layers obtained by substituting a part of a Ni site by other elements for the positive electrode and a negative electrode active material of a mixture of graphite and coke for the negative electrode.

SOLUTION: The composition of a composite oxide for a positive electrode active material is shown by the formula  $\text{LiNi}_x\text{M}_1\text{yM}_2\text{zO}_{2z}$ . (In the formula,  $\text{M}_1$ : At least one kind Selected from Co, Mn,  $\text{M}_2$ : one or more kinds selected from Al, B, Fe, Cr, Mg;  $x+y+z=1$ ,  $0.5 < x < 0.95$ ,  $0.01 < y < 0.4$ ,  $0.001 < z < 0.2$ . A part of inexpensive Ni contained in the positive electrode active material is substituted by two or more elements to improve cycle characteristics. A negative electrode active material of a mixture of highly **crystalline** graphite and inexpensive coke increases a battery capacity, and suppresses a **crystal** from being collapsed by restricting a movement of a Li ion between both **electrodes** during normal charge and discharge. In addition, **deposition** of a dendrite on the negative electrode at the time of excessive charging is prevented by irreversible large capacity.

COPYRIGHT: (C)2000,JPO

L89 ANSWER 4 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1999-016572 JAPIO  
TI POSITIVE **ELECTRODE** MATERIAL FOR **LITHIUM** SECONDARY  
BATTERY, AND PREPARATION OF PRECURSOR COMPOSITION THEREOF  
IN TAKEYA KANAME; KUBO SHIGEKI  
PA SUMITOMO METAL MINING CO LTD  
PI JP 11016572 A 19990122 Heisei  
AI JP 1997-166797 (JP09166797 Heisei) 19970624  
PRAI JP 1997-166797 19970624  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1999  
IC ICM **H01M004-58**  
ICS C01G053-00; **H01M004-02**; **H01M004-04**; H01M010-40  
AB PROBLEM TO BE SOLVED: To provide a preparation method for a positive **electrode** material for a **lithium** secondary battery comprising a compound oxide of Li and Ni containing Al of homogeneous solid-solution condition, and having a layer **crystal** structure of excellent thermal stability, and provide a preparation method for a precursor composition with homogeneously dispersed Al used therefor. SOLUTION: A nickel salt is suspended in water, an alkali salt of an aluminic acid is dissolved in it, and the alkali salt of the aluminic acid is neutralized to **deposit** an **aluminum** hydroxide. After a mixture of the **deposited aluminum** hydroxide and the nickel salt is dried, a lithium salt is added and mixed to prepare a precursor composition 1. The precursor composition is baked in the atmosphere of air containing 1 vol.% or more of ozone, or oxygen to prepare a positive electrode material.  
COPYRIGHT: (C)1999,JPO

L89 ANSWER 5 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1998-241690 JAPIO  
TI **LITHIUM** SECONDARY BATTERY NEGATIVE **ELECTRODE**  
IN KOJIMA YOSHITSUGU; SHIMIZU YOSHIHIRO; KOIWAI AKIHIKO; SUZUKI NOBUAKI  
PA TOYOTA CENTRAL RES & DEV LAB INC  
PI JP 10241690 A 19980911 Heisei  
AI JP 1997-61920 (JP09061920 Heisei) 19970227  
PRAI JP 1997-61920 19970227  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1998

IC ICM H01M004-58  
ICS H01M004-02

AB PROBLEM TO BE SOLVED: To provide a **lithium** secondary battery negative **electrode** having high discharge capacity, low irreversible capacity, and superior cycle characteristic by forming negative electrode active material of specific amount of graphite and the rest, amorphous carbon containing phosphorus, oxygen, and inevitable impurity, and specifying the containing amount range of phosphorus and oxygen with respect to the whole amorphous carbon.  
SOLUTION: Negative electrode active material is formed of graphite with 5 to 50% (i.e., weight%, hereunder the same) and the rest, amorphous carbon containing phosphorus, oxygen, and unavoidable impurity, and the containing amount of phosphorus is in the range of 0.01 to 10%, and the containing amount of oxygen is in the range of 0.01 to 15% with respect to the whole amorphous carbon. The amorphous carbon 1 is made of larger carbon **crystal** elements 10, which is formed by decomposing and forming one part of the carbon **crystal** element constituting raw coke through heat. Lithium ions 2 are **intercalation** between the layers 13 of the layer structure of the carbon **crystal** elements 10, and lithium clusters 20 formed of lithium ions 2 are stored in cavities 11, formed between the mutual ends 12 of the carbon **crystal** elements 10, so as to obtain a **lithium** secondary battery negative **electrode** having superior cycle characteristic.  
COPYRIGHT: (C)1998,JPO

L89 ANSWER 6 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1998-064542 JAPIO  
TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN NITTA YOSHIAKI  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 10064542 A 19980306 Heisei  
AI JP 1996-220939 (JP08220939 Heisei) 19960822  
PRAI JP 1996-220939 19960822  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1998  
IC ICM H01M004-58  
ICS H01M004-02; H01M010-40  
AB PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery in which **deposition** of needle **crystals** on the **surface** of an electrode accompanying charge/ discharge is retarded by using a lithium - silicon oxide represented by a specific formula in a negative electrode.  
SOLUTION: A nonaqueous electrolyte secondary battery comprises a nonaqueous electrolyte, a positive electrode, and a negative **electrode** using a **lithium** - silicon oxide represented by a general formula of  $\text{Li}_{x/2}\text{MSi}_2\text{O}_7$  ( $2 \leq x \leq 4$ , M is at least one of V, Mn, and Cr). The lithium - silicon oxide using Mn and Cr is prepared in such a way that lithium oxide and silicon dioxide of a stoichiometric composition ratio, and  $\text{Cr}_3\text{O}_4$  and/or  $\text{Mn}_3\text{O}_4$  of the required amount are put in a ceramic container, and they are melted at about 950°C under the flow of a mixture gas of argon gas and about 10% oxygen. When V is doped, a composite oxide of Si and V is prepared, lithium oxide is mixed to the silicon - vanadium composite oxide, then the similar process is applied. The nonaqueous electrolyte secondary battery with high capacity is obtained.  
COPYRIGHT: (C)1998,JPO

L89 ANSWER 7 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1997-190821 JAPIO

TI LITHIUM SECONDARY BATTERY  
IN GOTO AKIHIRO; YOSHIKAWA MASANORI; YAMAUCHI SHIYUUKO  
PA HITACHI LTD  
HITACHI CHEM CO LTD  
PI JP 09190821 A 19970722 Heisei  
AI JP 1996-1179 (JP08001179 Heisei) 19960109  
PRAI JP 1996-1179 19960109  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1997  
IC ICM H01M004-58  
ICS H01M004-02; H01M004-04  
AB PROBLEM TO BE SOLVED: To obtain a lithium secondary battery having high energy density and large discharging capacity, by including a conical or pyramid form of graphite powder made by specifying its aspect ratio, and having a layer form structure on the bottom surface, in the carbon material of a negative electrode.  
SOLUTION: This lithium secondary battery has a negative electrode consisting of a carbon type material which can **intercalate** the **lithium**, a positive **electrode**, and a nonaqueous electrolyte as the main component elements. To this carbon type material of the negative electrode, a conical or a pyramid form of graphite whose aspect ratio is 1.0 to 1.5, and having a layer form structure on the bottom surface is included more than 10vol%. It is preferable that the graphite powder is the powder **crystallized** from a solution metal such as **iron**. The regulation of the mean aspect ratio of the **crystallized** graphite particles is carried out by regulating the Si including amount in the molten **iron** less than 2.0%, or by adding a rare earth element unit such as Ca, Mg, or Ce, or their compound, in the molten **iron**. Consequently, a high speed charging and discharging can be carried out, and a lithium secondary battery with a long cycle life, and an excellent safety, can be obtained.  
COPYRIGHT: (C)1997,JPO

L89 ANSWER 8 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1997-073893 JAPIO  
TI LARGE-CAPACITY ELECTRODE, AND SECONDARY BATTERY USING THE SAME  
IN HAYASHI YOSHITAKA; KATO IKUO; OSAWA TOSHIYUKI; KATAGIRI NOBUO; FUJII TOSHISHIGE  
PA RICOH CO LTD  
PI JP 09073893 A 19970318 Heisei  
AI JP 1996-184052 (JP08184052 Heisei) 19960625  
PRAI JP 1995-186372 19950629  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1997  
IC ICM H01M004-02  
ICS H01M004-58; H01M010-40  
AB PROBLEM TO BE SOLVED: To provide an **electrode** which uses **lithium** complex oxides, for use in a large-capacity battery, and a secondary battery using the electrode, which has a large energy density and is excellent in cycle characteristic.  
SOLUTION: This battery electrode has an active material containing lithium complex oxides, a conductive agent, and a conductive high polymer. The lithium complex oxides occupy 40 to 99wt.% of the total weight including the conductive high polymer. The lithium complex oxides have a maximum particle diameter of 20 $\mu$ m or less and are made to exist uniformly in powder form with an average particle diameter of 10 $\mu$ m or less. Further, the circumference of the particles is covered with the conducting agent and the conductive high polymer. The lithium complex oxides may be complex oxides of lithium and manganese of a spinel **crystalline** structure. The conducting agent is desirably 1 to 20wt.% of the total weight of the active material. The electrode thus formed is used as a positive electrode, and a negative electrode is formed

from an **intercalated** material into and from which an alkali metal can be inserted and desorbed electrochemically. The figure is a discharge curve of a secondary battery.

COPYRIGHT: (C)1997,JPO

L89 ANSWER 9 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1997-007593 JAPIO  
TI LITHIUM SECONDARY BATTERY  
IN SAITO KEIICHI; MASASHIRO TAKAHISA; TOBISHIMA SHINICHI; YAMAKI JUNICHI  
PA NIPPON TELEGR & TELEPH CORP <NTT>  
PI JP 09007593 A 19970110 Heisei  
AI JP 1995-173027 (JP07173027 Heisei) 19950616  
PRAI JP 1995-173027 19950616  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1997  
IC ICM **H01M004-38**  
ICS **H01M010-40**  
AB PURPOSE: To prevent decreasing safety due to repeating a charge/discharge, by using a lithium metal containing conductive non-metal powder incapable of inserting/detaching a lithium ion in a negative **electrode** of a **lithium** secondary battery.  
CONSTITUTION: By including conductive non-metal powder incapable of inserting/ detaching a lithium ion in a lithium **metal**, **depositing** lithium is preferentially generated from a contact **surface** with the lithium metal. The conductive non- metal powder incapable of inserting/detaching a lithium ion serves as a nucleus even when deposited, to grow a **crystal**. From this fact, a uniform deposition form as a negative electrode total unit can be realized, to prevent easily generating branch-shaped lithium even when repeated a charge/discharge over a long period. Even in the case of separating by forming the branch-shape lithium, by contact with the conductive non-metal powder which is incapable of inserting/ detaching a lithium ion, since reusing in a charge/discharge can be made, improving a life can be attained.  
COPYRIGHT: (C)1997,JPO

L89 ANSWER 10 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1996-124559 JAPIO  
TI MANUFACTURE OF LITHIUM SECONDARY BATTERY AND OF NEGATIVE ELECTRODE ACTIVE MATERIAL  
IN YAMADA KAZUO; MITACHI TAKEHITO; YONEDA TETSUYA; NISHIMURA NAOTO  
PA SHARP CORP  
PI JP 08124559 A 19960517 Heisei  
AI JP 1994-264005 (JP06264005 Heisei) 19941027  
PRAI JP 1994-264005 19941027  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1996  
IC ICM **H01M004-02**  
ICS **H01M004-48; H01M004-58; H01M010-40**  
AB PURPOSE: To improve the initial charge/discharge efficiency characteristic.  
CONSTITUTION: A lithium secondary battery comprises a positive electrode, negative electrode and a nonaqueous system ion conductor. The negative electrode contains as a negative electrode active material a main negative electrode active material composed of graphite capable of **intercalating/deintercalating** a lithium ion and the second negative electrode active material composed of **copper** oxide, and the second negative electrode active material is a **copper** oxide (II) of low **crystallization**, **copper** oxide (I) obtained by reducing this **copper** oxide (II) of low **crystallization**, and a mixture of the **copper** oxide (II) of low **crystallization** and the **copper** oxide (I), or

lithium-contained **copper** oxide. By using a compound negative electrode of high charge/discharge efficiency in the initial time consisting of this main negative electrode active material and the second negative **electrode** active material, a **lithium** secondary cell having high capacity further excellent in a cycle characteristic is manufactured.

COPYRIGHT: (C)1996,JPO

L89 ANSWER 11 OF 18 JAPIO (C) 2003 JPO on STN

AN 1995-288130 JAPIO

TI NEGATIVE **ELECTRODE** ALLOY FOR **LITHIUM** SECONDARY BATTERY AND LITHIUM SECONDARY BATTERY

IN TAKADA YOSHINORI; SASAKI KOZO; MARUMOTO MITSUHIRO

PA MITSUBISHI CABLE IND LTD

PI JP 07288130 A 19951031 Heisei

AI JP 1995-34126 (JP07034126 Heisei) 19950222

PRAI JP 1994-49869 19940222

SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1995

IC ICM **H01M004-40**

ICS **H01M004-02**; H01M010-40

AB PURPOSE: To enhance electromotive force, charging/discharging capacity, energy density, and lengthen charging/discharging cycle life by using a Li-Ag-Te system alloy having a specified composition range in a negative electrode.

CONSTITUTION: The composition of a negative electrode alloy is preferably represented by formulas I, II, and III. By the  $\gamma$  phase of a Li-Ag system alloy, which relates to absorption/desorption of lithium, of a Li-Ag-Te system alloy, discharging capacity is maintained for a long time and charging/discharging cycle life is lengthened. By an intermetallic compound such as  $\text{Ag}_2\text{Te}$  and  $\text{Li}_2\text{Te}$ , **crystal** grains are made fine, diffusion of lithium and silver is accelerated, absorption/desorption efficiency of lithium is enhanced. By containing M1-M2 system alloy composition represented by formula IV, deterioration of negative electrode attendant on absorption/desorption of lithium is retarded by the binding effect of this intermetallic compound. Alloying is made by conventional melting process or vapor **deposition** process. (In formula IV, M1 is a 3B-5B group metal, and M2 is a transition metal excluding Ag).

COPYRIGHT: (C)1995,JPO

L89 ANSWER 12 OF 18 JAPIO (C) 2003 JPO on STN

AN 1995-130395 JAPIO

TI NONAQUEOUS ELECTROLYTE SECONDARY BATTERY

IN MIYASAKA TSUTOMU; KAGAWA OKIMASA

PA FUJI PHOTO FILM CO LTD

PI JP 07130395 A 19950519 Heisei

AI JP 1993-273809 (JP05273809 Heisei) 19931101

PRAI JP 1993-273809 19931101

SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1995

IC ICM H01M010-40

ICS **H01M004-02**; **H01M004-50**; **H01M004-58**

AB PURPOSE: To improve discharge capacity, charge/discharge cycle performance and safety by using transition metal composite oxide as negative **electrode** active material, spinel **lithium** manganese composite oxide as positive electrode active material and nonaqueous solution as electrolyte.

CONSTITUTION: A nonaqueous electrolyte secondary battery is formed basically with positive electrode active material, negative **electrode** active material and **lithium** salt containing nonaqueous electrolyte. In the positive electrode active

material, spinel structure lithium containing manganese oxide shown as  $\text{Li}_{1-x}\text{Mn}_{2-y}\text{O}_4$  ( $0 \leq x < 1.7$ ,  $0 < y < 0.7$ ) is contained. The negative electrode active material is obtained by **intercalating** lithium ions in transition metal oxide which may contains lithium. In such a case, the **intercalation** of the lithium ions is performed until the basic **crystal** structure of the transition metal oxide is changed (a X-ray diffraction pattern is changed). The **intercalation** is kept until the basic **crystal** structure of the lithium ions containing transition metal oxide after **intercalated** is in substantially unchanged condition during charging and discharging (the X-ray diffraction pattern is substantially unchanged).  
COPYRIGHT: (C)1995,JPO

L89 ANSWER 13 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1994-150930 JAPIO  
TI NON-AQUEOUS SECONDARY BATTERY  
IN YAMADA KAZUO; MITACHI TAKEHITO; YONEDA TETSUYA  
PA SHARP CORP  
PI JP 06150930 A 19940531 Heisei  
AI JP 1992-302424 (JP04302424 Heisei) 19921112  
PRAI JP 1992-302424 19921112  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1994  
IC ICM H01M004-58  
ICS H01M004-02; H01M010-40  
AB PURPOSE: To provide a non-aqueous secondary battery having large capacity by making carbon material to include particles each having substantially spherical structure body or their aggregate so that each of the particles has an imperfect **crystal** structure and its diameter is less than 5 micro-m.  
CONSTITUTION: In a non-aqueous secondary battery which is sealed in condition that an non-aqueous electrolyte is interposed between a positive electrode and a negative electrode and in which the active material of the negative electrode is formed of carbon material, the carbon material is made to include particles each having substantially spherical structure body or their aggregate so that each of the particles has an imperfect **crystal** structure and its diameter is less than 5 micro-m. Thus, lithium has a large effective area in contact with electrolyte in the case of **electrode** reaction and the **lithium** easily **intercalates** or deintercalates between laminated carbon layers of hexagon mesh face so that the ratio of the carbon used increases to make the battery to have a large capacity. In the case of using such as carbon as having a concentric spherical structure (onion-shaped structure) of which fine structure is not perfect, lithium diffuses to the carbon easily, the ratio of carbon used increases and a carbon negative electrode having a large capacity is used, thereby the battery is made to have the large capacity.  
COPYRIGHT: (C)1994,JPO&Japio

L89 ANSWER 14 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1994-150928 JAPIO  
TI NON-AQUEOUS ELECTROLYTE SECONDARY BATTERY  
IN WATANABE SHOICHIRO; SUGIMOTO TOYOJI  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 06150928 A 19940531 Heisei  
AI JP 1992-299517 (JP04299517 Heisei) 19921110  
PRAI JP 1992-299517 19921110  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1994  
IC ICM H01M004-58

ICS H01M004-02; H01M010-40

AB PURPOSE: To make a non-aqueous electrolyte secondary battery have high volt age and high energy density and improve its charge and discharge cycle life time characteristic and storage ability by using lithium composite oxide the faces of whose particles are covered by samarium oxide, etc., as a positive electrode active material.

CONSTITUTION: Lithium composite oxide  $\text{Li}_{1-x}\text{CoO}_2$  ( $0 \leq x \leq 1$ ) or  $\text{Li}_{1-x}\text{CoMoO}_2$  (wherein M is transition metal except Co and  $0 \leq x \leq 1$ ) the faces of whose particles are covered by samarium oxide or composite oxide is used as a positive electrode active material. A non-aqueous electrolyte secondary battery formed of a group of polarity plates, etc., is constructed by the positive **electrode, lithium** and a negative **electrode** made of carbon material capable of **intercalating** or deintercalating lithium alloy or lithium, etc. Since direct reaction between the surfaces of a positive active material particles and electrolyte is suppressed and decomposition reaction of the electrolyte on the positive electrode active material and **crystal** disintegration of the positive electrode active material can be prevented under high voltage, charge and discharge cycle life time characteristic and storage ability can be improved as a battery.

COPYRIGHT: (C)1994,JPO&Japio

L89 ANSWER 15 OF 18 JAPIO (C) 2003 JPO on STN

AN 1994-124707 JAPIO

TI NONAQUEOUS ELECTROLYTIC BATTERY

IN NITTA YOSHIAKI; HARAGUCHI KAZUNORI; KOBAYASHI SHIGEO; OKAMURA KAZUHIRO

PA MATSUSHITA ELECTRIC IND CO LTD

PI JP 06124707 A 19940506 Heisei

AI JP 1992-274690 (JP04274690 Heisei) 19921014

PRAI JP 1992-274690 19921014

SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1994

IC ICM H01M004-58

ICS H01M004-02; H01M010-40

AB PURPOSE: To provide a battery having enhanced charge and discharge characteristics by using a composite oxide substituted with a three-dimensional transition element satisfying a specific chemical formula.

CONSTITUTION: A composite oxide is substituted with a transition element satisfying an expression of  $\text{Li}_{1-x}\text{Me}_x\text{O}_2$  (where Me: one transition metal of Cu, Zn and Ag, and  $1.0 \leq x \leq 1.3$ ), having the **crystal** structure of a hexagonal system where the value of (x) is in the range of 0.01 to 0.05 when Me is Cu and Ag, and in the range of 0.05 to 0.2 when Me is Zn, and further having such a lattice constants identified from an X-ray diffraction chart as  $a_0$  between 2.85 and 2.89 Å,  $c_0$  between 14.20 and 14.30. Then, this composite oxide is used as an active material for a positive electrode. A secondary battery is constituted of the positive electrode, a negative **electrode of lithium, lithium** alloy or such carbon material as allowing the **intercalation** of lithium, and a nonaqueous electrolyte. Thus, a nonaqueous electrolytic secondary battery with enhanced charge and discharge characteristics can be provided, as the specific composite compound is used as the positive electrode.

COPYRIGHT: (C)1994,JPO&Japio

L89 ANSWER 16 OF 18 JAPIO (C) 2003 JPO on STN

AN 1993-314977 JAPIO  
TI NONAQUEOUS ELECTROLYTIC SECONDARY BATTERY  
IN KOBAYASHI SHIGEO; HARAGUCHI KAZUNORI; MORIGAKI KENICHI; NITTA YOSHIKI;  
TERAOKA TAKAHIRO  
PA MATSUSHITA ELECTRIC IND CO LTD  
PI JP 05314977 A 19931126 Heisei  
AI JP 1992-117226 (JP04117226 Heisei) 19920511  
PRAI JP 1992-117226 19920511  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1993  
IC ICM H01M004-58  
ICS H01M010-40  
AB PURPOSE: To increase capacity and improve cycle characteristics by using a carbon material with a Fulleren **crystal** structure of nodular molecules as a negative electrode.  
CONSTITUTION: An electrode plate group 4 in a case 1 comprises positive and negative electrodes spirally wound by a plurality of turns via a separator. A carbon material of a Fulleren **crystal** structure of nodular molecules constituted of a hexagon having six carbon atoms and a pentagon having five carbon atoms, is used as a negative **electrode**. Consequently, a **lithium** amount **intercalated** and de-**intercalated** with carbon increases. Also, as the carbon has a nodular **crystal** structure, the negative electrode becomes strong, compared with the case of a laminar structure, and a battery having large capacity and excellent cycle characteristics can be provided. Also, the nodular molecules are constituted of 60, 70, 76 and 84 carbon atoms.  
COPYRIGHT: (C)1993,JPO&Japio

L89 ANSWER 17 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1991-190053 JAPIO  
TI MANUFACTURE OF ELECTRODE  
IN YOSHIMOTO YOSHIKAZU; WADA HIROSHI; YOSHIDA MASARU; NAKAJIMA SHIGEO  
PA SHARP CORP  
PI JP 03190053 A 19910820 Heisei  
AI JP 1989-329880 (JP01329880 Heisei) 19891219  
PRAI JP 1989-329880 19891219  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1991  
IC ICM H01M004-04  
ICS H01M004-02; H01M010-40  
AB PURPOSE: To obtain a negative electrode having large capacity density and a flat discharge curve by bringing pyrolytic carbon, obtained by gas-phase decomposition of hydrocarbons, into contact with lithium vapor to form an **intercalation** compound and using the pyrolytic carbon for an electrode.  
CONSTITUTION: Pyrolytic carbon is produced by gas-phase heat decomposition of hydrocarbons such as aliphatic hydrocarbon, aromatic hydrocarbon, and alioylyc hydrocarbon. The pyrolytic carbon is brought into contact with lithium vapor to form an **intercalation** compound of the pyrolytic carbon and lithium, then the pyrolytic carbon is used for an **electrode**. By this process, **lithium** is uniformly doped in the highly **crystallized** component and activated. The negative **electrode** for a **lithium** secondary battery having large capacity density and a flat discharge curve is obtained.  
COPYRIGHT: (C)1991,JPO&Japio

L89 ANSWER 18 OF 18 JAPIO (C) 2003 JPO on STN  
AN 1983-108669 JAPIO  
TI SOLID ELECTROLYTE BATTERY  
IN MOCHIZUKI MASAJI; NAGAI TATSU  
PA HITACHI MAXELL LTD

PI JP 58108669 A 19830628 Showa  
AI JP 1981-206763 (JP56206763 Showa) 19811221  
PRAI JP 1981-206763 19811221  
SO PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1983  
IC ICM H01M006-18  
ICS H01M004-58; H01M004-62  
AB PURPOSE: To increase cathode utilization and improve a cathode reaction by forming a cathode having the mixture of  $\text{TiS}_{2\text{SB}}$  powder and solid electrolyte powder as an active mass on one side of a solid electrolyte. CONSTITUTION: Single **crystals** of  $\text{TiS}_{2\text{SB}}$  are **deposited** on a quartz plate by a C.V.D method and others.  $\text{Li}_{3\text{SB}}\text{N-LiI}$  compound which is solid electrolyte powder is mixed with this single **crystal**  $\text{TiS}_{2\text{SB}}$  powder and this mixture is molded to form a **cathode** 1.  $\text{Li}_{3\text{SB}}\text{N-LiI}$  compound is formed as a solid electrolyte 3 on the cathode 1. An anode is formed on the electrolyte 3 by vapor depositing of Li or press-bonding of Li foil. A **cathode** plate 4 and an anode plate 5 are fixed on these electrodes to form a battery. In this solid electrolyte battery,  $\text{Li}_{\text{SP}+\text{SP}}$  ion acts effectively with  $\text{TiS}_{2\text{SB}}$ , especially when  $\text{TiS}_{2\text{SB}}$  is single **crystal**, utilization of the cathode active mass is increased and excellent discharge performance is obtained. COPYRIGHT: (C)1983,JPO&Japio

=> file wpix

FILE 'WPIX' ENTERED AT 12:05:10 ON 11 SEP 2003

COPYRIGHT (C) 2003 THOMSON DERWENT

FILE LAST UPDATED: 6 SEP 2003 <20030906/UP>  
MOST RECENT DERWENT UPDATE: 200357 <200357/DW>  
DERWENT WORLD PATENTS INDEX SUBSCRIBER FILE, COVERS 1963 TO DATE

>>> NEW WEEKLY SDI FREQUENCY AVAILABLE --> see NEWS <<<

>>> SLART (Simultaneous Left and Right Truncation) is now available in the /ABEX field. An additional search field /BIX is also provided which comprises both /BI and /ABEX <<<

>>> PATENT IMAGES AVAILABLE FOR PRINT AND DISPLAY <<<

>>> FOR A COPY OF THE DERWENT WORLD PATENTS INDEX STN USER GUIDE, PLEASE VISIT:  
[http://www.stn-international.de/training\\_center/patents/stn\\_guide.pdf](http://www.stn-international.de/training_center/patents/stn_guide.pdf) <<<

=> d L108 all

L108 ANSWER 1 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 2002-659538 [71] WPIX  
DNN N2002-521226 DNC C2002-185526  
TI Lithium cell, useful e.g. in button cell or rechargeable lithium-polymer, has metal foil conductor with electrochemically deposited **crystallites** of same or different metal on **surface**.  
DC E13 L03 X16  
IN BIRKE, P; HAUG, P; HOLL, K; ILIC, D  
PA (MICR-N) MICROBATTERIE AG; (VART) VARTA GERAETEBATTERIE GMBH; (MICR-N) MICROBATTERIE GMBH; (BIRK-I) BIRKE P; (HAUG-I) HAUG P; (HOLL-I) HOLL K; (ILIC-I) ILIC D  
CYC 30

PI EP 1235286 A2 20020828 (200271)\* DE 6p H01M004-02 <--  
R: AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT  
RO SE SI TR  
DE 10108695 A1 20020905 (200271) H01M004-38 <--  
US 2002119376 A1 20020829 (200271) H01M004-66 <--  
JP 2002304998 A 20021018 (200301) 5p H01M004-66 <--  
CN 1372342 A 20021002 (200307) H01M004-64 <--  
KR 2002069099 A 20020829 (200309) H01M004-38 <--  
ADT EP 1235286 A2 EP 2002-1556 20020123; DE 10108695 A1 DE 2001-10108695  
20010223; US 2002119376 A1 US 2002-79003 20020220; JP 2002304998 A JP  
2002-43644 20020220; CN 1372342 A CN 2002-105123 20020222; KR 2002069099 A  
KR 2001-78732 20011213  
PRAI DE 2001-10108695 20010223  
IC ICM H01M004-02; H01M004-38; H01M004-64;  
H01M004-66  
ICS H01M004-70; H01M006-16; H01M010-40  
AB EP 1235286 A UPAB: 20021105  
NOVELTY - Providing a galvanic cell with **lithium**-intercalating  
**electrode(s)**, in which the electrochemically active material is  
applied to a metal foil conductor.  
DETAILED DESCRIPTION - In a galvanic cell with **lithium**  
-intercalating **electrode(s)**, in which the electrochemically  
active material is applied to a metal foil conductor, the **surface**  
of the metal foil is provided with electrochemically deposited  
**crystallites** of a second or identical metal, which enlarges the  
area of contact and reduces the contact resistance to the active material.  
USE - The cells are useful e.g. as button cells and rechargeable  
lithium-polymer batteries.  
ADVANTAGE - Loss of contact between the conductor and  
electrochemically active composition is the most frequent cause of failure  
of galvanic cells. Expanded metal conductors are normally used in  
rechargeable lithium polymer cells but require costly coating with primer  
to ensure satisfactory adhesion of the electrodes. The **crystallite**  
layer increases the adhesion and eliminates the need to use expanded metal  
and primer.  
Dwg.0/2  
FS CPI EPI  
FA AB; DCN  
MC CPI: E06-D08; L03-E01B5B  
EPI: X16-E03A1; X16-E08A

=> d L108 2-7 all

L108 ANSWER 2 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1999-179954 [15] WPIX  
DNN N1999-132190 DNC C1999-052330  
TI Treated carbon fibers - by catalytic etching of mesophase fibers to  
selectively remove hard carbon shell.  
DC L03 X16  
IN CHU, X; KINOSHITA, K  
PA (REGC) UNIV CALIFORNIA  
CYC 1  
PI US 5874166 A 19990223 (199915)\* 15p H01M004-58 <--  
ADT US 5874166 A US 1996-708151 19960822  
PRAI US 1996-708151 19960822  
IC ICM H01M004-58  
AB US 5874166 A UPAB: 19990416  
NOVELTY - Hard carbon shells (35) on mesophase carbon fibers are  
selectively removed by **depositing** catalytic **metal**

particles on the shell to form etch sites (36). Etching then exposes the edges (38) of graphitic layers (36) which act as reversible electrode sites. DETAILED DESCRIPTION - A mesophase carbon fiber comprises a hard carbon shell, 0.01-0.1  $\mu$  thick, which is treated to remove 1-80% of the shell to expose sufficient edges of the underlying plates to form a carbon electrode having a reversible capacity of at least 170 mAh/g. Other portions of the shell remain to impart physical strength and integrity. INDEPENDENT CLAIMS are also included for the following: (a) a carbon structure comprising radial carbon plates with exposed **surface** edges as above, and (b) a method of forming the above comprising forming catalyst sites on the hard shell and selectively etching around these to expose the edges above.

USE - As treated carbon fibers for reversible carbon **electrodes** for, e.g., **lithium** and oxygen cells

ADVANTAGE - Electrodes formed from the fibers have high charge and discharge capacity and reversibility, good mechanical strength and **corrosion** resistance DESCRIPTION OF DRAWING(S) - The drawing shows an isometric view of the carbon fiber after loading with catalyst. (34) Shell; (35) Catalyst sites; (36) Graphite plates; (38) Edges.

Dwg.3/10

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B3

EPI: X16-E01A; X16-E01G; X16-E08A

L108 ANSWER 3 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1995-267007 [35] WPIX

DNN N1995-205021 DNC C1995-121329

TI **Crystalline lithium** deposited on **cathode**

**base** by electrolysis - using electrolyte contg tetra hydro furan deriv and/or 1,3-dioxolane as solvent.

DC E13 L03 M11 X16

IN MATSUI, T; TAKEYAMA, K

PA (MATU) MATSUSHITA DENKI SANGYO KK; (MATU) MATSUSHITA ELEC IND CO LTD

CYC 2

PI JP 07169460 A 19950704 (199535)\* 10p H01M004-02 <--

US 5558953 A 19960924 (199644) 12p H01M006-14

JP 3202880 B2 20010827 (200152) 12p H01M004-02 <--

ADT JP 07169460 A JP 1994-255373 19941020; US 5558953 A US 1994-319761 19941007; JP 3202880 B2 JP 1994-255373 19941020

FDT JP 3202880 B2 Previous Publ. JP 07169460

PRAI JP 1993-263411 19931021

IC ICM **H01M004-02**; H01M006-14

ICS C25C001-02; **H01M004-04**; **H01M004-40**;

**H01M004-58**; H01M010-40

AB JP 07169460 A UPAB: 19950905

The **crystalline** lithium metal has a polygonal **surface** deposited on a cathode metal **base** due to the electrolysis of a lithium ion conductive electrolyte.

Also claimed is the prepn. of the **crystalline** lithium metal by: (a) facing a material for electrochemically releasing a lithium ion and a metal **base** in a non-aq. lithium ion conductive electrolyte contg. a THF deriv. of formula (I) and/or 1,3-dioxolane deriv. of formula (II) as solvent and (b) supplying a cathodic electric current to the **metal base** to **deposit** lithium on the **metal base**. In formulae (I) and (II),  $R_1 = C_mH_{2m+1}$ ;  $R_2 = C_nH_{2n+1}$ ; m and n are not simultaneously 0.

Also claimed is a lithium storage battery comprising: (a) rechargeable positive electrodes; (b) negative electrodes consisting of the **metal base** having **deposited** lithium; and

(c) non-aq. lithium ion conductive electrolyte.

ADVANTAGE - The **crystalline** lithium metal is thin c.f. conventional **crystalline** lithium metals and is used as electrode foil. The use of the **crystalline lithium** metal gives the negative **electrodes** having less generation of dendrite and high charge and discharge efficiency. The resulting lithium storage battery has high safety, prolonged charge and discharge cycle life, and high reliability.

Dwg.0/5

FS CPI EPI

FA AB; GI; DCN

MC CPI: E07-A02E; E07-A04; L03-E01B5; M11-A06

EPI: X16-B01F1; X16-E01C; X16-E01G

L108 ANSWER 4 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1995-173461 [23] WPIX

DNN N1995-135980 DNC C1995-080463

TI Negative **electrode** for **lithium** sec. batteries - includes elements with large electronegativity and lithium with low electronegativity, and lithium ions distributed in matrix form.

DC L03 X16

IN HASEGAWA; SUZUKI, K

PA (NPDE) NIPPONDENSO CO LTD

CYC 2

PI JP 07094186 A 19950407 (199523)\* 3p H01M004-40 <--

US 5498764 A 19960312 (199616) 5p H01M004-38 <--

ADT JP 07094186 A JP 1993-236257 19930922; US 5498764 A US 1994-308491 19940921

PRAI JP 1993-236257 19930922

IC ICM H01M004-38; H01M004-40

ICS H01M004-02; H01M004-36

AB JP 07094186 A UPAB: 19950619

The negative electrode is composed of elements with large electronegativity and lithium metal with low electronegativity. The lithium ions are distributed in the form of a matrix. The lithium **metal** is **deposited** selectively on a charging part. A charging curvature part and multiple liq. **crystal** nuclei are formed. The deposition of lithium is continued until a lithium layer is formed.

ADVANTAGE - Restrains growth of dendrite **crystal**. Lengthens charging and discharging life time.

Dwg.0/0

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B5

EPI: X16-B01F1; X16-E01C

L108 ANSWER 5 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1993-312892 [40] WPIX

DNN N1993-240930 DNC C1993-139045

TI Mfr. of carbon composite electrode material - by coating highly **crystalline** carbon particles with metal and adding an outer carbon layer having a turbulent **crystal** structure.

DC E36 L03 X16

IN MITATE, T; TANAKA, H; YAMADA, K; YOSHIKAWA, M

PA (SHAF) SHARP KK

CYC 5

PI EP 555080 A1 19930811 (199340)\* EN 10p H01M004-96 <--

R: DE FR GB

JP 05299073 A 19931112 (199350) 6p H01M004-02 <--

EP 555080 B1 19960515 (199624) EN 10p H01M004-96 <--  
R: DE FR GB  
DE 69302596 E 19960620 (199630) H01M004-96 <--  
US 5595838 A 19970121 (199710) 8p C25B011-04  
US 5776610 A 19980707 (199834)# B32B005-16  
JP 2999085 B2 20000117 (200008) 6p H01M004-02 <--  
ADT EP 555080 A1 EP 1993-300813 19930204; JP 05299073 A JP 1993-17598  
19930204; EP 555080 B1 EP 1993-300813 19930204; DE 69302596 E DE  
1993-602596 19930204, EP 1993-300813 19930204; US 5595838 A Cont of US  
1993-13029 19930203, US 1994-323572 19941017; US 5776610 A Div ex US  
1993-13029 19930203, Div ex US 1994-323572 19941017, US 1996-729170  
19961011; JP 2999085 B2 JP 1993-17598 19930204  
FDT DE 69302596 E Based on EP 555080; US 5776610 A Div ex US 5595838; JP  
2999085 B2 Previous Publ. JP 05299073  
PRAI JP 1992-17969 19920204; US 1996-729170 19961011  
REP EP 239410; EP 334501; EP 346088; EP 419090  
IC ICM B32B005-16; C25B011-04; H01M004-02; H01M004-96  
ICS C01B031-04; H01M004-04; H01M004-58; H01M010-40  
AB EP 555080 A UPAB: 19960731  
C composite electrode is mfd. by: coating C particles of high  
**crystallinity** with a film contg. a Gp. VIII metal; and coating the  
resulting particles with a C layer by hydrocarbon (deriv.) pyrolysis.  
Pref. Gp. VIII metal is Ni, Co or Fe or an alloy of these.  
USE/ADVANTAGE - As the negative **electrode** active material  
in **Li** sec. batteries. (claimed) A C composite of high  
**surface** area and high core **crystallinity** is formed and  
at a relatively low temp.  
Dwg.1/3  
Dwg.1/3  
FS CPI EPI  
FA AB; GI; DCN  
MC CPI: E31-N03; L03-E01B3  
EPI: X16-B01F1; X16-E01G  
  
L108 ANSWER 6 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1993-213691 [26] WPIX  
DNN N1993-164353 DNC C1993-094742  
TI **Anode** for rechargeable **lithium** cell - comprises  
lithium magnesium silicide material which intercalates to form single  
**crystal** or amorphous phases.  
DC L03 M26 X16  
IN ATTIA, A I; HALPERT, G; HUANG, C; SURAMPUDI, S; ATTIA, A  
PA (USAS) NASA US NAT AERO & SPACE ADMIN  
CYC 1  
PI US 959858 A0 19930601 (199326)\* 16p H01M000-00  
US 5294503 A 19940315 (199411) 9p H01M004-58 <--  
ADT US 959858 A0 US 1992-959858 19921013; US 5294503 A US 1992-959858 19921013  
PRAI US 1992-959858 19921013  
IC ICM H01M000-00; H01M004-58  
AB US N7959858 N UPAB: 20030312  
Battery includes an **LixMg2Si anode** which intercalates **Li**  
to form a single **crystal** phase when x is up to 1.0 and an  
amorphous phase when x is 1.0-2.0. The battery has an organic electrolyte.  
Cell pref. comprises an anode layer of **LixMg2Si deposited**  
on an **Ni** screen current collector; a separator element; and a  
cathode layer formed of a polymer binder contg. a dispersion of  
chalcogenide or oxide particles such as **TiS2** or **LixCoO2** pressed into an  
expanded **Ni** sheet. The **LixMg2Si** material may also include 0.1-1M **Ag**  
**based** on **Li**. A pref. suitable electrolyte is an 0.5-3.0 M salt  
dissolved in an organic electrolyte, e.g. 1M **LiAsF** in 10% **EC** + 90% **2MeTHF**.

USE/ADVANTAGE - Anode has good electrolyte stability, large Li storage capacity, good reversibility and good mechanical strength even after cycling.

Dwg.1/8

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B5; M26-B

EPI: X16-E01C; X16-E08A

L108 ANSWER 7 OF 7 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1989-207963 [29] WPIX

DNN N1989-158595 DNC C1989-092262

TI Aluminium electroconductive polymer composite electrode - for sec cell, **based** on aluminium with specified **crystal** face giving good bond.

DC A26 A85 L03 P73 X12 X16

IN KABATA, T; KIMURA, O; OHSAWA, T

PA (RICO) RICOH KK

CYC 4

PI DE 3841924 A 19890713 (198929)\*

JP 01157060 A 19890620 (198930)

FR 2624526 A 19890616 (198931)

US 4886572 A 19891212 (199007) 13p

JP 02043266 A 19900213 (199012)

DE 3844875 A1 19930401 (199314) H01M004-60 <--

DE 3844940 A1 19950302 (199514) H01M004-60 <--

DE 3841924 C2 19951012 (199545) 12p H01M004-60 <--

DE 3844875 C2 19960905 (199640) 16p H01M004-60 <--

JP 2669672 B2 19971029 (199748) 816p C08L101-00

DE 3844940 C2 20000203 (200011) H01M004-60 <--

ADT DE 3841924 A DE 1988-3841924 19881213; FR 2624526 A FR 1988-16403 19881213; US 4886572 A US 1988-283605 19881213; DE 3844875 A1 Div ex DE 1988-3841924 19881213, DE 1988-3844875 19881213; DE 3844940 A1 Div ex DE 1988-3841924 19881213, DE 1988-3844940 19881213; DE 3841924 C2 DE 1988-3841924 19881213; DE 3844875 C2 Div ex DE 1988-3841924 19881213, DE 1988-3844875 19881213; JP 2669672 B2 JP 1988-298253 19881128; DE 3844940 C2 Div ex DE 1988-3841924 19881213, DE 1988-3844940 19881213

FDT DE 3844875 A1 Div ex DE 3841924; DE 3844940 A1 Div ex DE 3841924; DE 3841924 C2 Div in DE 3844875; DE 3844875 C2 Div ex DE 3841924; JP 2669672 B2 Previous Publ. JP 02043266; DE 3844940 C2 Div ex DE 3841924

PRAI JP 1987-314165 19871214; JP 1988-83971 19880407; JP 1988-298253 19881128

IC ICM C08L101-00; H01M004-60

ICS B23H003-00; B32B015-08; B44C001-22; C08G061-10; C08G061-12;

C08G073-02; C08G085-00; C08K003-08; C23F001-00; C25B003-10;

C25B009-00; C25D009-02; C25D013-08; H01M004-02;

H01M004-04; H01M004-38; H01M004-66

AB DE 3841924 A UPAB: 19930923

In a composite of Al and an electroconductive polymer (I), the **surface** of the Al to which (I) is bonded has a predominantly (HOO) **crystal** face (H = 1, 2, 4).

(I) is (substd.) polyaniline (IA). (I) is deposited by electrolytic **deposition** on an Al redn. electrode with (HOO)

**surface**. This **surface** may be etched first. (I) is depositing by contacting the oxidised form with a reducing medium, which may be a nonmetal or **metal**. (IA) is **deposited** on an Al electrode at +0.75 to +0.95 V vs. SCE in 3-6 N aq. acid (mixt.) contg. H2SO4, HCl and/or HBF4.

USE/ADVANTAGE - The composite is claimed for use in a sec. cell, pref. as positive electrode in a cell with a non-aq. electrolyte and a

negative **electrode** having **Li** (alloy) as active substance. The bond between the Al ano (I) and the impedance at the interface are improved. The sec. cell has high capacity, high energy density and excellent stability for repeated charge/discharge. 816pp  
Dwg.No.1,2/5)

FS CPI EPI GMPI

FA AB; GI

MC CPI: A05-J11; A09-A03; A12-B04; A12-E06A; L03-E01B8; L03-E01B9; L03-E03  
EPI: X12-D01C; X16-B01X; X16-E01

=> d L109 1-18 ti

L109 ANSWER 1 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI **Electrode** film used in **lithium-ion** battery, includes laminated film with two layers of different heat resistance property, and has fine permeation holes formed on lower **surface** of laminated film.

L109 ANSWER 2 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Electrochemical cell for electrochemistry and battery technology, includes negative electrode with ternary alloy layer of lithium and two other metals.

L109 ANSWER 3 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI **Electrode** for rechargeable **lithium** battery, includes **surface** coating layer provided on **surface** of active material layer.

L109 ANSWER 4 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI **Anode** for electrochemical cell comprises **lithium** metal layer, and metal-lithium alloy layer.

L109 ANSWER 5 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Anode formation for primary, secondary electrochemical cell, involves **depositing** active **layer** comprising lithium metal (foil) and multi-layer structure of single ion conducting layers and polymer layers on **substrate**.

L109 ANSWER 6 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Method of manufacturing **electrodes** for **lithium** secondary cell.

L109 ANSWER 7 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Preparation of anode of electrochemical cell includes **depositing** temporary protective **metal** layer on lithium metal layer.

L109 ANSWER 8 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Multilayer electric current producing cell preparing method involves pressing multilayered subassembly of anode, separator and cathode to form prismatic subassembly.

L109 ANSWER 9 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Fabrication of active metal electrode used as negative **electrodes** in batteries such as **lithium electrodes** in **lithium-** sulfur batteries.

L109 ANSWER 10 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

TI Formation of vanadium oxide film on **substrate** used as **cathode** in **lithium-ion** battery.

- L109 ANSWER 11 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI **Lithium** secondary battery - has **cathode** active material coating layer in which occlusion/release of lithium ion is possible, on nickel **coating** which is **deposited** over **copper ( alloy) base** material.
- L109 ANSWER 12 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI **Electrode**, pref. for a secondary **lithium** cell - comprises a support having a plastic network **substrate** with open cells with a metal layer on the network **surface** and a supported active material.
- L109 ANSWER 13 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI Non-aqueous electrolyte secondary battery for communication apparatus - has anode obtained by coating anode active material at specific portions of **metal deposition film** formed on plastic **substrate**.
- L109 ANSWER 14 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI **Lithium** secondary battery - has **cathode** consisting of graphite **layer deposited** on **iron substrate** NoAbstract Dwg 1/3.
- L109 ANSWER 15 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI Assembling constituents of electrochemical generator - **based** on thin films of lithium or its alloy and of polymeric electrolyte.
- L109 ANSWER 16 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI Long life alloy **electrode base** for **lithium** storage battery - comprises aluminium **film deposited** on iridium or tin sheet NoAbstract NoDwg.
- L109 ANSWER 17 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI Current collector for sulphide contg. positive electrode - for electrochemical cell, has **surface** reacting with sulphur at cell voltage.
- L109 ANSWER 18 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
TI Lattice for lead storage battery electrode - made of lead **alloy** with lithium **deposited** on and diffused into **surface** layers.

=> d L109 1-19 all

L109 ANSWER 1 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 2003-573342 [54] WPIX  
DNN N2003-455878  
TI **Electrode** film used in **lithium-ion** battery, includes laminated film with two layers of different heat resistance property, and has fine permeation holes formed on lower **surface** of laminated film.  
DC X16  
PA (KAKO-N) KAKOGAWA PLASTICS KK; (PANA-N) PANAC KK  
CYC 1  
PI JP 2003197198 A 20030711 (200354)\* 7p H01M004-64 <--  
ADT JP 2003197198 A JP 2001-393825 20011226  
PRAI JP 2001-393825 20011226  
IC ICM H01M004-64

ICS H01M002-16; H01M004-02; H01M010-40  
AB JP2003197198 A UPAB: 20030821  
NOVELTY - A collector film (5) which consists of a metal vapor deposition film, is patterned on the surface of a laminated film (3). The laminated film consists of two layers (1,2) with different heat resisting property, on its upper surface. The fine permeation holes (4) are provided to the other surface of the laminated film.  
DETAILED DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:  
(1) battery element; and  
(2) laminated non-aqueous battery.  
USE - Electrode film used in laminated non-aqueous battery (claimed) e.g. lithium-ion battery.  
ADVANTAGE - Since laminated film consists of layers of different heat resistance properties, thin-shape of electrode is obtained and safety is improved with respect to overall heat generation of the lithium-ion battery.  
DESCRIPTION OF DRAWING(S) - The figure shows the partial top views and a sectional view of the electrode film in the battery.  
low heat resistance layer 1  
high heat resistance layer 2  
laminated film 3  
fine permeation holes 4  
collector film 5  
Dwg.3/11  
FS EPI  
FA AB; GI  
MC EPI: X16-B01F; X16-E01; X16-E02; X16-F02  
  
L109 ANSWER 2 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 2003-361779 [34] WPIX  
CR 1996-268819 [27]; 1997-558117 [51]; 1998-446053 [38]; 1998-541733 [46]; 1999-302578 [25]; 2000-181181 [16]; 2000-222629 [19]; 2001-090475 [10]; 2001-581771 [65]; 2002-436022 [46]  
DNN N2003-288872 DNC C2003-095411  
TI Electrochemical cell for electrochemistry and battery technology, includes negative electrode with ternary alloy layer of lithium and two other metals.  
DC A85 L03 M11 X16  
IN CHU, M; NIMON, Y S; VISCO, S J  
PA (POLY-N) POLYPLUS BATTERY CO  
CYC 1  
PI US 2002182508 A1 20021205 (200334)\* 22p C25C007-00  
ADT US 2002182508 A1 Cont of US 1998-148024 19980903, CIP of US 2000-480286 20000110, CIP of US 2000-713997 20001115, US 2002-189881 20020703  
FDT US 2002182508 A1 Cont of US 6017651, CIP of US 6165644  
PRAI US 2002-189881 20020703; US 1998-148024 19980903; US 2000-480286 20000110; US 2000-713997 20001115  
IC ICM C25C007-00  
ICS C25B009-00; H01M004-40; H01M004-58  
AB US2002182508 A UPAB: 20030529  
NOVELTY - An electrochemical cell comprises:  
(i) a positive electrode (100) including sulfur, lithium sulfide, and/or lithium polysulfide; and  
(ii) a negative electrode having a ternary alloy layer comprising lithium, a first and a second metal.  
The first metal accommodates volume changes in the ternary alloy during lithium cycling. The second metal alloys with lithium and the first metal.

DETAILED DESCRIPTION - An electrochemical cell comprises:

- (i) a positive **electrode** (100) including sulfur, **lithium** sulfide, and/or lithium polysulfide; and
- (ii) a negative electrode having a ternary alloy layer comprising lithium, a first and a second metal.

The first metal provides a matrix that accommodates volume changes in the ternary alloy during lithium cycling. The second metal alloys with lithium and the first metal and increases **lithium** cycling efficiency and **anode** stability towards electrolyte components during storage. INDEPENDENT CLAIMS are also included for:

(a) an anode for use in an electrochemical cell comprising a lithium metal layer and a ternary alloy layer;

(b) a method of forming a **lithium anode** with a metal-**lithium** alloy layer for an electrochemical cell, comprising **depositing** two **metal layers** on outer **surface** of the lithium foil, and alloying the two metal layers to form a ternary alloy layer comprising lithium and the metals; and

(c) a battery cell comprising a positive anode of a mixture of electrochemically active and electronically conductive materials and a negative electrode (an anode).

USE - As a battery cell (claimed). Used for electrochemistry and battery technology, e.g. for portable electronic devices.

ADVANTAGE - The device enhances the cycle life and shelf life of lithium-metal batteries. The battery has reduced voltage delay after initiation of battery discharge. The ternary alloy increases **lithium** cycling efficiency and **anode** stability towards electrolyte components during storage of the cell.

DESCRIPTION OF DRAWING(S) - The figure shows a block diagram illustrating the formation of an aluminum-lithium alloy on a lithium metal foil **surface**.

Electrode 100

Anode 120, 130

Dwg.1/8

FS CPI EPI

FA AB; GI

MC CPI: A12-E06A; L03-E01B5; L03-E01B5B; M11-A

EPI: X16-B01F1; X16-E01C

L109 ANSWER 3 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2003-103051 [09] WPIX

DNN N2003-082369 DNC C2003-025884

TI **Electrode** for rechargeable **lithium** battery, includes **surface** coating layer provided on **surface** of active material layer.

DC L03 X16

IN KAMINO, M; OHSHITA, R; TAMURA, N

PA (SAOL) SANYO ELECTRIC CO LTD; (KAMI-I) KAMINO M; (OHSH-I) OHSHITA R; (TAMU-I) TAMURA N

CYC 2

PI US 2002168572 A1 20021114 (200309)\* 6p H01M004-40 <--

JP 2002289178 A 20021004 (200309) 6p H01M004-02 <--

ADT US 2002168572 A1 US 2002-103127 20020322; JP 2002289178 A JP 2001-84761 20010323

PRAI JP 2001-84761 20010323

IC ICM H01M004-02; H01M004-40

ICS H01M004-04; H01M004-38; H01M004-66; H01M010-40

AB US2002168572 A UPAB: 20030206

NOVELTY - An electrode includes **surface** coating layer that is

provided on a **surface** of active material layer, opposite to the **surface** on which the current collector layer is provided. The **surface** coating is composed of metal or metal alloy incapable or capable of alloying with lithium.

DETAILED DESCRIPTION - An electrode comprises current collector layer provided with active material layer. The current collector layer is composed of metal incapable of alloying with lithium and the active material layer is composed of metal capable of alloying with lithium. A **surface** coating layer is provided on a **surface** of active material layer, opposite to the **surface** on which the current collector layer is provided. The **surface** coating is composed of metal or metal alloy incapable or capable of alloying with lithium.

An INDEPENDENT CLAIM is included for a rechargeable **lithium** battery including negative **electrode**, positive electrode and nonaqueous electrolyte (2).

USE - For rechargeable lithium battery.

ADVANTAGE - The electrode exhibits improved charge-discharge characteristics. The presence of the **surface** coating layer prevents a reaction of electrolyte and **surface** of active material layer, thus suppressing deterioration of active material layer at its **surface** and improving charge-discharge cycle characteristics.

DESCRIPTION OF DRAWING(S) - The drawing shows a schematic sectional view of a beaker cell.

Nonaqueous electrolyte 2

Dwg. 2/2

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B5; L03-E01B8

EPI: X16-E01C; X16-E02

L109 ANSWER 4 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2002-436022 [46] WPIX

CR 1996-268819 [27]; 1997-558117 [51]; 1998-446053 [38]; 1998-541733 [46];  
1999-302578 [25]; 2000-181181 [16]; 2000-222629 [19]; 2001-090475 [10];  
2001-581771 [65]; 2003-361779 [34]

DNN N2002-343229 DNC C2002-123910

TI **Anode** for electrochemical cell comprises **lithium** metal layer, and metal-lithium alloy layer.

DC L03 X16

IN CHU, M; NIMON, Y S; VISCO, S J

PA (POLY-N) POLYPLUS BATTERY CO; (POLY-N) POLYPLUS BATTERY CO INC

CYC 97

PI WO 2002041416 A2 20020523 (200246)\* EN 44p H01M004-02 <--

RW: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ  
NL OA PT SD SE SL SZ TR TZ UG ZW

W: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK  
DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR  
KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PH PL PT RO  
RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW

AU 2002011410 A 20020527 (200261) H01M004-02 <--

US 6537701 B1 20030325 (200325) H01M004-58 <--

ADT WO 2002041416 A2 WO 2001-US31019 20011003; AU 2002011410 A AU 2002-11410  
20011003; US 6537701 B1 Cont of US 1998-148024 19980903, CIP of US  
2000-480286 20000110, US 2000-713997 20001115

FDT AU 2002011410 A Based on WO 2002041416; US 6537701 B1 Cont of US 6017651,  
CIP of US 6165644

PRAI US 2000-713997 20001115; US 1998-148024 19980903; US 2000-480286  
20000110

IC ICM H01M004-02; H01M004-58

ICS **H01M004-04**; H01M010-40  
AB WO 200241416 A UPAB: 20030723  
NOVELTY - An **anode** comprises a **lithium** metal layer, and metal-lithium alloy layer. The metal-lithium alloy layer increases the **lithium** cycling efficiency and **anode** stability towards electrolyte components during storage of electrochemical cell.

DETAILED DESCRIPTION - INDEPENDENT CLAIMS are included for the following:

(a) An electrochemical cell or a battery cell comprising a positive electrode comprising electrochemically active material and electronically conductive material, a negative electrode or **anode** (100, 120, 130) comprising **lithium** layer with metal-lithium alloy layer, and an electrolyte solution (110);

(b) A method of forming a **lithium anode** with metal-**lithium alloy layer** (106) including **depositing a metal layer** on an outer **surface** of the lithium foil, alloying the lithium foil and metal layer on outer **surface** of lithium foil to form a metal-lithium layer, and forming a **surface** coating (108) on metal-lithium alloy layer.

USE - For electrochemical cell e.g., battery cell.

ADVANTAGE - The inventive anode includes a **surface** coating that is effective to increase **lithium** cycling efficiency and **anode** stability towards electrolyte during storage of electrochemical cell. It is capable of providing batteries having improved cycle life, increased shelf-life, and reduced voltage delay after initiation of battery discharge.

DESCRIPTION OF DRAWING(S) - The drawing shows a block diagram of the formation of aluminum-lithium alloy on the **surface** of the lithium foil.

Anode 100, 120, 130

Metal-lithium alloy layer 106

**Surface** coating 108

Electrolyte solution 110

Dwg.1/8

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B5B

EPI: X16-B01F; X16-E01

L109 ANSWER 5 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2002-291269 [33] WPIX

CR 2001-432627 [46]; 2001-475660 [51]

DNN N2002-227418 DNC C2002-085390

TI Anode formation for primary, secondary electrochemical cell, involves **depositing active layer** comprising lithium metal (foil) and multi-layer structure of single ion conducting layers and polymer layers on **substrate**.

DC A85 L03 P42 X16

IN AFFINITO, J; MIKHAYLIK, Y V; SHEEHAN, C J; SKOTHEIM, T A

PA (AFFI-I) AFFINITO J; (MIKH-I) MIKHAYLIK Y V; (SHEE-I) SHEEHAN C J; (SKOT-I) SKOTHEIM T A; (MOLT-N) MOLTECH CORP

CYC 97

PI US 2002012846 A1 20020131 (200233)\* 22p H01M004-40 <--

WO 2002095849 A2 20021128 (200280) EN H01M004-04 <--

RW: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ  
NL OA PT SD SE SL SZ TR TZ UG ZM ZW

W: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK  
DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR  
KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU

SD SE SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW  
ADT US 2002012846 A1 Provisional US 1999-167171P 19991123, CIP of US  
2000-721519 20001121, CIP of US 2000-721578 20001121, US 2001-864890  
20010523; WO 2002095849 A2 WO 2002-US16649 20020523  
PRAI US 1999-167171P 19991123; US 2000-721519 20001121; US 2000-721578  
20001121; US 2001-864890 20010523  
IC ICM H01M004-04; H01M004-40  
ICS B05D005-12; H01M004-66  
AB US2002012846 A UPAB: 20021212  
NOVELTY - Anode is formed by **depositing** active layer  
(10) comprising lithium metal or lithium metal foil and multi-layer  
structure (21) comprising 3 or more layers selected from single ion  
conducting layers (40,41) and polymer layers (30) on **substrate**.  
Structure (21) is formed by depositing polymer or a single ion conducting  
layer on layer (10) followed by deposition of another two layers  
**based** on preset condition.  
DETAILED DESCRIPTION - Anode is formed by **depositing** active  
layer (10) comprising lithium metal or a lithium metal foil and  
multi-layer structure (21) comprising three or more layers selected from  
single ion conducting layers (40,41) and polymer layers (30) on a  
**substrate**. Structure (21) is formed by depositing a first polymer  
or a single ion conducting layer on layer (10) followed by  
**deposition** of second layer comprising a single ion  
conducting layer if the first layer is a polymer, or a polymer layer if  
the first layer is a single ion conducting layer. A third layer comprising  
a single ion conducting layer if the second layer is a polymer, or a  
polymer layer if the second layer is a single ion conducting layer  
is **deposited** subsequently to form the anode.  
USE - For primary and secondary electrochemical cell  
ADVANTAGE - The electrochemical cell prepared using the anode  
favorable cycle characteristics.  
DESCRIPTION OF DRAWING(S) - The figure shows a sectional view of the  
anode.  
Lithium metal layer 10  
Multi-layer structure 21  
Polymer layer 30  
Single ion conducting layer 40,41  
Dwg.1/8  
FS CPI EPI GMPI  
FA AB; GI  
MC CPI: A11-B05; A12-E06A; L03-E01B5B  
EPI: X16-A02A; X16-B01F1; X16-E03A1; X16-E08A  
  
L109 ANSWER 6 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 2001-455987 [49] WPIX  
DNC C2001-137716  
TI Method of manufacturing **electrodes** for lithium  
secondary cell.  
DC A85 L03 X16  
IN CHOI, S G; PARK, C G; WALTER WAVNER, C G  
PA (SKCS-N) SKC CO LTD  
CYC 1  
PI KR 2001001828 A 20010105 (200149)\* 1p H01M004-64 <--  
ADT KR 2001001828 A KR 1999-21294 19990609  
PRAI KR 1999-21294 19990609  
IC ICM H01M004-64  
AB KR2001001828 A UPAB: 20010831  
NOVELTY - An **electrode** manufacturing method for a  
**lithium** secondary cell is provided to enhance adhering force  
between a current collecting layer and an activating layer while

protecting a **deposited metal layer** from damage.

DETAILED DESCRIPTION - An **electrode** for a **lithium** secondary cell is manufacture by compounding a current collecting material with an electrode active material. A carbon or plastic fiber mesh deposited with a conductive metal is used. The carbon or plastic fiber mesh is used as coated with a conductive metal. The **surface** of the current collecting material is coated for a pretreatment with a slurry in which a binder resin and conductive particles are dispersed into an organic solvent. The plastic fiber includes polyethylene, polypropylene and polyester. The conductive metal includes copper, aluminum, nickel or stainless steel. The conductive metal coating can be performed via a vacuum deposition.

Dwg.1/10

FS CPI EPI

FA AB; GI

MC CPI: A04-G02E4; A04-G03E; A05-E01B3; A11-B05D; A11-C04B1; A12-E06A;  
A12-S05X; L03-E01B5

EPI: X16-E08A

L109 ANSWER 7 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2001-432627 [46] WPIX

CR 2001-475660 [51]; 2002-291269 [33]

DNN N2001-320590 DNC C2001-130876

TI Preparation of anode of electrochemical cell includes **depositing** temporary protective **metal** layer on lithium metal layer.

DC A85 L03 X16

IN MIKHAYLIK, Y V; SHEEHAN, C J; SKOTHEIM, T A

PA (MOLT-N) MOLTECH CORP

CYC 95

PI WO 2001039303 A1 20010531 (200146)\* EN 41p H01M004-02 <--

RW: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ  
NL OA PT SD SE SL SZ TR TZ UG ZW

W: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CR CU CZ DE DK DM  
DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC  
LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE  
SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW

AU 2001017967 A 20010604 (200153) H01M004-02 <--

EP 1234348 A1 20020828 (200264) EN H01M004-02 <--

R: AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT  
RO SE SI

KR 2002059780 A 20020713 (200306) H01M004-02 <--

KR 2002059781 A 20020713 (200306) H01M004-02 <--

JP 2003515893 W 20030507 (200331) 44p H01M004-02 <--

CN 1415123 A 20030430 (200351) H01M004-02 <--

ADT WO 2001039303 A1 WO 2000-US32234 20001121; AU 2001017967 A AU 2001-17967  
20001121; EP 1234348 A1 EP 2000-980746 20001121, WO 2000-US32234 20001121;  
KR 2002059780 A KR 2002-706625 20020523; KR 2002059781 A KR 2002-706627  
20020523; JP 2003515893 W WO 2000-US32234 20001121, JP 2001-540870  
20001121; CN 1415123 A CN 2000-818173 20001121

FDT AU 2001017967 A Based on WO 2001039303; EP 1234348 A1 Based on WO  
2001039303; JP 2003515893 W Based on WO 2001039303

PRAI US 1999-167171P 19991123

IC ICM H01M004-02

ICS H01M002-16; H01M004-04; H01M004-60;

H01M004-66; H01M006-16; H01M010-40

AB WO 200139303 A UPAB: 20030808

NOVELTY - An anode of an electrochemical cell is prepared by depositing  
into a **substrate** a lithium **metal layer**, and  
**depositing** on the lithium metal layer a temporary protective metal

layer. The temporary protective metal is capable of forming an alloy with lithium metal or is capable of diffusing into the lithium metal.

DETAILED DESCRIPTION - INDEPENDENT CLAIMS are also included for:

(A) the anode;

(B) an electrochemical cell comprising a cathode comprising a cathode active material, the anode and a non-aqueous electrolyte interposed between the anode and the cathode; and

(C) formation of an electrochemical cell.

USE - Used in an electrochemical cell.

ADVANTAGE - The process allows increased ease of fabrication of cells, and produces cells with long life cycle and high energy density.

Dwg.0/0

FS CPI EPI

FA AB

MC CPI: A12-E06A; A12-E09; L03-E01B5

EPI: X16-E01C; X16-E08A

L109 ANSWER 8 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2000-465395 [40] WPIX

DNN N2000-347414 DNC C2000-140054

TI Multilayer electric current producing cell preparing method involves pressing multilayered subassembly of anode, separator and cathode to form prismatic subassembly.

DC A85 L03 X16

IN DODDS, C S; GERNOV, Y M; KANTO, E V; SKOTHEIM, T A; THIBAUT, W C; GERONOV, Y M

PA (MOLT-N) MOLTECH CORP; (DODD-I) DODDS C S; (GERN-I) GERNOV Y M; (KANT-I) KANTO E V; (SKOT-I) SKOTHEIM T A; (THIB-I) THIBAUT W C

CYC 89

PI WO 2000036678 A2 20000622 (200040)\* EN 76p H01M006-04

RW: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW NL  
OA PT SD SE SL SZ TZ UG ZW

W: AL AM AT AU AZ BA BB BG BR BY CA CH CN CR CU CZ DE DK DM EE ES FI  
GB GD GE GH GM HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT  
LU LV MA MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ  
TM TR TT TZ UA UG US UZ VN YU ZA ZW

AU 2000021935 A 20000703 (200046) H01M006-04

US 6190426 B1 20010220 (200112) H01M010-38

US 2001003863 A1 20010621 (200137) H01M010-04

ADT WO 2000036678 A2 WO 1999-US30133 19991216; AU 2000021935 A AU 2000-21935 19991216; US 6190426 B1 US 1998-215030 19981217; US 2001003863 A1 Div ex US 1998-215030 19981217, US 2001-771079 20010125

FDT AU 2000021935 A Based on WO 2000036678; US 2001003863 A1 Div ex US 6190426

PRAI US 1998-215030 19981217; US 2001-771079 20010125

IC ICM H01M006-04; H01M010-04; H01M010-38

ICS H01M004-40; H01M004-58

AB WO 200036678 A UPAB: 20000823

NOVELTY - A separator (6) is interposed between an **anode** having a **lithium** active material and a solid composite cathode. This arrangement is wound on a mandrel to form a rounded anode separator-solid composite subassembly. The mandrel is then removed and the subassembly pressed to form a prismatic subassembly. After removing it is contacted with the lithium salt electrolyte to form a cell stack.

DETAILED DESCRIPTION - The cell stack is then enclosed in a barrier metal film and seated to form a casing. The film is a laminar combination of anode, separator and solid composite cathode comprising cathode active material. The cathode has two opposing **surface** and non-permeable current collector in contact with one **surface** of cathode active layer. The anode and cathode active layer are positioned in face to face relationship. The laminar combination is wound on a round mandrel having a

circumference selected preferably from length of 140-200% or 150-195% or 160-190% of difference between external length dimension and external thickness dimension of prismatic cell stack. Anode and cathode tabs are attached to lithium metal layer of anode active layer and current collector of composite cathode. The laminar combination is wound to form a rounded shaped anode separator solid composite cathode subassembly having a jelly roll configuration. After compressing the cell stack it is sealed in a film to form a casing. The rounded subassembly is shaped into a form that is intermediate between rounded shape and prismatic shape. The intermediate form comprises a pre-fold edge. The anode tabs and cathode tabs are extended from the prismatic cell stack to the casing in an electrically insulated relationship with respect to each other and to casing. The extensions of lithium metal layer are placed in electrical contact by ultrasonic welding. The anode and cathode comprises a non-permeable current collector which comprises conductive layer selected from a group consisting of conductive metals, coatings comprising conductive metal pigments, conductive carbons and conductive metal oxide pigments. The conductive layer of non-permeable current collector is in contact with an insulating layer. A metallic layer is deposited in electrical contact with the conductive layer at all anode contact edges, by metal screen. The conductive metal foil of current collector of cathode extends beyond the corresponding edges of anode and separator to form a conductive coil extension and all the extensions are placed in an electrical contact by ultrasonic welding. The prismatic subassembly of battery is formed by pressing the rounded subassembly in a press. The pressure is preferably in the range of 100-6000 kPa or 200-5000 kPa or 200-3500 kPa. The prismatic subassembly is contacted with the source of liquid non-aqueous lithium salt electrolyte to form prismatic cell stack utilizing a vacuum back fill procedure. The procedure involves placing the prismatic subassembly in a container, subjecting the container to vacuum for specific time, contacting the subassembly with electrolyte and continuing contacting of subassembly for total time period. The total period is preferably in the range of 0.01-50 hours or 0.02-25 hours or 0.02-2 hours and/or 0.01-50 hours. During formation of the prismatic cell stack, a strip of material is wound around the circumference assembly to maintain two substantially parallel flat surfaces. Before packing the stack the material is removed and excess electrolyte on outer surface of cell stack is also removed. An INDEPENDENT CLAIM is also included for multilayered electric current producing cell comprising a casing and prismatic cell stack comprising anode, cathode and separator in between, the area of the anode active layer is greater than or equal to 1000 cm<sup>2</sup>. The ratio of the area of the anode active layer to the volume of cell stack is greater than 60 cm<sup>-1</sup>

USE - For production of prismatic cells that generates an electric current.

ADVANTAGE - Since excess amount of electrolyte introduced into the prismatic cell is reduced, the mechanical stress that damage the multilayers of prismatic cell is also reduced.

DESCRIPTION OF DRAWING(S) - The figure shows the mandrel shape and jelly roll configuration of a prismatic cell.

separator 6

cathode active layer 8

non-permeable cathode current collector 10

mandrel 24

anode-separator-solid composite cathode subassembly 50

anode 52

Dwg. 4/10

FS CPI EPI

FA AB; GI

MC CPI: A12-E06A; L03-E02; L03-E03  
EPI: X16-A02A; X16-B01F1; X16-E01C; X16-F02

L109 ANSWER 9 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2000-072273 [06] WPIX

DNN N2000-056559 DNC C2000-020606

TI Fabrication of active metal electrode used as negative **electrodes**  
in batteries such as **lithium electrodes** in  
**lithium-** sulfur batteries.

DC A85 L03 X16

IN TSANG, F Y; VISCO, S J

PA (POLY-N) POLYPLUS BATTERY CO; (POLY-N) POLYPLUS BATTERY CO INC; (POLY-N)  
POLYPLUS BATTERY CO LTD

CYC 86

PI WO 9957770 A1 19991111 (200006)\* EN 33p H01M004-02 <--  
RW: AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW NL  
OA PT SD SE SL SZ UG ZW  
W: AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GD  
GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV  
MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT  
UA UG US UZ VN YU ZA ZW

AU 9933713 A 19991123 (200016)

US 6214061 B1 20010410 (200122) H01M004-04 <--

EP 1093672 A1 20010425 (200124) EN H01M004-02 <--

R: AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT  
RO SE SI

BR 9910109 A 20011009 (200168) H01M004-02 <--

KR 2001043145 A 20010525 (200168) H01M004-02 <--

MX 2000010743 A1 20010401 (200171) H01M010-40

CN 1307731 A 20010808 (200173) H01M004-02 <--

AU 745287 B 20020321 (200233) H01M004-02 <--

JP 2002513991 W 20020514 (200236) 40p H01M004-04 <--

US 6432584 B1 20020813 (200255) H01M004-08 <--

ADT WO 9957770 A1 WO 1999-US6895 19990329; AU 9933713 A AU 1999-33713  
19990329; US 6214061 B1 Provisional US 1998-83947P 19980501, US  
1998-139601 19980825; EP 1093672 A1 EP 1999-915119 19990329, WO  
1999-US6895 19990329; BR 9910109 A BR 1999-10109 19990329, WO 1999-US6895  
19990329; KR 2001043145 A KR 2000-712042 20001030; MX 2000010743 A1 MX  
2000-10743 20001101; CN 1307731 A CN 1999-808029 19990329; AU 745287 B AU  
1999-33713 19990329; JP 2002513991 W WO 1999-US6895 19990329, JP  
2000-547661 19990329; US 6432584 B1 Provisional US 1998-83947P 19980501,  
Cont of US 1998-139601 19980825, US 2000-678063 20001002

FDT AU 9933713 A Based on WO 9957770; EP 1093672 A1 Based on WO 9957770; BR  
9910109 A Based on WO 9957770; AU 745287 B Previous Publ. AU 9933713,  
Based on WO 9957770; JP 2002513991 W Based on WO 9957770

PRAI US 1998-139601 19980825; US 1998-83947P 19980501; US 2000-678063  
20001002

IC ICM H01M004-02; H01M004-04; H01M004-08;  
H01M010-40

ICS H01M004-40

AB WO 9957770 A UPAB: 20000203

NOVELTY - A glassy or amorphous protective layer impervious and conductive  
to active metal ions is formed on a **substrate**. A first active  
**metal layer** is **deposited** on the protective  
layer and a current collector (208) is provided on the first active metal  
layer, forming an active metal electrode.

DETAILED DESCRIPTION - INDEPENDENT CLAIMS are also included for the  
following:

- (i) a battery comprising the active metal electrode;
- (ii) a partially fabricated battery cell essentially consisting of a

current collector, a glassy or amorphous protective layer, an active metal layer provided between the current collector and the protective layer and a gel or solid electrolyte provided on the protective layer; and

(iii) a battery cell comprising the partially fabricated battery cell.

USE - Used as **lithium electrodes** in **lithium-sulfur batteries** (claimed), negative **electrodes** for primary batteries such as lithium manganese dioxide batteries, lithium (CF)X batteries, lithium thionyl chloride batteries, lithium sulfur dioxide batteries, lithium iron sulfide batteries (Li/FeS<sub>2</sub>), lithium polyaniline batteries and lithium iodine batteries, secondary batteries such as lithium-sulfur batteries, lithium cobalt oxide batteries, lithium nickel oxide batteries, lithium manganese oxide batteries and lithium vanadium oxide batteries, other rechargeable batteries employing active metals other than **lithium**. Also used as negative **electrodes** and electrode- electrolyte laminates, solid state electrolyte separators such as sodium beta-alumina glass or ceramic, polymeric electrolytes, porous membranes etc.

ADVANTAGE - The protective layer on the negative electrode prevents the positive and negative electrodes from contacting one another and serves the function of separator. The protective layer is tough, thick and made from a material that resists cracking and abrasion. A high quality protective layer which is smooth, continuous and free of pores or defects is provided on the **substrate**. The protective layer is chemically stable to the electrolyte within the voltage window of the cell and is conductive to lithium ion. The protective layer is impervious to moisture, carbon dioxide, oxygen and the **lithium electrode** can be handled under ambient conditions without the need of dry box conditions as typically employed to process other **lithium electrodes**. The protective layer provides a good protection for the lithium and imparts long shelf life of the **electrode** and electrolyte composites. The **lithium metal electrode** manufactured has a longer cycle life and better safety characteristics. The protective layer formed on the **substrate** prevents formation of dendrites and mossy deposits. The batteries having the active metal electrode does not require a carbon intercalation matrix to support lithium ions. The batteries possess a high energy density than a conventional lithium ion cell. The lithium metal batteries do not have a large irreversible capacity loss associated with the formation of lithium ion batteries. The battery cells obtained using the active electrode is rechargeable.

DESCRIPTION OF DRAWING(S) - The figure shows the schematic illustration of a **lithium electrode**.

partially fabricated **lithium electrode** 200

current collector laminate 202

current collector 208

electrolyte laminate; 254

electrolyte layer 256

glass layer 258

web carrier 262

Dwg.2b/3

FS CPI EPI

FA AB; GI

MC CPI: A12-E06; L03-E01B5

EPI: X16-A02A; X16-B01F1; X16-E03A1; X16-E08A

L109 ANSWER 10 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1999-302534 [25] WPIX

DNN N1999-226665 DNC C1999-088691

TI Formation of vanadium oxide film on **substrate** used as

**cathode** in lithium-ion battery.

DC E12 E31 L03 X16  
 IN BENSON, D K; LIU, P; TRACY, C E; TURNER, J A; ZHANG, J  
 PA (MIDE) MIDWEST RES INST; (BENS-I) BENSON D K; (LIUP-I) LIU P; (TRAC-I)  
 TRACY C E; (TURN-I) TURNER J A; (ZHAN-I) ZHANG J  
 CYC 79  
 PI WO 9919534 A1 19990422 (199925)\* EN 29p C23C016-40  
 RW: AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE  
 W: AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GE  
 GH GM HR HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG  
 MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG  
 UZ VN YU ZW  
 AU 9910772 A 19990503 (199937) C23C016-40  
 US 6156395 A 20001205 (200066) C23C016-40  
 US 2003022065 A1 20030130 (200311) H01M004-48 <--  
 ADT WO 9919534 A1 WO 1998-US21434 19981009; AU 9910772 A AU 1999-10772  
 19981009; US 6156395 A Cont of US 1997-948832 19971010, US 1999-325146  
 19990603; US 2003022065 A1 Cont of US 1997-948832 19971010, Div ex US  
 1999-325146 19990603, Div ex US 2000-715531 20001117, US 2002-180861  
 20021004  
 FDT AU 9910772 A Based on WO 9919534; US 2003022065 A1 Div ex US 6156395  
 PRAI US 1997-948832 19971010; US 1999-325146 19990603; US 2000-715531  
 20001117; US 2002-180861 20021004  
 IC ICM C23C016-40; H01M004-48  
 ICS C01G031-02  
 AB WO 9919534 A UPAB: 20011203  
 NOVELTY - Process comprises forming a feed gas of vanadium-containing  
 precursor with inert gas, oxygen and hydrogen under specified conditions,  
 feeding to reaction chamber containing **substrate**, generating RF  
 plasma within the chamber and continuously removing the by-produced gas.  
 DETAILED DESCRIPTION - Formation of a vanadium oxide film on a  
**substrate** used as a **cathode** in a lithium-ion  
 battery using a plasma enhanced chemical vapor deposition, comprises:  
 (i) positioning a **substrate** within the plasma reaction  
 chamber at room temperature;  
 (ii) forming a precursor gas of a reactive, vanadium-containing  
 precursor in an inert carrier gas and maintaining at -23 to 127 deg. C and  
 1-760 torr;  
 (iii) forming a feed gas mixture by combining the precursor gas with  
 oxygen gas and hydrogen gas, and flowing into reaction chamber, the  
 precursor gas, oxygen gas and hydrogen gas having predetermined flow  
 rates;  
 (iv) generating an RF plasma within the reaction chamber to effect a  
 chemical reaction to effect a chemical reaction to cause  
**deposition** of a **vanadium** oxide film and formation of a  
 by-product gas at room temperature, the predetermined flow rate of  
 hydrogen gas being sufficient to provide hydrogen gas for reacting with  
 the vanadium-containing precursor to form the vanadium oxide film without  
 reducing the vanadium oxide film; and  
 (v) continuously removing the by-product gas from the chamber.  
 USE - Used for forming a **cathode** in a lithium-ion  
 battery using a plasma enhanced chemical vapor deposition.  
 ADVANTAGE - The vanadium oxide thin-film layer has high charge  
 capacity and cyclic stability. Process is economic process for producing  
 vanadium oxide thin-films for specific use in lithium rechargeable  
 batteries. The deposition rates of these film is higher than previously  
 but films are produced with high charge/discharge, high stability and high  
 energy density.  
 DESCRIPTION OF DRAWING(S) - Figure 1 is a schematic of a PECVD system  
 for forming vanadium oxide thin films.

PECVD System 10  
     Reaction Chamber 12  
 RF Plasma 14  
 Pump 16  
 Lower Plate 18  
     **Substrate** 20  
         Vanadium Oxide Film 22  
 Upper Plate 24  
 Control Panel 26  
     Reactive Precursor Source 28  
     Inert Carrier Gas Source 30  
     Flow Regulator Valve 32  
 Precursor Gas 34  
     Temperature Controller 36  
     Oxygen Gas Source 38  
     Flow Regulator Valve(42) Oxygen Gas 40  
     Hydrogen Gas Source 44  
     Flow Regulator Valve 46  
 Hydrogen Gas 48  
 Dwg.1/8  
 FS CPI EPI  
 FA AB; GI; DCN  
 MC CPI: E35-N; L03-E01B5  
     EPI: X16-E08A

L109 ANSWER 11 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 1997-542129 [50] WPIX

DNN N1997-451462 DNC C1997-173218

TI **Lithium** secondary battery - has **cathode** active  
 material coating layer in which occlusion/release of lithium ion is  
 possible, on nickel **coating** which is **deposited** over  
**copper ( alloy) base** material.

DC L03 X16

PA (FJIC) FUJI ELECTROCHEMICAL CO LTD

CYC 1

PI JP 09259866 A 19971003 (199750)\* 5p H01M004-02 <--

ADT JP 09259866 A JP 1996-59796 19960315

PRAI JP 1996-59796 19960315

IC ICM **H01M004-02**

ICS **H01M004-66**; H01M010-40

AB JP 09259866 A UPAB: 19971217

The battery has a sheet like anode and cathode (2,4) separated by  
 a separator (6) which together constitutes an electrode group (8) is  
 placed inside a cathode side can (10). A non aqueous electrolyte (12) is  
 injected into the can which has a gasket (14) at the opening edge. Then,  
 the can is sealed with a anode plate (16). The cathode has a  
**nickel deposit** over a **base** material made of  
 copper or a copper **alloy**. The **nickel deposit**  
 is **coated** with a cathode active material layer in  
 which occlusion/release of lithium ions is possible.

ADVANTAGE - Improves capacitance/maintenance property of battery.  
 Prevents alloy formation in **base** material when active material  
 layer occludes **lithium** ion on negative **electrode**  
 material coating.

Dwg.1/3

FS CPI EPI

FA AB; GI

MC CPI: L03-E01B5

EPI: X16-E08A

L109 ANSWER 12 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
 AN 1994-326186 [41] WPIX  
 DNC C1994-148292  
 TI **Electrode**, pref. for a secondary lithium cell -  
 comprises a support having a plastic network **substrate** with open  
 cells with a metal layer on the network **surface** and a supported  
 active material.  
 DC A85 L03 M13  
 IN IKEDA, H; KUBO, M; OKUDA, J  
 PA (UEMU) UEMURA & CO LTD C; (UEMU) UEMURA KOGYO KK  
 CYC 9  
 PI EP 621648 A2 19941026 (199441)\* EN 13p H01M004-80 <--  
 R: CH DE FR GB IT LI NL  
 JP 06349481 A 19941222 (199510) 7p H01M004-02 <--  
 US 5434024 A 19950718 (199534) 11p H01M004-72 <--  
 EP 621648 A3 19950524 (199546) H01M004-80 <--  
 EP 621648 B1 19990331 (199917) EN H01M004-80 <--  
 R: DE FR GB IT  
 DE 69324238 E 19990506 (199924) H01M004-80 <--  
 JP 3427435 B2 20030714 (200347) 7p H01M004-02 <--  
 ADT EP 621648 A2 EP 1993-305937 19930727; JP 06349481 A JP 1993-228172  
 19930820; US 5434024 A US 1993-93921 19930721; EP 621648 A3 EP 1993-305937  
 19930727; EP 621648 B1 EP 1993-305937 19930727; DE 69324238 E DE  
 1993-624238 19930727, EP 1993-305937 19930727; JP 3427435 B2 JP  
 1993-228172 19930820  
 FDT DE 69324238 E Based on EP 621648; JP 3427435 B2 Previous Publ. JP 06349481  
 PRAI JP 1993-111105 19930414  
 REP DE 2017702; DE 3919570; EP 151064; EP 392082; GB 115961; GB 762670  
 IC ICM H01M004-02; H01M004-72; H01M004-80  
 ICS C23C014-00; C23C014-04; C23C014-20; C23C014-32; C25B011-03;  
 H01M004-66; H01M010-40  
 AB EP 621648 A UPAB: 19941206  
 In an embodiment, the plastic network **substrate** is removed. The  
 metal **layer** is pref. **deposited** by vapour phase  
 plating, esp. arc ion plating. A prefd. metal is Al. Secondary cell  
 includes the above electrode as positive electrode.  
 In an example Al is arc ion plated onto a polyurethane foam plate of  
 thickness 2 mm at pressure 10 -4 torr, arc current 100 AH and time 20  
 mins. A 10 micron Al film covers the entire foam lattice **surface**  
 . The lattice may then be filled with an active mixt. of e.g. MnO2, Li,  
 PVA and C powder.  
 ADVANTAGE - Electrode support structure provides good adhesion to  
 active material and uses low amts. of conductive material and binder,  
 resulting in improved cell charge/discharge performance.  
 Dwg.0/9  
 FS CPI  
 FA AB; GI  
 MC CPI: A12-E06A; L03-E01B5; M13-F03

L109 ANSWER 13 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
 AN 1992-164076 [20] WPIX  
 DNN N2000-041807 DNC C2000-014059  
 TI Non-aqueous electrolyte secondary battery for communication apparatus -  
 has anode obtained by coating anode active material at specific portions  
 of **metal deposition film** formed on plastic  
**substrate**.  
 DC L03 X16  
 PA (MITQ) MITSUBISHI ELECTRIC CORP  
 CYC 1  
 PI JP 04104478 A 19920406 (199220)\* 4p

JP 2987178 B2 19991206 (200005)B 3p H01M010-40  
ADT JP 04104478 A JP 1990-222066 19900821; JP 2987178 B2 JP 1990-222066  
19900821  
FDT JP 2987178 B2 Previous Publ. JP 04104478  
PRAI JP 1990-222066 19900821  
IC **H01M004-02**; H01M010-40  
ICM H01M010-40  
ICS H01M002-34; **H01M004-02**  
AB JP 2987178 B UPAB: 20000128 ABEQ treated as Basic  
NOVELTY - A **cathode** plate (6) made of **lithium** and a  
rechargeable **anode** plate are wound with a separator (4)  
inbetween. The anode plate is a plastic **substrate** (1) with  
**metal deposition film** (2) on one side. Anode  
active material (3) is coated on the film at specific portions by fixed  
pattern.  
USE - For power supply in communication apparatus.  
ADVANTAGE - Generation of short circuit is eliminated. Capacity and  
charging-discharging cycle are improved. DESCRIPTION OF DRAWING(S) - The  
figure shows principal portion of battery. (1) Plastic **substrate**  
; (2) **Metal deposition film**; (3) Anode  
active material; (4) Separator; (6) Cathode plate.  
Dwg.1/3  
AB JP 04104478 A UPAB: 20000228  
NOVELTY - A **cathode** plate (6) made of **lithium** and a  
rechargeable **anode** plate are wound with a separator (4)  
inbetween. The anode plate is a plastic **substrate** (1) with  
**metal deposition film** (2) on one side. Anode  
active material (3) is coated on the film at specific portions by fixed  
pattern.  
USE - For power supply in communication apparatus.  
ADVANTAGE - Generation of short circuit is eliminated. Capacity and  
charging-discharging cycle are improved. DESCRIPTION OF DRAWING(S) - The  
figure shows principal portion of battery. (1) Plastic **substrate**  
; (2) **Metal deposition film**; (3) Anode  
active material; (4) Separator; (6) Cathode plate.  
Dwg.1/3  
FS CPI EPI  
FA AB; GI  
MC CPI: L03-E01B; L03-E03  
EPI: X16-B01F1; X16-E01  
  
L109 ANSWER 14 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1990-190371 [25] WPIX  
TI **Lithium** secondary battery - has **cathode** consisting of  
graphite **layer deposited** on **iron**  
**substrate** NoAbstract Dwg 1/3.  
DC L03 X16  
PA (SHAF) SHARP KK  
CYC 1  
PI JP 02126573 A 19900515 (199025)\*  
ADT JP 02126573 A JP 1988-280870 19881107  
PRAI JP 1988-280870 19881107  
IC **H01M004-02**; H01M010-40  
FS CPI EPI  
FA NOAB; GI  
MC CPI: L03-E01B3  
EPI: X16-B01X  
  
L109 ANSWER 15 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1989-009856 [02] WPIX

DNN N1989-007521 DNC C1989-004567  
TI Assembling constituents of electrochemical generator - **based on**  
thin films of lithium or its alloy and of polymeric electrolyte.  
DC A85 L03 P51 P73 X16  
IN BELANGER, A; GAUTHIER, M  
PA (HYDR-N) HYDRO QUEBEC; (ERAP) SOC NAT ELF AQUITAINE; (HYDR-N) HYDRO-QUEBEC  
CYC 16  
PI EP 298801 A 19890111 (198902)\* FR 7p  
R: AT BE CH DE ES FR GB GR IT LI LU NL SE  
WO 8810517 A 19881229 (198903) FR  
W: JP US  
FR 2616971 A 19881223 (198907)  
JP 01503661 W 19891207 (199004)  
US 4897917 A 19900206 (199012) 6p  
EP 298801 B 19920318 (199212) 8p  
R: AT BE CH DE ES FR GB IT LI LU NL SE  
DE 3869243 G 19920423 (199218)  
ES 2031256 T3 19921201 (199301) H01M004-02 <--  
CA 1326261 C 19940118 (199409) FR H01M004-02 <--  
JP 2839520 B2 19981216 (199904) 6p H01M006-18  
ADT EP 298801 A EP 1988-401494 19880616; WO 8810517 A WO 1986-FR313 19860616;  
FR 2616971 A FR 1987-8542 19870618; JP 01503661 W JP 1989-505446 19890217;  
US 4897917 A US 1988-218243 19880713; EP 298801 B EP 1988-401494 19880616;  
ES 2031256 T3 EP 1988-401494 19880616; CA 1326261 C CA 1988-569784  
19880617; JP 2839520 B2 JP 1988-505446 19880616, WO 1988-FR313 19880616  
FDT ES 2031256 T3 Based on EP 298801; JP 2839520 B2 Previous Publ. JP  
01503661, Based on WO 8810517  
PRAI FR 1987-8542 19870618  
REP 2.Jnl.Ref; EP 13199; EP 143566; EP 146245; EP 147929; GB 2148586; JP  
60049573; US 4621035  
IC ICM H01M004-02; H01M006-18  
ICS B21B009-00; B32B007-06; H01M004-12; H01M010-38  
AB EP 298801 A UPAB: 19930923  
The constituents, comprising thin film negative **electrode**  
**based on Li** or **Li** alloy and component  
comprising at least one thin film of a polymeric electrolyte conductive  
through Li ions, are assembled by (1) using as precursor for the negative  
electrode an intermediary assembly formed from thin film of Li or Li alloy  
supported on film of inert plastic material having adhesion to Li such to  
allow manipulation of the intermediary assembly but less than that of the  
**Li-based** film to the solid polymeric electrolyte; (2) applying  
free metallic face of intermediary assembly to the polymeric electrolyte  
at temp. and under pressure such that Li of intermediary assembly adheres  
to the electrolyte. Opt. the plastic film with Li is sepd. partly or  
completely by peeling.  
ADVANTAGE - Thin **Li** film-based negative  
**electrode** is more readily handled, positioned, and aligned.  
0/0  
FS CPI EPI GMPI  
FA AB  
MC CPI: A12-E09; L03-E01C  
EPI: X16-A02A; X16-E03  
L109 ANSWER 16 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1987-208461 [30] WPIX  
TI Long life alloy **electrode base** for lithium  
storage battery - comprises aluminium **film deposited**  
on iridium or tin sheet NoAbstract NoDwg.  
DC L03 X16  
PA (KAOS) KAO CORP

CYC 1  
PI JP 62031950 A 19870210 (198730)\*  
ADT JP 62031950 A JP 1985-169512 19850731  
PRAI JP 1985-169512 19850731  
IC **H01M004-40**  
FS CPI EPI  
FA NOAB  
MC CPI: L03-E01B8  
EPI: X16-B01X; X16-E01

L109 ANSWER 17 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1984-088432 [14] WPIX  
DNN N1984-066106 DNC C1984-037702  
TI Current collector for sulphide contg. positive electrode - for electrochemical cell, has **surface** reacting with sulphur at cell voltage.  
DC L03 X16 X21  
IN BARTHOLME, L G; SHIMOTAKE, H  
PA (USAT) US DEPT ENERGY  
CYC 1

PI US 424112 A0 19840103 (198414)\* 17p  
US 4440837 A 19840403 (198416)  
ADT US 424112 A0 US 1982-424112 19820927  
PRAI US 1982-424112 19820927  
IC **H01M004-52**; H01M006-36  
AB US N6424112 N UPAB: 20011211

The current collector consists of a **base** metal of Cu, Ag, Au, Al or alloys, coated with Fe, Ni, Cr or alloys. When subjected to cell voltages, an S-contg. cpd. forms at the current collector **surface** protecting it from further S attack during operation. The cell is of the type having e.g. an Fe sulphide positive electrode; a negative **electrode**, e.g. Li-Al alloy; and a molten salt electrolyte contg. alkali and/or alkaline earth metal halides, e.g. LiCl-KCl eutectic, contacting positive and negative electrodes.

The high temp. sec. cells are useful for e.g. electric automobiles, energy storage. The collector provides low cell resistance and uniform current distribution throughout the cycle, even for electrode areas exceeding 35 in.<sup>2</sup>/side, e.g. 150 in.<sup>2</sup>/side. Cells using the collector (Fe collector) had specific power at 50% discharge 89(83)W/kg and specific energy 79.3 (73.1) V hr./ kg.

Dwg.0/1

FS CPI EPI  
FA AB  
MC CPI: L03-E01B  
EPI: X16-E02; X21-B01

L109 ANSWER 18 OF 18 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN  
AN 1978-46623A [26] WPIX  
TI Lattice for lead storage battery electrode - made of lead alloy with lithium **deposited** on and diffused into **surface** layers.  
DC L03 M26 X16  
PA (MATU) MATSUSHITA ELEC IND CO LTD  
CYC 1  
PI JP 53055745 A 19780520 (197826)\*  
PRAI JP 1976-130761 19761029  
IC **H01M004-68**  
AB JP 53055745 A UPAB: 19930901

The lattice for a lead storage battery exhibits excellent self discharge rate and improved service life at overdischarge cycle.

For example, an alloy comprising 4.5 wt.% Sb, 0.3 wt.% As and balance Pb, or an alloy comprising 0.1 wt.% Ca and balance Pb is used. Li is vacuum deposited on the **surface** of the Pb alloy lattice at is approx. 900 degrees C under reduced pressure to a thickness of 0.1-0.3 mu. The lattice is then heated at is approx. 250 degrees C for is approx. 15 min. in an inert gas to promote the dispersion of Li into the Pb alloy lattice body. Suitable paste-like active material is adhered to the lattice by conventional methods to form a Pb electrode.

FS CPI EPI  
FA AB  
MC CPI: L03-E01B1; M26-B04